

2X2AMPGRN1S64SVC - Amplified Drop Ceiling "Green" Speakers on a 2X2 Metal Tile

The OWI **2X2AMPGRN1S64SVC** is a self powered speaker/amplifier (AMP1SGRN) combined with three non-powered (2X2IC6NA) speakers on 2X2 Metal Tiles and Backcans assembly with a Volume Control model AMPSTVCW. It is UL Listed, Energy Verified, Energy Star audio product. This unit can drive up to four speakers connected series parallel to have a net impedance of 8 ohms. With an included UL Listed, **Level 5**(Energy Star), 15 volt, 3.5 ampere power supply, the amplifier can output 32 watts, or 8 watts per speaker in a four speaker hook-up.



Features:

- Self-Powered "Green" Speaker on a 2X2 Metal Tile
- UL and Energy Star Listed
- 15V DC, UL Listed, Level 5 (Energy Star) Rated Power Supply
- 2 x 16 or Total 32 Watts Max Power
- Three Audio Inputs
- Priority Override Feature
- Balanced Line Level Output
- Self Test Feature
- RS232 Controllable Supervision
- Stereo/Mono Volume Control Included
- Infrared Wireless Microphone Auxiliary Input
- Speaker Combination Program Available

Touchboards

205 Westwood Ave, Long Branch, NJ 07740
Phone: 866-94 BOARDS (26273) / (732)-222-1511
Fax: (732)-222-7088 | E-mail: sales@touchboards.com

Available in the following complete install packages:

- [2X2AMPGRN1S61](#) - Single speaker combination with a 2x2 metal tile, backcans
- [2X2AMPGRN1S61SVC](#) - Single speaker combination with a 2x2 metal tile, backcans and volume control
- [2X2AMPGRN1S62](#) - Two speaker combination with a 2x2 metal tile, backcans
- [2X2AMPGRN1S62SVC](#) - Two speaker combination with a 2x2 metal tile, backcans and volume control
- [2X2AMPGRN1S64](#) - Four speaker combination with a 2x2 metal tile, backcans

