

Eiki 3279A

Cassette Recorder /Player

KEY FEATURES

Record level led indicator Automatic level control 3-digit, 2X tape counter Built-in Electret microphone Auxiliary Input jack (3.5mm) Remote Mic. Jack (3.5mm) Remote pause jack (2.46mm)



OPTIONAL ACCESSORIES

Standard headset Remote control microphone 3279A

date of original purchase for

parts and labour.

Specifications

Туре	Portable AC/battery recorder player	Signal To Noise Ratio	40dB
Frequency Response	125Hz to 8 KHz	Audio: Output	Speakers 100mm (4") round x 1
Wow & Flutter	0.30%	Speaker Jacks	1/4", 4 Ohm x 1
Battery or AC Operation	AC/DC (6"C")	Dimensions (H x W x D)	2.75" x 11.5" x 7.125
Remote Microphone Jack	1/8" (3.5mm x 1)	Weight	4 lbs.
Auxilary Input Jack	1/8" (3.5mm x 1)	Packaged Weight	2,49 kg without batteries
Remote Pause	1/10" (2.46 mm) x 1	Power Requirements	AC 120 Volts, 60Hz, DC 12 Volts (6 "C" size batteries)
Headset Jacks	½" x 4		(0 C Size batteries)
Audio Output:	Amplifier 1 Watts RMS (D.H.T. 5%)	Power Consumption	10 W approximately
		Safety Compliance	UL Listed
		Warranty - Unit	1-Year limited warranty from

Specifications subject to change without notice. ©2002 Eiki International, Inc. Issued June 12, 2001.

Eiki International, Inc., 30251 Esperanza, Rancho Santa Margarita, CA 92688-2132. Tel: 800-242-3454; Fax: 800-457-3454, E-mail: usa@eiki.com In Canada: 310 First St., Unit 2, P.O. Box 156, Midland, ON L4R 4K8. Tel: 800-563-3454, Fax: 800-567-4069, E-mail: infocanada@eiki.com Fax-on-Demand: (Toll Free) 877-345-4329 Visit our World Wide Web site: http://www.eiki.com

