



Safety Data Sheet

according to WHMIS 2023 and HCS 2024

Page 1/12

Date of issue 03/13/2025

Version number 9.01

Revision: 03/13/2025

1 Identification

· Product identifier

· Trade name: 419D

· Other Means of Identification: Acrylic Conformal Coating

· Related Part Number: 419D-Liquid, 419D-55ML, 419D-1L, 419D-4L, 419D-20L, 419D-200ML

· Application of the substance / the mixture Conformal Coating

· Uses advised against Not available

· Details of the supplier of the safety data sheet

Manufacturer/Supplier:

MG Chemicals (Head Office)
1210 Corporate Drive
Burlington, Ontario L7L 5R6
CANADA
+(1) 800-340-0772
+(1) 905-331-1396
info@mgchemicals.com

Distributor:

Mouser Electronics
1000 North Main Street
Mansfield, TX 76063
USA
+(1) 817-804-3800

· Information department: sds@mgchemicals.com

· Emergency telephone number:

For hazardous material incidents ONLY (leaks, spills, fires, exposures or accidents)
USA or CANADA-Call Verisk 3E at +1-866-519-4752 or +1-760-476-3962 (Service access code: 335388)

For emergencies involving the transport of dangerous goods; 24/7 service
CANADA-Call CANUTEC collect at +1-613-996-6666 or *666 on cellular phones

2 Hazard identification

· Classification of the substance or mixture

Flammable liquids – Category 2

H225 Highly flammable liquid and vapour.

Eye damage/irritation – Category 2A

H319 Causes serious eye irritation.

Specific target organ toxicity (single exposure) – Category 3
H336 May cause drowsiness or dizziness.

· Label elements

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

—CA—

Safety Data Sheet

according to WHMIS 2023 and HCS 2024

Page 2/12

Date of issue 03/13/2025

Version number 9.01

Revision: 03/13/2025

Trade name: 419D

(Contd. of page 1)

Hazard pictograms



GHS02 GHS07

Signal word Danger

Hazard-determining components of labeling:

n-butyl acetate

Butan-2-one

Hazard statements

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Precautionary statements

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 Keep container tightly closed.

P240 Ground and bond container and receiving equipment.

P241 Use explosion-proof electrical equipment.

P243 Take action to prevent static discharges.

P261 Avoid breathing mist, vapors or spray.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves, protective clothing, and eye protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P312 Call a POISON CENTER/doctor if you feel unwell.

P337+P313 If eye irritation persists: Get medical advice.

P370+P378 In case of fire: Use CO₂, powder or water spray to extinguish.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents and container in accordance with local, regional, and national regulations.

Other hazards Repeated exposure may cause skin dryness or cracking.

3 Composition/Information on ingredients

Chemical characterization: Mixtures

Description: Mixture of the substances listed below with nonhazardous additions.

Dangerous components:

123-86-4	n-butyl acetate	55% w/w
----------	-----------------	---------

(Contd. on page 3)

CA

Safety Data Sheet

according to WHMIS 2023 and HCS 2024

Page 3/12

Date of issue 03/13/2025

Version number 9.01

Revision: 03/13/2025

Trade name: 419D

(Contd. of page 2)		
78-93-3	Butan-2-one	15% w/w
80-62-6	methyl methacrylate	<0.1% w/w
97-88-1	n-butyl methacrylate	<0.1% w/w

4 First-aid measures

· Description of first aid measures

· After inhalation:

Remove person to fresh air and keep comfortable for breathing.
If feeling unwell: Call a POISON CENTRE or doctor.

· After skin contact:

Take off immediately all contaminated clothing.
Wash with plenty of soap and water.

· After eye contact:

Rinse cautiously with water for 20 minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If eye irritation persists: Get medical advice or attention.

· After swallowing:

Rinse mouth.
Do NOT induce vomiting.
If symptoms persist consult doctor.

· Most important symptoms and effects, both acute and delayed

No further relevant information available.

· Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

· Extinguishing media

· Suitable extinguishing agents:

CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· For safety reasons unsuitable extinguishing agents:

Water with full jet

· Special hazards arising from the substance or mixture

The liquid may float on water and ignite.
Vapors are heavier than air. Vapors may travel to sources of ignition near the ground. They can cause flash fire or ignite explosively.
Prevent fire-fighting wash from entering waterway or sewer system.

· Hazardous combustion products:

Carbon Oxides (CO_x)

· Advice for firefighters

· Protective equipment:

No special measures required.



Safety Data Sheet

according to WHMIS 2023 and HCS 2024

Page 4/12

Date of issue 03/13/2025

Version number 9.01

Revision: 03/13/2025

Trade name: 419D

(Contd. of page 3)

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation
Remove or keep away all sources of extreme heat or open flames.
Avoid breathing mist, spray, or vapors.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Collect liquid in a sealable, chemical-resistant container.
Wash residue with a paper towel and place dirty towels in container.
Use soap and water to remove the last traces of residue.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Precautions for safe handling**
Wear protective gloves and eye protection.
Wash hands and exposed skin thoroughly after handling.
Take off contaminated clothing and wash it before reuse.
Avoid breathing mist, spray, or vapors.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
 - **Storage:**
 - **Requirements to be met by storerooms and receptacles:** Store in a cool location.
 - **Information about storage in one common storage facility:** Not required.
 - **Further information about storage conditions:**
Store locked up.
Keep receptacle tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

— CA —
(Contd. on page 5)

Safety Data Sheet

according to WHMIS 2023 and HCS 2024

Page 5/12

Date of issue 03/13/2025

Version number 9.01

Revision: 03/13/2025

Trade name: 419D

(Contd. of page 4)

8 Exposure controls/ Personal protection

· Control parameters

· Components with limit values that require monitoring at the workplace:

123-86-4 n-butyl acetate	
EL (Canada)	STEL: 150 ppm TWA: 50 ppm
EV (Canada)	STEL: 950 mg/m ³ , 200 ppm TWA: 710 mg/m ³ , 150 ppm
PEL (USA)	TWA: 710 mg/m ³ , 150 ppm
REL (USA)	STEL: 950 mg/m ³ , 200 ppm TWA: 710 mg/m ³ , 150 ppm
TLV (USA)	STEL: 712 mg/m ³ , 150 ppm TWA: 238 mg/m ³ , 50 ppm
78-93-3 Butan-2-one	
EL (Canada)	STEL: 100 ppm TWA: 50 ppm R, Skin
EV (Canada)	STEL: 885 mg/m ³ , 300 ppm TWA: 590 mg/m ³ , 200 ppm
PEL (USA)	TWA: 590 mg/m ³ , 200 ppm
REL (USA)	STEL: 885 mg/m ³ , 300 ppm TWA: 590 mg/m ³ , 200 ppm
TLV (USA)	STEL: 150 ppm TWA: 75 ppm BEI, Skin
· Ingredients with biological limit values:	
78-93-3 Butan-2-one	
BEI (USA)	2 mg/L Medium: urine Time: end of shift Parameter: Methyl ethyl ketone (nonspecific)

· **Additional information:** The lists that were valid during the creation were used as basis.

· Exposure controls

· **Appropriate engineering controls** No further data; see section 7.

· Personal protective equipment:

· General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.
Advice should be sought from respiratory protection specialists.

(Contd. on page 6)

Safety Data Sheet

according to WHMIS 2023 and HCS 2024

Page 6/12

Date of issue 03/13/2025

Version number 9.01

Revision: 03/13/2025

Trade name: 419D

(Contd. of page 5)

· Protection of hands:



Protective gloves: EN374

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Wear safety glasses: EN 166

9 Physical and chemical properties

· Information on basic physical and chemical properties

· Physical state	Liquid
· Form:	Low viscosity
· Color:	Clear
· Odor:	Fruit-like
· Melting point/Melting range:	Undetermined.
· Boiling point/Boiling range:	≥80 °C (≥176 °F)
· Flammability:	Highly flammable.
· Explosion limits:	
· Lower:	1.6 Vol %
· Upper:	10.4 Vol %
· Flash point:	-9 °C (15.8 °F)
· Auto igniting:	≥400 °C (≥752 °F)
· Decomposition temperature:	Not determined.
· pH-value:	Not determined.
· Viscosity:	
· Kinematic at 20 °C (68 °F):	110 mm ² /s
· Dynamic:	Not determined.

(Contd. on page 7)

—CA—

Safety Data Sheet

according to WHMIS 2023 and HCS 2024

Page 7/12

Date of issue 03/13/2025

Version number 9.01

Revision: 03/13/2025

Trade name: 419D

(Contd. of page 6)

<ul style="list-style-type: none"> · Solubility in / Miscibility with <ul style="list-style-type: none"> · Water: · Partition coefficient (n-octanol/water): · Vapor pressure: · Vapor pressure: <ul style="list-style-type: none"> · Relative density at 20 °C (68 °F): · Vapor density (air=1) at 20 °C (68 °F): · Particle characteristics 	<p>Not miscible or difficult to mix.</p> <p>Not determined.</p> <p>Not available</p> <p>0.92</p> <p>>2.5</p> <p>Not applicable.</p>
<ul style="list-style-type: none"> · Other information <ul style="list-style-type: none"> · Important information on protection of health and environment, and on safety. <ul style="list-style-type: none"> · Ignition temperature: · Danger of explosion: · Solvent content: <ul style="list-style-type: none"> · Organic solvents: · Evaporation rate at 20 °C (68 °F) 	<p>Product is not selfigniting.</p> <p>Product is not explosive. However, formation of explosive air/vapor mixtures are possible.</p> <p>Not available</p> <p><1</p>

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability** Chemically stable at normal temperatures and pressures.
 - **Thermal decomposition / conditions to be avoided:**

No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** Avoid ignition sources, open flames, and incompatible substances.
- **Incompatible materials:**

Strong oxidizing agents

Strong acids
- **Hazardous decomposition products:**

No dangerous decomposition products known.

Hazardous combustion products: see section 5.

11 Toxicological information

- **Information on toxicological effects**
 - **Acute toxicity:**

· LD/LC50 values that are relevant for classification:		
123-86-4 n-butyl acetate		
Oral	LD50	>10,768 mg/kg (rat)

(Contd. on page 8)

—CA—

Safety Data Sheet

according to WHMIS 2023 and HCS 2024

Page 8/12

Date of issue 03/13/2025

Version number 9.01

Revision: 03/13/2025

Trade name: 419D

(Contd. of page 7)

Dermal	LD50	>17,600 mg/kg (rabbit)
Inhalative	LC50/4 h	>21 mg/L (rat)
78-93-3 Butan-2-one		
Oral	LD50	2,737 mg/kg (rat)
Dermal	LD50	6,480 mg/kg (rabbit)
Inhalative	LC50/ 8 h	23,500 mg/m3 (rat)
80-62-6 methyl methacrylate		
Oral	LD50	7,872 mg/kg (rat)
97-88-1 n-butyl methacrylate		
Oral	LD50	22,600 mg/kg (rat)
Dermal	LD50	11,300 mg/kg (rabbit)
Inhalative	LC50/4 h	4,910 mg/L (rat)

- **Primary irritant effect:**
 - **on the eye:** Irritating effect.
- **Summary of effects and symptoms by route of exposure**
 - **Eyes:**
 - redness, serious irritation
 - pain
 - **Skin:**
 - redness, may cause mild irritation
 - dry skin
 - **Inhalation:**
 - dizziness or drowsiness
 - cough
 - headache
 - sore throat
 - nausea
 - **Swallowed:**
 - vomiting
 - diarrhea
 - see inhalation symptoms
- **Delayed and immediate effects as well as chronic effects from short and long-term exposure**

Prolonged or repeated exposure may defat skin and cause skin dryness and cracking, and local redness and discomfort.
- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

· **Carcinogenic categories**

· IARC (International Agency for Research on Cancer)		
80-62-6	methyl methacrylate	3
97-88-1	n-butyl methacrylate	2B

(Contd. on page 9)

CA



Safety Data Sheet

according to WHMIS 2023 and HCS 2024

Page 9/12

Date of issue 03/13/2025

Version number 9.01

Revision: 03/13/2025

Trade name: 419D

(Contd. of page 8)

· NTP (National Toxicology Program)
None of the ingredients is listed.

12 Ecological information

· Toxicity

· Aquatic toxicity:
123-86-4 n-butyl acetate
LC50 96h 18 mg/L (minnow)

· **Persistence and degradability** No further relevant information available.

· **Bioaccumulative potential** No further relevant information available.

· **Mobility in soil** No further relevant information available.

· Results of PBT and vPvB assessment

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **Other adverse effects** No further relevant information available.

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packagings:

· **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· UN-Number	
· DOT/TDG, IMDG, IATA	UN1263
· UN proper shipping name	
· DOT/TDG, IATA	Paint
· IMDG	PAINT

(Contd. on page 10)

—CA—

Safety Data Sheet

according to WHMIS 2023 and HCS 2024

Page 10/12




Date of issue 03/13/2025

Version number 9.01

Revision: 03/13/2025

Trade name: 419D

(Contd. of page 9)

· Transport hazard class(es)	
· DOT/TDG (Transport dangerous goods):	
	
· Class · Label	3 Flammable liquids 3
· IMDG, IATA	
	
· Class · Label	3 Flammable liquids 3
· Packing group	
· DOT/TDG, IMDG, IATA	II
· Environmental hazards:	
Not applicable.	
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	
Not applicable.	
· Transport/Additional information:	
	Limited Quantity
419D-55ML, 419D-1L, 419D-4L	
· DOT/TDG	
· Quantity limitations	On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L
· IMDG	
· Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· Special precautions for user	
Not applicable.	
· Hazard identification number (Kemler code): · EMS Number: · Stowage Category	33 F-E, <u>S</u> -E B

(Contd. on page 11)

—CA—



Safety Data Sheet

according to WHMIS 2023 and HCS 2024

Page 11/12

Date of issue 03/13/2025

Version number 9.01

Revision: 03/13/2025

Trade name: 419D

(Contd. of page 10)

· **UN "Model Regulation":** UN 1263 PAINT, 3, II

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **OSHA Hazard Communication Standard (29 CFR Part 1900)**

The safety data sheet and label comply with HCS 2024.

· **Hazardous Products Act (R.S.C., 1985, c. H-3)**

The safety data sheet and label comply with the Hazardous Product Act and WHMIS 2023.

· **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

80-62-6 | methyl methacrylate

· **TSCA (Toxic Substances Control Act):**

All components have the value ACTIVE.

· **Hazardous Air Pollutants**

80-62-6 | methyl methacrylate

· **Proposition 65**

· **Chemicals known to cause cancer:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogenic categories**

· **TLV (Threshold Limit Value)**

80-62-6 | methyl methacrylate

A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **Canadian substance listings:**

· **Canadian Domestic Substances List (DSL)**

All ingredients are listed.

(Contd. on page 12)

—CA—



Safety Data Sheet

according to WHMIS 2023 and HCS 2024

Page 12/12

Date of issue 03/13/2025

Version number 9.01

Revision: 03/13/2025

Trade name: 419D

(Contd. of page 11)

· Canadian Non-Domestic Substances List (NDSL)
None of the ingredients is listed.
· Canadian Ingredient Disclosure list (limit 0.1%)
None of the ingredients is listed.
· Canadian Ingredient Disclosure list (limit 1%)
All ingredients are listed.

· **HMIS-ratings (scale 0 - 4)**

Health = * 2

Fire = 3

Reactivity = 0

· **Europe**

· **RoHS (Restriction of Hazardous Substances Directive)**

This product does not contain any lead, cadmium, mercury, hexavalent chromium, PBB's, PBDE's, DEHP, BBP, DBP, or DIBP and complies with European RoHS regulations.

· **WEEE (Waste Electrical and Electronic Equipment Directive)**

This product is not a piece of electrical or electronics equipment, and is therefore not governed by this regulation.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Product safety department.

· **Contact:** sds@mgchemicals.com

· **Version number of previous version:** 9.00

· **Date of preparation** 03/13/2025

· **Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

· *** Data compared to the previous version altered.**

— CA —