



Safety Data Sheet

according to WHMIS 2023 and HCS 2024

Page 1/13

Date of issue 11/05/2025

Version number 5.01

Revision: 11/05/2025

1 Identification

· Product identifier

· Trade name: 419E

· Other Means of Identification: Premium Acrylic Conformal Coating

· Related Part Number: 419E-Liquid, 419E-55ML, 419E-1L, 419E-4L, 419E-20L

· Application of the substance / the mixture Protective coating for printed circuit boards

· Uses advised against Not available

· Details of the supplier of the safety data sheet

Manufacturer/Supplier:

MG Chemicals (Head Office)
1210 Corporate Drive
Burlington, Ontario L7L 5R6
CANADA

+(1) 800-340-0772

+(1) 905-331-1396

info@mgchemicals.com

Distributor:

Masline
511 Clinton Ave S
Rochester, New York 14620
United States
+(1) 586-546-5373

· Information department: sds@mgchemicals.com

· Emergency telephone number:

For hazardous material incidents ONLY (leaks, spills, fires, exposures or accidents)
USA or CANADA-Call 3E at +1-866-519-4752 or +1-760-476-3962 (Service access code: 335388)

For emergencies involving the transport of dangerous goods; 24/7 service
CANADA-Call CANUTEC collect at +1-613-996-6666 or *666 on cellular phones

* 2 Hazard identification

· Classification of the substance or mixture

Flammable liquids – Category 2

H225 Highly flammable liquid and vapour.

Eye damage/irritation – Category 2A

H319 Causes serious eye irritation.

Sensitization - skin – Category 1

H317 May cause an allergic skin reaction.

Reproductive Toxicity - Category 2

H361 Suspected of damaging fertility or the unborn child.

Specific target organ toxicity (single exposure) – Category 3 H335 May cause respiratory irritation.

3

Specific target organ toxicity (single exposure) – Category 3 H336 May cause drowsiness or dizziness.

3

(Contd. on page 2)

—CA—

Safety Data Sheet

according to WHMIS 2023 and HCS 2024

Page 2/13

Date of issue 11/05/2025

Version number 5.01

Revision: 11/05/2025

Trade name: 419E

(Contd. of page 1)

Label elements

GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictograms



Signal word Danger

Hazard-determining components of labeling:

Butan-2-one
isobutyl isobutyrate
methyl salicylate
methyl methacrylate
n-butyl methacrylate

Hazard statements

H225 Highly flammable liquid and vapour.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H361 Suspected of damaging fertility or the unborn child.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.

Precautionary statements

P102 Keep out of reach of children.
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P240 Ground / bond container and receiving equipment.
P241 Use explosion-proof equipment.
P243 Take action to prevent static discharges.
P261 Avoid breathing mist, vapors or spray.
P264 Wash thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P272 Contaminated work clothing should not be allowed out of the workplace.
P280 Wear protective gloves, protective clothing, and eye protection.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313 IF exposed or concerned: Get medical advice.
P312 Call a POISON CENTER or doctor if you feel unwell.
P333+P313 If skin irritation or rash occurs: Get medical advice.
P337+P313 If eye irritation persists: Get medical advice.
P362+P364 Take off contaminated clothing and wash it before reuse.

(Contd. on page 3)

—CA—

Safety Data Sheet

according to WHMIS 2023 and HCS 2024

Page 3/13

Date of issue 11/05/2025

Version number 5.01

Revision: 11/05/2025

Trade name: 419E

(Contd. of page 2)

P370+P378 In case of fire: Use CO₂, powder or water spray to extinguish.
P403+P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.
P501 Dispose of contents and container in accordance with local, regional, and national regulations.

· **Other hazards** Repeated exposure may cause skin dryness or cracking.

3 Composition/Information on ingredients

· **Chemical characterization: Mixtures**

· **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

| | | |
|----------|----------------------|-----------|
| 78-93-3 | Butan-2-one | 46.0% w/w |
| 97-85-8 | isobutyl isobutyrate | 24.0% w/w |
| 119-36-8 | methyl salicylate | 1.0% w/w |
| 80-62-6 | methyl methacrylate | 0.1% w/w |
| 97-88-1 | n-butyl methacrylate | 0.1% w/w |

4 First-aid measures

· **Description of first aid measures**

· **After inhalation:**

Remove person to fresh air and keep comfortable for breathing.

If feeling unwell: Call a POISON CENTRE or doctor.

If exposed or concerned: Get medical advice/attention.

· **After skin contact:**

Wash with plenty water.

If skin irritation or rash occurs: Get medical advice or attention.

Take off contaminated clothing and wash it before reuse.

If exposed or concerned: Get medical advice or attention.

· **After eye contact:**

Rinse cautiously with water for 20 minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice or attention.

· **After swallowing:**

Rinse mouth.

Do NOT induce vomiting.

If symptoms persist consult doctor.

If exposed or concerned: Get medical advice or attention.

· **Most important symptoms and effects, both acute and delayed**

No further relevant information available.

(Contd. on page 4)

—CA—



Safety Data Sheet

according to WHMIS 2023 and HCS 2024

Page 4/13

Date of issue 11/05/2025

Version number 5.01

Revision: 11/05/2025

Trade name: 419E

(Contd. of page 3)

- **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**

- **Suitable extinguishing agents:**

CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- **For safety reasons unsuitable extinguishing agents:** Water with full jet

- **Special hazards arising from the substance or mixture**

Vapors are heavier than air. Vapors may travel to sources of ignition near the ground. They can cause flash fire or ignite explosively.

Prevent fire-fighting wash from entering waterway or sewer system.

- **Hazardous combustion products:**

Carbon Oxides (CO_x)
other toxic fumes

- **Advice for firefighters**

- **Protective equipment:** Wear self-contained breathing apparatus and full fire-fighting turn-out gear.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Remove or keep away all sources of extreme heat or open flames.

Avoid breathing mist, spray, or vapors.

- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.

- **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Collect liquid in a sealable, chemical-resistant container.

Wash residue with a paper towel and place dirty towels in container.

Use soap and water to remove the last traces of residue.

- **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

— CA —
(Contd. on page 5)

Safety Data Sheet

according to WHMIS 2023 and HCS 2024

Page 5/13

Date of issue 11/05/2025

Version number 5.01

Revision: 11/05/2025

Trade name: 419E

(Contd. of page 4)

7 Handling and storage

· Precautions for safe handling

Wear protective gloves and eye protection.
Wash hands and exposed skin thoroughly after handling.
Take off contaminated clothing and wash it before reuse.
Contaminated work clothing should not be allowed out of the workplace.
Avoid breathing mist, spray, or vapors.
Use only outdoors or in a well-ventilated area.
Obtain, read and follow all safety instructions before use.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Use explosion-proof apparatus / fittings and spark-proof tools.
Ground and bond container and receiving equipment.

· Conditions for safe storage, including any incompatibilities

· Storage:

· Requirements to be met by storerooms and receptacles:

Store in a cool location.
Keep in a dry and clean area, away from incompatible substances

· Information about storage in one common storage facility: Not required.

· Further information about storage conditions:

Keep receptacle tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
Store locked up.

· Specific end use(s) See section 1.2

8 Exposure controls/ Personal protection

· Control parameters

· Components with limit values that require monitoring at the workplace:

78-93-3 Butan-2-one

| | |
|-------------|---|
| EL (Canada) | STEL: 100 ppm TWA: 50 ppm R, Skin |
| EV (Canada) | STEL: 885 mg/m ³ , 300 ppm TWA: 590 mg/m ³ , 200 ppm |
| PEL (USA) | TWA: 590 mg/m ³ , 200 ppm |
| REL (USA) | STEL: 885 mg/m ³ , 300 ppm TWA: 590 mg/m ³ , 200 ppm |
| TLV (USA) | STEL: 150 ppm TWA: 75 ppm BEI, Skin |

(Contd. on page 6)

— CA —

Safety Data Sheet

according to WHMIS 2023 and HCS 2024

Page 6/13

Date of issue 11/05/2025

Version number 5.01

Revision: 11/05/2025

Trade name: 419E

(Contd. of page 5)

| | |
|--|---|
| 80-62-6 methyl methacrylate | |
| EL (Canada) | STEL: 100 ppm TWA: 50 ppm S(D) |
| EV (Canada) | STEL: 100 ppm TWA: 50 ppm |
| PEL (USA) | TWA: 410 mg/m ³ , 100 ppm |
| REL (USA) | TWA: 410 mg/m ³ , 100 ppm |
| TLV (USA) | STEL: 410 mg/m ³ , 100 ppm TWA: 205 mg/m ³ , 50 ppm DSEN, A4 |
| 97-88-1 n-butyl methacrylate | |
| EL (Canada) | TWA: 50 ppm IARC 2B |
| Ingredients with biological limit values: | |
| 78-93-3 Butan-2-one | |
| BEI (USA) | 2 mg/L Medium: urine Time: end of shift Parameter: Methyl ethyl ketone (nonspecific) |

· **Additional information:**

The lists that were valid during the creation were used as basis.
Refer to the national or regional occupational exposure limit regulation for abbreviations and acronyms.

· **Exposure controls**

· **Appropriate engineering controls** No further data; see section 7.

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.

· **Breathing equipment:**

Advice should be sought from respiratory protection specialists.
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.
If the product is heated or worker has a known allergic reaction, consider using a full mask with organic vapor cartridge or with an independent air supply.

· **Protection of hands:**

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.



Protective gloves: EN374

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

(Contd. on page 7)

—CA—

Safety Data Sheet

according to WHMIS 2023 and HCS 2024

Page 7/13

Date of issue 11/05/2025

Version number 5.01

Revision: 11/05/2025

Trade name: 419E

(Contd. of page 6)

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Safety glasses or tightly sealed goggles: EN 166

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

| | |
|---|--------------------------|
| · Physical state | Liquid |
| · Form: | Viscous |
| · Color: | Clear |
| · Odor: | Sweetish |
| · Odor threshold: | Not determined. |
| · Melting point/Melting range: | Undetermined. |
| · Boiling point/Boiling range: | 80 °C (176 °F) |
| · Flammability: | Highly flammable. |
| · Explosion limits: | |
| · Lower: | 1.8 Vol % |
| · Upper: | 11.6 Vol % |
| · Flash point: | -9 °C (15.8 °F) |
| · Auto igniting: | 400 °C (752 °F) |
| · Decomposition temperature: | Not determined. |
| · pH-value: | Not determined. |
| · Viscosity: | |
| · Kinematic at 20 °C (68 °F): | >20.5 mm ² /s |
| · Dynamic: | Not determined. |
| · Solubility in / Miscibility with | |
| · Water: | Partly miscible. |
| · Partition coefficient (n-octanol/water): | Not determined. |
| · Vapor pressure at 20 °C (68 °F): | 60 hPa (45 mm Hg) |
| · Relative density at 25 °C (77 °F): | 0.88 |
| · Vapor density (air=1): | >2.14 |
| · Particle characteristics | Not applicable |

(Contd. on page 8)

—CA—

Safety Data Sheet

according to WHMIS 2023 and HCS 2024

Page 8/13

Date of issue 11/05/2025

Version number 5.01

Revision: 11/05/2025

Trade name: 419E

(Contd. of page 7)

- **Other information**
 - **Important information on protection of health and environment, and on safety.**
 - **Ignition temperature:** Product is not selfigniting.
 - **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
 - **Organic solvents:** 46.00 %
 - **VOC content:** 46,000 %
 - **Solids content:** 460.0 g/l / 3.84 lb/gal
 - **Evaporation rate:** 28.9 %
 - **Evaporation rate:** Not determined.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability** Chemically stable at normal temperatures and pressures.
 - **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** Avoid open flames, excessive heat, sparks, ignition sources, and incompatible substances.
- **Incompatible materials:**
 - Oxidizing agents
 - Strong acids
 - Strong bases
- **Hazardous decomposition products:**
 - No dangerous decomposition products known.
 - Hazardous combustion products: see section 5.

11 Toxicological information

- **Information on toxicological effects**
 - **Acute toxicity:**

| · LD/LC50 values that are relevant for classification: | | |
|--|------|----------------------|
| ATE (Acute Toxicity Estimate) | | |
| Oral | LD50 | 89,000 mg/kg (ATE) |
| 78-93-3 Butan-2-one | | |
| Oral | LD50 | 2,737 mg/kg (rat) |
| Dermal | LD50 | 6,480 mg/kg (rabbit) |

(Contd. on page 9)

—CA—

Safety Data Sheet

according to WHMIS 2023 and HCS 2024

Page 9/13

Date of issue 11/05/2025

Version number 5.01

Revision: 11/05/2025

Trade name: 419E

(Contd. of page 8)

| | | |
|-------------------------------------|-----------|--------------------------------|
| Inhalative | LC50/ 8 h | 23,500 mg/m ³ (rat) |
| 97-85-8 isobutyl isobutyrate | | |
| Oral | LD50 | 7,712 mg/kg (rat) |
| Dermal | LD50 | 10,626 mg/kg (rabbit) |
| 119-36-8 methyl salicylate | | |
| Oral | LD50 | 890 mg/kg (ATE) |
| | | 887 mg/kg (rat) |
| 80-62-6 methyl methacrylate | | |
| Oral | LD50 | 7,872 mg/kg (rat) |
| 97-88-1 n-butyl methacrylate | | |
| Oral | LD50 | 22,600 mg/kg (rat) |
| Dermal | LD50 | 11,300 mg/kg (rabbit) |
| Inhalative | LC50/4 h | 4,910 mg/L (rat) |

- **Primary irritant effect:**
 - **on the eye:** Irritating effect.
- **Sensitization:** Sensitization possible through skin contact.
- **Summary of effects and symptoms by route of exposure**
 - **Eyes:** redness, serious irritation
 - **Skin:**
 - rash, allergic contact dermatitis
 - dry skin
 - **Inhalation:**
 - cough
 - headache
 - irritation of the respiratory tract
 - **Swallowed:**
 - abdominal pain
 - nausea, vomiting
 - headache
 - cough
 - drowsiness
 - dizziness
- **Delayed and immediate effects as well as chronic effects from short and long-term exposure**
 - Prolonged or repeated exposure may defat skin and cause skin dryness and cracking, and local redness and discomfort.
 - Prolonged or repeated exposure may cause skin allergies.
- **Additional toxicological information:**
 - The product shows the following dangers according to internally approved calculation methods for preparations:
 - Irritant

· **Carcinogenic categories**

| · IARC (International Agency for Research on Cancer) | | |
|---|----------------------|----|
| 80-62-6 | methyl methacrylate | 3 |
| 97-88-1 | n-butyl methacrylate | 2B |

(Contd. on page 10)

—CA—

Safety Data Sheet

according to WHMIS 2023 and HCS 2024

Page 10/13

Date of issue 11/05/2025

Version number 5.01

Revision: 11/05/2025

Trade name: 419E

(Contd. of page 9)

· NTP (National Toxicology Program)

None of the ingredients is listed.

12 Ecological information

· Toxicity

· Aquatic toxicity:

119-36-8 methyl salicylate

| | |
|------------|-----------------------|
| EC50/ 48 h | 28 mg/L (crustaceans) |
| EC50/ 72 h | 1.1 mg/L (algae) |
| LC50 96h | 19.8 mg/L (fish) |

· **Persistence and degradability** No further relevant information available.

· **Bioaccumulative potential** No further relevant information available.

· **Mobility in soil** No further relevant information available.

· Results of PBT and vPvB assessment

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **Other adverse effects** No further relevant information available.

13 Disposal considerations

· Waste treatment methods

· **Recommendation:** This material and its container must be disposed of as hazardous waste.

· Uncleaned packagings:

· Recommendation:

Containers may still present a chemical hazard/ danger when empty.

Dispose of contents in accordance with all local, regional, national, and international regulations.

Where possible retain label warnings and SDS and observe all notices pertaining to the product.

14 Transport information

· UN-Number

· DOT/TDG, IMDG, IATA

UN1263

· UN proper shipping name

· DOT/TDG, IATA

Paint

(Contd. on page 11)

—CA—

Safety Data Sheet

according to WHMIS 2023 and HCS 2024

Page 11/13




Date of issue 11/05/2025

Version number 5.01

Revision: 11/05/2025

Trade name: 419E

(Contd. of page 10)

| | |
|---|---|
| · IMDG | PAINT |
| · Transport hazard class(es) | |
| · DOT/TDG (Transport dangerous goods): | |
|  | |
| · Class | 3 Flammable liquids |
| · Label | 3 |
| · IMDG, IATA | |
|  | |
| · Class | 3 Flammable liquids |
| · Label | 3 |
| · Packing group | |
| · DOT/TDG, IMDG, IATA | II |
| · Environmental hazards: | Not applicable. |
| · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code | Not applicable. |
| · Transport/Additional information: | |
|  Limited Quantity 419E-55ML, 419E-1L, 419E-4L | |
| · DOT/TDG | |
| · Quantity limitations | On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L |
| · IMDG | |
| · Limited quantities (LQ) | 5L |
| · Excepted quantities (EQ) | Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml |
| · Special precautions for user | Not applicable. |
| · Hazard identification number (Kemler code): | 33 |
| · EMS Number: | F-E, <u>S</u> -E |
| · Stowage Category | B |

(Contd. on page 12)



Safety Data Sheet

according to WHMIS 2023 and HCS 2024

Page 12/13

Date of issue 11/05/2025

Version number 5.01

Revision: 11/05/2025

Trade name: 419E

(Contd. of page 11)

· UN "Model Regulation": UN 1263 PAINT, 3, II

* 15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· OSHA Hazard Communication Standard (29 CFR Part 1900)

The safety data sheet and label comply with HCS 2024.

· Hazardous Products Act (R.S.C., 1985, c. H-3)

The safety data sheet and label comply with the Hazardous Product Act and WHMIS 2023.

· Sara

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

80-62-6 | methyl methacrylate

· TSCA (Toxic Substances Control Act):

All components have the value ACTIVE.

· Hazardous Air Pollutants

80-62-6 | methyl methacrylate

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· TLV (Threshold Limit Value)

80-62-6 | methyl methacrylate

A4

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· Canadian substance listings:

· Canadian Domestic Substances List (DSL)

All ingredients are listed.

(Contd. on page 13)

—CA—

Safety Data Sheet

according to WHMIS 2023 and HCS 2024

Page 13/13

Date of issue 11/05/2025

Version number 5.01

Revision: 11/05/2025

Trade name: 419E

(Contd. of page 12)

| | |
|---|-------------------|
| · Canadian Non-Domestic Substances List (NDSL) | |
| None of the ingredients is listed. | |
| · Canadian Ingredient Disclosure list (limit 0.1%) | |
| 119-36-8 | methyl salicylate |
| · Canadian Ingredient Disclosure list (limit 1%) | |
| 78-93-3 | Butan-2-one |

· **HMIS-ratings (scale 0 - 4)**

Health = * 2

Fire = 3

Reactivity = 0

· **Europe**

· **RoHS (Restriction of Hazardous Substances Directive)**

This product does not contain any lead, cadmium, mercury, hexavalent chromium, PBB's, PBDE's, DEHP, BBP, DBP, or DIBP and complies with European RoHS regulations.

· **WEEE (Waste Electrical and Electronic Equipment Directive)**

This product is not a piece of electrical or electronics equipment, and is therefore not governed by this regulation.

| | |
|---|--|
| · Per- and polyfluoroalkyl substances (PFAS) | |
| None of the ingredients is listed. | |

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Regulatory department

· **Contact:** sds@mgchemicals.com

· **Version number of previous version:** 5.00

· **Date of preparation** 11/05/2025

· **Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

· *** Data compared to the previous version altered.**