

Disposable mixers

Two-component material mixing

Complete and thorough mixing for two-component materials

Ideal for single-use fluid dispensing applications, the elements in these mixers are 180° helical twists alternating in either right- or left-hand rotation. These alternating elements are joined so that their leading and trailing edges are mutually perpendicular.



Series 120



Part number	Mixing elements	Element dia. (in/mm)	Element length (in/mm)
7700467	8	0.093 / 2.36	0.77 / 1.96
7700465	12	0.093 / 2.36	1.16 / 2.95
7700459	12	0.125 / 3.18	1.30 / 3.30
7700469	14	0.187 / 4.75	2.23 / 5.66
7700470	16	0.189 / 4.80	2.56 / 6.50
7704166	7	0.212 / 5.38	1.48 / 3.76
7700478	21	0.212 / 5.38	4.45 / 11.30
7700475	8	0.248 / 6.30	2.00 / 5.08
7700480	12	0.248 / 6.30	3.00 / 7.62
7700481	16	0.248 / 6.30	3.96 / 10.06
7700486	20	0.247 / 6.27	5.00 / 12.70
7700489	24	0.248 / 6.30	5.94 / 15.09
7700507	12	0.314 / 8.00	3.67 / 9.32
7700498	6	0.370 / 9.40	2.00 / 5.08
7700500	12	0.370 / 9.40	3.90 / 9.91
7700509	24	0.366 / 9.30	7.83 / 19.89
7700515	12	0.497 / 12.62	5.00 / 12.70
7700519	18	0.497 / 12.62	7.47 / 18.98
7700523	10	0.630 / 16.00	5.42 / 13.77
7700526	8	0.784 / 19.91	5.37 / 13.64
7700528	4	1.025 / 26.04	5.90 / 14.99

Series 162A



Part number	Mixing elements	Element dia. (in/mm)	Housing length (in/mm)	Outside diameter (in/mm)	Pressure limit (psi/bar)
7701057	16	0.784 / 19.9	12.5 / 31.7	0.98 / 24.9	580 / 39
7701059	23	0.784 / 19.9	17.0 / 43.2	0.98 / 24.9	580 / 39
7701063	32	0.784 / 19.9	24.5 / 62.2	0.98 / 24.9	580 / 39
7701066	39	0.784 / 19.9	30.3 / 77.0	0.98 / 24.9	580 / 39
7701067	48	0.784 / 19.9	36.4 / 92.5	0.98 / 24.9	580 / 39


SEALANT EQUIPMENT

Series 160 spiral bell mixers



Part number	Mixing elements	Element dia. (in/mm)	Housing length (in/mm)	Outside diameter (in/mm)	Outlet tip orifice (in/mm)	Housing outlet	Pressure limit (psi/bar)
7440276	8	0.189 / 4.80	2.62 / 6.65	0.300 / 7.62	0.07 / 1.78	Luer slip	500 / 34
7440277	8	0.189 / 4.80	2.62 / 6.65	0.300 / 7.62	0.07 / 1.78	Luer lock	500 / 34
7436788	16	0.189 / 4.80	3.90 / 9.91	0.300 / 7.62	0.07 / 1.78	Luer slip	500 / 34
7436776	24	0.189 / 4.80	5.18 / 13.16	0.300 / 7.62	0.07 / 1.78	Luer slip	500 / 34
7440278	24	0.189 / 4.80	5.18 / 13.16	0.300 / 7.62	0.07 / 1.78	Luer lock	500 / 34
7436777	32	0.189 / 4.80	6.48 / 16.46	0.300 / 7.62	0.07 / 1.78	Luer slip	500 / 34
7440279	32	0.189 / 4.80	6.48 / 16.46	0.300 / 7.62	0.07 / 1.78	Luer lock	500 / 34
7440280	48	0.189 / 4.80	9.04 / 22.96	0.300 / 7.62	0.07 / 1.78	Luer slip	500 / 34
7440281	48	0.189 / 4.80	9.04 / 22.96	0.300 / 7.62	0.07 / 1.78	Luer lock	500 / 34
7440282	8	0.248 / 6.30	3.56 / 9.04	0.370 / 9.40	0.09 / 2.29	Luer slip	360 / 25
7440283	8	0.248 / 6.30	3.56 / 9.04	0.370 / 9.40	0.09 / 2.29	Luer lock	360 / 25
7440284	16	0.248 / 6.30	5.46 / 13.87	0.370 / 9.40	0.09 / 2.29	Luer slip	360 / 25
7440285	16	0.248 / 6.30	5.46 / 13.87	0.370 / 9.40	0.09 / 2.29	Luer lock	360 / 25
7436774	24	0.248 / 6.30	7.46 / 18.95	0.370 / 9.40	0.09 / 2.29	Luer slip	360 / 25
7440286	24	0.248 / 6.30	7.46 / 18.95	0.370 / 9.40	0.09 / 2.29	Luer lock	360 / 25
7440287	24	0.248 / 6.30	7.46 / 18.95	0.370 / 9.40	0.09 / 2.29	Luer lock	360 / 25
7429810	32	0.248 / 6.30	9.49 / 24.10	0.370 / 9.40	0.09 / 2.29	Luer slip	360 / 25
7436775	32	0.248 / 6.30	9.49 / 24.10	0.370 / 9.40	0.09 / 2.29	Luer lock	360 / 25
7440288	32	0.248 / 6.30	9.49 / 24.10	0.370 / 9.40	0.09 / 2.29	Luer lock	360 / 25
7429611	48	0.248 / 6.30	13.14 / 33.38	0.370 / 9.40	0.09 / 2.29	Luer slip	360 / 25
7440289	48	0.248 / 6.30	13.14 / 33.38	0.370 / 9.40	0.09 / 2.29	Luer lock	360 / 25
7440290	48	0.248 / 6.30	13.14 / 33.38	0.370 / 9.40	0.09 / 2.29	Luer lock	360 / 25
7440291	18	0.314 / 8.00	6.96 / 17.68	0.461 / 11.71	0.10 / 2.54	Stepped	330 / 23
7440292	18	0.314 / 8.00	6.96 / 17.68	0.461 / 11.71	0.10 / 2.54	Luer lock	330 / 23
7429813	24	0.314 / 8.00	8.84 / 22.45	0.461 / 11.71	0.10 / 2.54	Stepped	330 / 23
7440293	24	0.314 / 8.00	8.84 / 22.45	0.461 / 11.71	0.10 / 2.54	Luer lock	330 / 23
7429825	32	0.314 / 8.00	11.44 / 29.06	0.461 / 11.71	0.10 / 2.54	Stepped	330 / 23
7440295	32	0.314 / 8.00	11.44 / 29.06	0.461 / 11.71	0.10 / 2.54	Luer lock	330 / 23
7440296	12	0.366 / 9.30	5.48 / 13.92	0.510 / 12.95	0.12 / 3.05	Stepped	300 / 21
7440297	12	0.366 / 9.30	5.48 / 13.92	0.510 / 12.95	0.12 / 3.05	Luer lock	300 / 21
7440298	18	0.366 / 9.30	7.28 / 18.49	0.510 / 12.95	0.12 / 3.05	Stepped	300 / 21
7440299	18	0.366 / 9.30	7.28 / 18.49	0.510 / 12.95	0.12 / 3.05	Luer lock	300 / 21
7436780	24	0.366 / 9.30	9.15 / 23.24	0.510 / 12.95	0.12 / 3.05	Stepped	300 / 21
7436787	24	0.366 / 9.30	9.15 / 23.24	0.510 / 12.95	0.12 / 3.05	Luer lock	300 / 21
7429809	30	0.366 / 9.30	11.24 / 28.55	0.510 / 12.95	0.12 / 3.05	Stepped	300 / 21
7440300	30	0.366 / 9.30	11.24 / 28.55	0.510 / 12.95	0.12 / 3.05	Luer lock	300 / 21
7429612	40	0.366 / 9.30	14.14 / 35.92	0.510 / 12.95	0.12 / 3.05	Stepped	300 / 21
7440301	40	0.366 / 9.30	14.14 / 35.92	0.510 / 12.95	0.12 / 3.05	Luer lock	300 / 21

Series 160 spiral bell mixers

Part number	Mixing elements	Element dia. (in/mm)	Housing length (in/mm)	Outside diameter (in/mm)	Outlet tip orifice (in/mm)	Housing outlet	Pressure limit (psi/bar)
7429613	60	0.366 / 9.30	22.4 / 56.90	0.510 / 12.95	0.12 / 3.05	Stepped	300 / 21
7440302	64	0.366 / 9.30	24.0 / 60.96	0.510 / 12.95	0.12 / 3.05	Stepped	300 / 21
7440303	12	0.497 / 12.65	6.71 / 17.04	0.660 / 16.76	0.18 / 4.57	Stepped	270 / 19
7440304	12	0.497 / 12.65	6.71 / 17.04	0.660 / 16.76	0.18 / 4.57	Luer lock	270 / 19
7440305	18	0.497 / 12.65	9.08 / 23.06	0.660 / 16.76	0.18 / 4.57	Stepped	270 / 19
7440306	18	0.497 / 12.65	9.08 / 23.06	0.660 / 16.76	0.18 / 4.57	Luer lock	270 / 19
7436772	24	0.497 / 12.65	11.60 / 29.46	0.660 / 16.76	0.18 / 4.57	Stepped	270 / 19
7436773	24	0.497 / 12.65	11.60 / 29.46	0.660 / 16.76	0.18 / 4.57	Luer lock	270 / 19
7429808	30	0.497 / 12.65	14.09 / 35.79	0.660 / 16.76	0.18 / 4.57	Stepped	270 / 19
7440307	30	0.497 / 12.65	14.09 / 35.79	0.660 / 16.76	0.18 / 4.57	Luer lock	270 / 19
7429614	36	0.497 / 12.65	16.63 / 42.24	0.660 / 16.76	0.18 / 4.57	Stepped	270 / 19
7440309	36	0.497 / 12.65	16.63 / 42.24	0.660 / 16.76	0.18 / 4.57	Luer lock	270 / 19
7440309	36	0.497 / 12.65	16.63 / 42.24	0.660 / 16.76	0.18 / 4.57	Luer lock	270 / 19

Series 190



Part number	Mixing elements	Element dia. (in/mm)	Element length (in/mm)	Housing outlet	Retained volume (ml)
7701408	12	0.093 / 2.36	1.5 / 3.8	Slip luer	0.1
7701411	12	0.125 / 3.18	2.1 / 5.3	H tapered	0.2
7701416	24	0.125 / 3.18	3.4 / 8.6	H tapered	0.4
7701417	8	0.187 / 4.75	1.6 / 4.1	Full bore	0.4
7701424	16	0.187 / 4.75	3.4 / 8.6	Slip luer	0.9
7701436	16	0.187 / 4.75	3.4 / 8.6	H tapered	0.9
7701438	7	0.213 / 5.40	2.3 / 5.8	Slip luer	0.9
7701449	17	0.213 / 5.40	4.4 / 11.2	Stepped	1.9
7701453	21	0.213 / 5.40	5.3 / 13.5	Stepped	2.4
7701458	12	0.250 / 6.35	3.9 / 9.9	Slip luer	1.9
7701486	16	0.250 / 6.35	4.8 / 12.2	Stepped	2.5
7701487	20	0.250 / 6.35	5.9 / 15.0	Slip luer	3
7701488	20	0.250 / 6.35	5.9 / 15.0	Stepped	3
7701510	20	0.250 / 6.35	5.9 / 15.0	H tapered	3
7701507	20	0.250 / 6.35	5.3 / 13.5	Full bore	2.8

Series 260



Part number	Mixing elements	Element dia. (in/mm)	Element length (in/mm)	Housing outlet	Retained volume (ml)
7701742	5	0.366 / 9.3	4.9 / 12.4	Tapered	7
7701745	12	0.406 - 0.355 / 10.5 - 8.5	8.6 / 21.8	Tapered	12
7701749	12	0.502 / 12.8	6.7 / 17.02	Stepped	15
7701758	18	0.502 / 12.8	9.1 / 23.11	Stepped	19
7701759	18	0.502 / 12.8	14.1 / 35.8	Barb ext	24
7701770	24	0.502 / 12.8	11.7 / 29.72	Stepped	25
7701782	18	0.502 / 12.8	9.6 / 24.4	Stepped	19
7701795	18	0.502 / 12.8	14.4 / 36.5	Barb ext	24
7701804	16	0.789 / 20.0	12.9 / 32.7	Full bore	71
7701806	20	0.789 / 20.0	15.6 / 39.6	Full bore	88

© 2019 Nordson Corporation | All rights reserved | NSL-19-6005 | Revised 11/19

Nordson expertise is always here when you need it

In highly competitive manufacturing markets, productivity is vital and performance is essential. That's why we apply both to everything we do, whether it's our products, expertise or outstanding customer service. We'll always be there to help maintain the new standards you've set, with expert local service and support delivered through our teams working across the globe.

This unique Nordson approach helps you reach new levels of production, while working more accurately, efficiently and competitively than ever. Precisely why manufacturers who demand quality, can rely on Nordson.

Performance by design

Nordson SEALANT EQUIPMENT

Nordson Sealant Equipment
Wixom, MI, USA

Phone: 1.248.412.7920
Email: SealantSales@nordson.com

 /Nordson_Coating  /SealantEquipment

 /company/nordson-industrial-coating-systems

Find out more at:
www.nordson.com/nse



Nordson
SEALANT EQUIPMENT