



Safety Data Sheet

according to WHMIS 2023 and HCS 2024

Page 1/13

Date of issue 10/27/2025

Version number 6.04

Revision: 04/22/2025

1 Identification

Product identifier

Trade name: 8329TFS-A

Other Means of Identification: Thermally Conductive Epoxy Adhesive (Part A)

Related Part Number: 8329TFS-Part A, 8329TFS-25ML, 8329TFS-50ML, MC002977

Application of the substance / the mixture Thermally conductive adhesive resin

Uses advised against Not for use as a spray coating

Details of the supplier of the safety data sheet

Manufacturer/Supplier:

MG Chemicals (Head Office)

1210 Corporate Drive

Burlington, Ontario L7L 5R6

CANADA

+(1) 800-340-0772

+(1) 905-331-1396

info@mgchemicals.com

Distributor:

Masline

511 Clinton Ave S

Rochester, New York 14620

United States

+(1) 586-546-5373

Information department: sds@mgchemicals.com

Emergency telephone number:

For hazardous material incidents ONLY (leaks, spills, fires, exposures or accidents)

USA or CANADA-Call 3E at +1-866-519-4752 or +1-760-476-3962 (Service access code: 335388)

For emergencies involving the transport of dangerous goods; 24/7 service

CANADA-Call CANUTEC collect at +1-613-996-6666 or *666 on cellular phones

2 Hazard identification

Classification of the substance or mixture

Skin Irritation - Category 2 H315 Causes skin irritation.

Eye damage/irritation – Category 2A H319 Causes serious eye irritation.

Sensitization - skin – Category 1 H317 May cause an allergic skin reaction.

Aquatic Acute 1 H400 Very toxic to aquatic life.

Aquatic Chronic 1 H410 Very toxic to aquatic life with long lasting effects.

Label elements

GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

—CA—

Safety Data Sheet

according to WHMIS 2023 and HCS 2024

Page 2/13

Date of issue 10/27/2025

Version number 6.04

Revision: 04/22/2025

Trade name: 8329TFS-A

(Contd. of page 1)

Hazard pictograms



GHS07 GHS09

Signal word Warning

Hazard-determining components of labeling:

phenol, polymer with formaldehyde, glycidyl ether
oxirane, mono[(C12-14-alkyloxy)methyl] derivs
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane

Hazard statements

H315 Causes skin irritation.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H410 Very toxic to aquatic life with long lasting effects.

Precautionary statements

P102 Keep out of reach of children.
P280 Wear protective gloves / eye protection.
P302+P352 IF ON SKIN: Wash with plenty of water.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333+P313 If skin irritation or rash occurs: Get medical advice.
P337+P313 If eye irritation persists: Get medical advice.
P501 Dispose of contents and container in accordance with local, regional, and national regulations.

Other hazards

When exposed to extreme heat, this product may produce harmful zinc oxide and aluminum oxide fumes.

3 Composition/Information on ingredients

Chemical characterization: Mixtures

Description: Mixture of the substances listed below with nonhazardous additions.

Dangerous components:

1344-28-1	aluminium oxide	40.0% w/w
28064-14-4	phenol, polymer with formaldehyde, glycidyl ether Alternative CAS number: 9003-36-5	26.0% w/w
1314-13-2	zinc oxide	25.0% w/w
68609-97-2	oxirane, mono[(C12-14-alkyloxy)methyl] derivs	4.0% w/w
1675-54-3	2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane Consisting of: 25068-38-6 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)	2.0% w/w

(Contd. on page 3)

—CA—



Safety Data Sheet

according to WHMIS 2023 and HCS 2024

Page 3/13

Date of issue 10/27/2025

Version number 6.04

Revision: 04/22/2025

Trade name: 8329TFS-A

		(Contd. of page 2)
1333-86-4	Carbon black	0.7% w/w

4 First-aid measures

· Description of first aid measures

· After inhalation:

Remove person to fresh air and keep comfortable for breathing.
If symptoms persist consult doctor.

· After skin contact:

Wash with plenty water.
If skin irritation or rash occurs: Get medical advice or attention.
Take off contaminated clothing and wash it before reuse.

· After eye contact:

Rinse cautiously with water for 20 minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If eye irritation persists: Get medical advice or attention.

· After swallowing:

Rinse mouth.
Do NOT induce vomiting.
If symptoms persist consult doctor.

· Most important symptoms and effects, both acute and delayed

See section 11 for additional information.

· Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

· Extinguishing media

· Suitable extinguishing agents:

CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· Special hazards arising from the substance or mixture

Not flammable or combustible, but burns if involved in a fire. Produces irritating smoke of unknown toxicity in fires.
Prevent fire-fighting wash from entering waterway or sewer system.
Inhalation of metal fumes may cause metal fever and irritate the respiratory tract.
The flu-like symptoms of metal fever may be delayed, occurring 4 to 12 hours after exposure.

· Hazardous combustion products:

Carbon Oxides (CO_x)
Nitrogen Oxides (NO_x)
toxic metal fumes

(Contd. on page 4)

—CA—



Safety Data Sheet

according to WHMIS 2023 and HCS 2024

Page 4/13

Date of issue 10/27/2025

Version number 6.04

Revision: 04/22/2025

Trade name: 8329TFS-A

(Contd. of page 3)

- **Advice for firefighters**
 - **Protective equipment:** Wear self-contained breathing apparatus and full fire-fighting turn-out gear.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**

Avoid breathing the fumes or vapors.
Remove or keep away all sources of extreme heat or open flames.
- **Environmental precautions:**

Avoid release to the environment.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Collect liquid in a sealable, chemical-resistant container.
Wash residue with a paper towel and place dirty towels in container.
Use soap and water to remove the last traces of residue.
- **Reference to other sections**

See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Precautions for safe handling**

Wear protective gloves and eye protection.
Wash hands and exposed skin thoroughly after handling.
Take off contaminated clothing and wash it before reuse.
Collect spillage.
Contaminated work clothing should not be allowed out of the workplace.

 - **Information about protection against explosions and fires:** No special measures required.
- **Conditions for safe storage, including any incompatibilities**
 - **Storage:**
 - **Requirements to be met by storerooms and receptacles:**

Keep in a dry and clean area, away from incompatible substances
 - **Information about storage in one common storage facility:** Not required.
 - **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

— CA —
(Contd. on page 5)

Safety Data Sheet

according to WHMIS 2023 and HCS 2024

Page 5/13

Date of issue 10/27/2025

Version number 6.04

Revision: 04/22/2025

Trade name: 8329TFS-A

(Contd. of page 4)

8 Exposure controls/ Personal protection

· Control parameters

· Components with limit values that require monitoring at the workplace:

1333-86-4 Carbon black	
EL (Canada)	TWA: 3 mg/m ³ IARC 2B
EV (Canada)	TWA: 3.5 mg/m ³
PEL (USA)	TWA: 3.5 mg/m ³
REL (USA)	TWA: 3.5* mg/m ³ *0.1 in presence of PAHs; See Pocket Guide Apps.A+C
TLV (USA)	TWA: 3* mg/m ³ *inhalable fraction, A3

· **Additional information:** The lists that were valid during the creation were used as basis.

· Exposure controls

· **Appropriate engineering controls** No further data; see section 7.

· Personal protective equipment:

· General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.

· Breathing equipment:

If the product is heated or worker has a known allergic reaction, consider using a full mask with organic vapor cartridge or with an independent air supply.

· Protection of hands:

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.



Protective gloves: EN374

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 6)

—CA—

Safety Data Sheet

according to WHMIS 2023 and HCS 2024

Page 6/13

Date of issue 10/27/2025

Version number 6.04

Revision: 04/22/2025

Trade name: 8329TFS-A

(Contd. of page 5)

· Eye protection:



Safety glasses or tightly sealed goggles: EN 166

* 9 Physical and chemical properties

· Information on basic physical and chemical properties

· Physical state	Liquid
· Form:	Viscous
· Color:	Dark grey
· Odor:	Light
· Odor threshold:	Not available
· Melting point/Melting range:	Not available
· Boiling point/Boiling range:	207 °C (404.6 °F)
· Flammability:	Non flammable
· Explosion limits:	
· Lower:	Not applicable
· Upper:	Not applicable
· Flash point:	149 °C (300.2 °F)
· Auto igniting:	Not determined
· Decomposition temperature:	Not available
· pH-value:	Not applicable.
· Viscosity:	
· Kinematic at 20 °C (68 °F):	>20.5 mm ² /s
· Dynamic:	Not applicable.
· Solubility in / Miscibility with	
· Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not available
· Vapor pressure:	Not available
· Density at 20 °C (68 °F):	2.17 g/cm ³ (18.1087 lbs/gal)
· Relative density at 25 °C (77 °F):	2.2
· Vapor density (air=1):	Not available
· Particle characteristics	Not applicable

· Other information

· Important information on protection of health and environment, and on safety.

· Ignition temperature:	Product is not selfigniting.
· Danger of explosion:	Product does not present an explosion hazard.
· Organic solvents:	Not available
· VOC content:	0.000 %
· Solids content:	68.0 %

(Contd. on page 7)

—CA—

Safety Data Sheet

according to WHMIS 2023 and HCS 2024

Page 7/13

Date of issue 10/27/2025

Version number 6.04

Revision: 04/22/2025

Trade name: 8329TFS-A

(Contd. of page 6)

· Evaporation rate	Not determined.
---------------------------	-----------------

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability** Chemically stable at normal temperatures and pressures.
 - **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid**
Avoid ignition sources, open flames, and incompatible substances.
Do not use in away that forms mist or aerosolizes the product.
- **Incompatible materials:**
Strong oxidizing agents
Strong acids
Strong bases
Ammonia
Ethylene oxides
Halogenated compounds
Flax oils
- **Hazardous decomposition products:**
No dangerous decomposition products known.
Hazardous combustion products: see section 5.

11 Toxicological information

- **Information on toxicological effects**
 - **Acute toxicity:**

· LD/LC50 values that are relevant for classification:		
1344-28-1 aluminium oxide		
Oral	LD50	>2,000 mg/kg (rat)
Inhalative	LC50/4 h	>2 mg/L (mouse)
28064-14-4 phenol, polymer with formaldehyde, glycidyl ether		
Oral	LD50	>2,000 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rabbit)
1314-13-2 zinc oxide		
Oral	LD50	7,950 mg/kg (rat)
68609-97-2 oxirane, mono[(C12-14-alkyloxy)methyl] derivs		
Oral	LD50	19,200 mg/kg (rat)

(Contd. on page 8)

—CA—

Safety Data Sheet

according to WHMIS 2023 and HCS 2024

Page 8/13

Date of issue 10/27/2025

Version number 6.04

Revision: 04/22/2025

Trade name: 8329TFS-A

(Contd. of page 7)

Dermal	LD50	4,500 mg/kg (rat)
1675-54-3 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane		
Oral	LD50	11,400 mg/kg (rat)
1333-86-4 Carbon black		
Oral	LD50	>15,400 mg/kg (rat)
Dermal	LD50	>3,000 mg/kg (rabbit)

- **Primary irritant effect:**
 - **on the skin:** Irritant to skin and mucous membranes.
 - **on the eye:** Irritating effect.
- **Sensitization:** Sensitization possible through skin contact.
- **Summary of effects and symptoms by route of exposure**
 - **Eyes:** redness, serious irritation
 - **Skin:**
 - dry skin, redness
 - rash, allergic contact dermatitis
 - irritation
 - **Inhalation:**
 - cough
 - sore throat
 - irritation of the respiratory tract
 - **Swallowed:**
 - irritation
 - abdominal pain
 - nausea
 - vomiting
 - diarrhea
- **Delayed and immediate effects as well as chronic effects from short and long-term exposure**

Prolonged and repeated exposure to uncured epoxy hardener may lead to skin sensitization.
- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

· **Carcinogenic categories**

· IARC (International Agency for Research on Cancer)		
1675-54-3	2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	3
1333-86-4	Carbon black	2B
· NTP (National Toxicology Program)		
None of the ingredients is listed.		

— CA —

(Contd. on page 9)

Safety Data Sheet

according to WHMIS 2023 and HCS 2024

Page 9/13

Date of issue 10/27/2025

Version number 6.04

Revision: 04/22/2025

Trade name: 8329TFS-A

(Contd. of page 8)

12 Ecological information

· Toxicity

· Aquatic toxicity:

Very toxic to aquatic life with long lasting effect.
Avoid release to the environment.
Collect spillage.

28064-14-4 phenol, polymer with formaldehyde, glycidyl ether	
LC50 96h	>1–≤10 mg/L (not defined) In Europe, similar epoxy resin mixtures with CAS 28064-14-4 are generally classified as chronic category 2 marine pollutant due to LC50 96 h of >1 mg/L but ≤10 mg/L.
1314-13-2 zinc oxide	
LC50	0.042 mg/L (fish)
1333-86-4 Carbon black	
EC50/ 24 h	>5,600 mg/L (aquatic invertebrates)
EC50/ 72 h	>10,000 mg/L (aquatic algae and cyanobacteria)
EC0/ 3 h	>800 mg/L (microorganisms)
LC50	>1,000 mg/L (fish)

· **Persistence and degradability** Not readily biodegradable.

· **Bioaccumulative potential** No further relevant information available.

· **Mobility in soil** No further relevant information available.

· Results of PBT and vPvB assessment

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **Other adverse effects** No further relevant information available.

13 Disposal considerations

· Waste treatment methods

· **Recommendation:** This material and its container must be disposed of as hazardous waste.

· Uncleaned packagings:

· Recommendation:

Containers may still present a chemical hazard/ danger when empty.
Dispose of contents in accordance with all local, regional, national, and international regulations.
Where possible retain label warnings and SDS and observe all notices pertaining to the product.

— CA —
(Contd. on page 10)

Safety Data Sheet

according to WHMIS 2023 and HCS 2024

Page 10/13

Date of issue 10/27/2025



Version number 6.04

Revision: 04/22/2025

Trade name: 8329TFS-A

(Contd. of page 9)

14 Transport information

<ul style="list-style-type: none"> UN-Number DOT/TDG, IMDG, IATA 	UN3082
<ul style="list-style-type: none"> UN proper shipping name DOT/TDG IMDG IATA 	<p>Environmentally hazardous substance, liquid, n.o.s. (phenol, polymer with formaldehyde, glycidyl ether, zinc oxide)</p> <p>NOT REGULATED by Sea IMDG per 2.10.2.7 for sizes 5L or less.</p> <p>ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (phenol, polymer with formaldehyde, glycidyl ether, zinc oxide)</p> <p>NOT REGULATED by Air IATA Special Provision A197 for sizes 5L or less.</p> <p>Environmentally hazardous substance, liquid, n.o.s. (phenol, polymer with formaldehyde, glycidyl ether, zinc oxide)</p>
<ul style="list-style-type: none"> Transport hazard class(es) DOT/TDG, IMDG  <ul style="list-style-type: none"> Class Label 	<p>9 Miscellaneous dangerous substances and articles</p> <p>9</p>
<ul style="list-style-type: none"> IATA  <ul style="list-style-type: none"> Class Label 	<p>9 Miscellaneous dangerous substances and articles</p> <p>9</p>
<ul style="list-style-type: none"> Packing group DOT/TDG, IMDG, IATA 	III
<ul style="list-style-type: none"> Environmental hazards: Marine pollutant: Special marking (IATA): 	<p>MARINE POLLUTANT</p> <p>ENVIRONMENTALLY HAZARDOUS</p> <p>Symbol (fish and tree)</p>
<ul style="list-style-type: none"> Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code 	Not applicable.
<ul style="list-style-type: none"> Transport/Additional information: 	<p>Not Regulated</p> <p>8329TFS-25ML, 8329TFS-50ML, MC002977</p>

(Contd. on page 11)

—CA—



Safety Data Sheet

according to WHMIS 2023 and HCS 2024

Page 11/13

Date of issue 10/27/2025

Version number 6.04

Revision: 04/22/2025

Trade name: 8329TFS-A

(Contd. of page 10)

· DOT/TDG	
· Quantity limitations	On passenger aircraft/rail: 450 L On cargo aircraft only: 450 L
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· Special precautions for user	
· Hazard identification number (Kemler code):	Not applicable. 90
· EMS Number:	F-A,S-F
· Stowage Category	A
· UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (PHENOL, POLYMER WITH FORMALDEHYDE, GLYCIDYL ETHER, ZINC OXIDE), 9, III

* 15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· **OSHA Hazard Communication Standard (29 CFR Part 1900)**

The safety data sheet and label comply with HCS 2024.

· **Hazardous Products Act (R.S.C., 1985, c. H-3)**

The safety data sheet and label comply with the Hazardous Product Act and WHMIS 2023.

· **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

1344-28-1 aluminium oxide

1314-13-2 zinc oxide

· **TSCA (Toxic Substances Control Act):**

All components have the value ACTIVE.

· **Hazardous Air Pollutants**

None of the ingredients is listed.

· **Proposition 65**

· **Chemicals known to cause cancer:**

1333-86-4 Carbon black

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

(Contd. on page 12)

— CA —

Safety Data Sheet

according to WHMIS 2023 and HCS 2024

Page 12/13

Date of issue 10/27/2025

Version number 6.04

Revision: 04/22/2025

Trade name: 8329TFS-A

(Contd. of page 11)

· Chemicals known to cause reproductive toxicity for males:	
None of the ingredients is listed.	
· Chemicals known to cause developmental toxicity:	
None of the ingredients is listed.	

· Carcinogenic categories		
· TLV (Threshold Limit Value)		
1344-28-1	aluminium oxide	A4
1333-86-4	Carbon black	A4
· NIOSH-Ca (National Institute for Occupational Safety and Health)		
1333-86-4	Carbon black	

· Canadian substance listings:	
· Canadian Domestic Substances List (DSL)	
All ingredients are listed.	
· Canadian Non-Domestic Substances List (NDSL)	
None of the ingredients is listed.	
· Canadian Ingredient Disclosure list (limit 0.1%)	
None of the ingredients is listed.	
· Canadian Ingredient Disclosure list (limit 1%)	
1344-28-1	aluminium oxide
1314-13-2	zinc oxide
1675-54-3	2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane

· **HMIS-ratings (scale 0 - 4)**

Health = * 2
Fire = 1
Reactivity = 0

· **Europe**

· **RoHS (Restriction of Hazardous Substances Directive)**

This product does not contain any lead, cadmium, mercury, hexavalent chromium, PBB's, PBDE's, DEHP, BBP, DBP, or DIBP and complies with European RoHS regulations.

· **WEEE (Waste Electrical and Electronic Equipment Directive)**

This product is not a piece of electrical or electronics equipment, and is therefore not governed by this regulation.

· Per- and polyfluoroalkyl substances (PFAS)	
None of the ingredients is listed.	

— CA —

(Contd. on page 13)



Safety Data Sheet

according to WHMIS 2023 and HCS 2024

Page 13/13

Date of issue 10/27/2025

Version number 6.04

Revision: 04/22/2025

Trade name: 8329TFS-A

(Contd. of page 12)

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** Regulatory department
- **Contact:** sds@mgchemicals.com
- **Version number of previous version:** 6.03
- **Date of preparation** 10/27/2025
- **Abbreviations and acronyms:**
 - IMDG: International Maritime Code for Dangerous Goods
 - DOT: US Department of Transportation
 - IATA: International Air Transport Association
 - EINECS: European Inventory of Existing Commercial Chemical Substances
 - ELINCS: European List of Notified Chemical Substances
 - CAS: Chemical Abstracts Service (division of the American Chemical Society)
 - VOC: Volatile Organic Compounds (USA, EU)
 - LC50: Lethal concentration, 50 percent
 - LD50: Lethal dose, 50 percent
 - PBT: Persistent, Bioaccumulative and Toxic
 - vPvB: very Persistent and very Bioaccumulative
 - NIOSH: National Institute for Occupational Safety
- *** Data compared to the previous version altered.**

— CA —