

Digital Rockwell Hardness Indicator



Features:

- Resolution: 0.1 HR
- Replace manual indicator directly
- Data memory is up to 999 readings
- Ready to measure immediately without calibration
- Scales convert automatically
- Auto power off

3 DIFFERENT MODELS AVAILABLE



Accuracy	±0.5HR
Resolution	0.1HR
Display	128 x 64 Graphic LCD with backlight
Memory	999 readings
Scales 900330-DI/ 900331-DI 900345-DI	HRC, HRA, HRB, HRD, HRE, HRF, HRG, HRK, HRH, HR15N, HR30N, HR45N, HR15T, HR30T, HR45T
Convert Scales	HB, HV
Power	Ni-H Rechargeable battery pack
Charger	Input: 100~240/50~60Hz; output 5V 1A/DC
Operating Environment	Temperature: -10°C~+50°C; Humidity: 20%~85%
Storage Environment	Temperature: -30°C~+70°C; Humidity: 5%~95%
Dimensions	114 x 37 mm
Weight	420g
Accessories	Charger
Standard	ASTM E18, ISO 6508

900330-9500 Digital Indicator for 900-330 & HR150

900331-9500 Digital Indicator for 900-331/Starrett 3814 & SPI 15-817-0

900345-9500 Digital Indicator for 900-345