



Directions:

Staticide® topicals can be applied by spraying, wiping, dipping, transfer roller coating, gravure coating, or flexographic printing. Having a similar viscosity to water, for high production applications mechanically apply solution by implementing fine-mist sprayers or foam rollers. The product can also be manually sprayed using a trigger sprayer at 8-12" from desired surface. For carpet, apply so that fibers absorb anti-stat. It should feel damp but not saturated. Allow solution to dry.

SDS available at www.aclstaticide.com.

Product #520

4-oz bottle; 12 per case (finger-pump sprayer)

Product #2005

1-quart bottle; 12 per case (trigger sprayer)

Product #2002

1-gallon bottle; 4 per case

Product #2002-5

5-gallon pail

Product #2002-2

50-gallon drum

Heavy Duty Staticide®

Static Control for Porous Surfaces

Heavy Duty Staticide® anti-static topical is easy to use and highly effective in controlling electrostatic charges in industrial manufacturing and static-sensitive environments.

As a key component in any static control program, it is non-toxic, non-flammable, and non-staining. This ready-to-use solution formulated specifically for porous surfaces is ideal for eliminating static on carpets, upholstery, and fabrics.

Use Heavy Duty Staticide® to eliminate:

- Dust attraction - keep equipment cleaner longer
- Damage potential to sensitive electronic components and subassemblies during manufacture, testing, packaging, shipping, and receiving
- Data errors, paper jams, and other glitches in office machines
- Jamming or slipping of paper, plastics, and other materials during printing, packaging, and converting
- Ignition of combustible vapors, dust, and solvents, causing fire or explosion
- Irregularities caused by static in quality printing, heat sealing, silk screening, lamination, and other special applications
- Static discharge on workbenches and production surfaces

Features:

- ❖ Formulated for porous surfaces.
- ❖ Exceeds MIL-B-81705 and NFPA-56A electrostatic decay criteria
- ❖ Meets requirements for topical anti-stats as listed in the Military Handbook DOD-HDBK-263
- ❖ Proven effective in relative humidity below 15%
- ❖ Decays static in less than 2 seconds
- ❖ Surface resistance between 10^9 - 10^{10} ohms
- ❖ One gallon covers approximately 2000 sq.ft. per gallon
- ❖ Lasts from weeks to months depending on application

ACL Staticide®

840 W. 49th Place · Chicago, IL 60609
800.782.8420 · 847.981.9212 · fax 847.981.9278
info@aclstaticide.com · www.aclstaticide.com



ACL Inc. registered to
ISO-9001 : 2015
Certificate No. 10002746