



## 4018 Staticide® Acrylic Floor Finish

### Low Cost Protection Against ESD

Staticide® 4018 Acrylic Floor Finish offers static protection at a reasonable price. This economical formula leaves a durable, glossy finish that can last up to six months with proper maintenance. This ESD polish is a popular choice for companies that require frequent cleaning.

Easy to apply and maintain, Staticide® 4018 Acrylic Floor Finish leaves floors with a surface resistance of  $10^8$  -  $10^9$  ohms, complying with ANSI/ESD S20.20 guidelines. This water-based formula is RoHS and REACH compliant, biodegradable, non-flammable, and free of acids, alkalis, ammonia, formaldehyde and phthalates.

#### Directions:

Clean floor and apply two thin coats of floor finish with a dedicated rayon mop. Wait one hour between coats. Consult application procedure for details and precise instructions.

#### Maintenance:

Sweep or damp mop daily to remove dirt. Periodically clean with a 1:1 dilution of water and floor finish. Apply a thin top coat of floor finish every 4 – 6 weeks. For heavy cleaning, use the 4100 Restorer Cleaner. Consult maintenance procedure for details and precise instructions.

**Product #4018-1**  
4 gallons per case

**Product #4018-5**  
5-gallon pail

**Product #4018-2**  
54-gallon drum

#### Ideal for the following applications:

- Production areas
- Warehousing
- Shipping areas
- Electronics repair facilities

- Coverage: 1,500 - 2,000 square feet per gallon
- Non-toxic; biodegradable
- Non-volatile solids: 18± 5%
- Strip cycle: 6 months
- Suitable to use on vinyl, linoleum, and ceramic tiles
- Surface resistivity:  $10^8$  –  $10^9$  ohms per square (average)
- Low V.O.C.
- Water-based acrylic