

MIPRO TRUE DIGITAL

Innovation · Reliability · Performance

ACT-800T Digital Encryptable Bodypack Transmitter

- MU55LX Lavalier included
- Aluminum polymer laminate housing
- Multifunction backlit LCD
- AF metering
- 13 hours - 1 ICR 18500 rechargeable battery or 2 AA alkaline batteries
- USB Type-C charging port
- Direct and remote mute control
- Selectable input impedance
- Selectable RF output
- Selectable low cut
- Selectable mute functionality
- Selectable limiting
- Selectable phase control
- Menu lockout feature



Specifications

Frequency Bands	5UA: 482~554 MHz 5NU: 554~604 MHz
RF Power Output	10mW/50mW (switchable)
Encryption	256 bit
Spurious Emission	<4 nW
Oscillation Mode	PLL Synthesized
Frequency Stability	≤±0.005% (-10~+60°C)
Modulation Type	Digital Modulation
Audio Compression	DSP Inertial Coding
Input Impedance	Selectable mic or line
Battery	1 ICR 18500 rechargeable lithium battery OR 2 AA alkaline batteries
Battery Life	13 hours
Dimensions	63(W)×82(H)×22(D)mm / 2.5(W)×3.2(H)×0.9(D)"
Weight	Approx. 87g / 3oz, excluding batteries