

Model 1026

Provides a variety of functions: megohmmeter, DC voltmeter, AC voltmeter, ohmmeter and continuity testing

► SPECIFICATIONS

| MODEL | 1026 | |
|--------------------------|---|---|
| INSULATION TESTS | | |
| Test Voltage | 250V 500V 1000V | 1k Ω to 4000M Ω 1k Ω to 4000M Ω 1k Ω to 4000M Ω |
| Accuracy | <2000M Ω ≥2000M Ω | ±3% of Reading + 5cts ±5% of Reading + 5cts |
| RESISTANCE TESTS | | |
| Measurement Range | Auto ranging to 4000 Ω | |
| Resolution | 0.1 to 1 Ω | |
| Accuracy | ±1% of Reading + 5cts | |
| CONTINUITY TESTS | | |
| Measurement Range | Displays and beeps below 40 Ω | |
| Active | ≤40 Ω | |
| Protection | 600Vrms | |
| VOLTAGE TESTS | | |
| AC VOLTAGE | | |
| Measurement Range | 0 to 600V | |
| Accuracy | ±1.5% of Reading + 5cts | |
| DC VOLTAGE | | |
| Measurement Range | 0 to 600V | |
| Accuracy | ±1% of Reading + 3cts | |
| ELECTRICAL | | |
| Power Source | Eight 1.5V AA Alkaline batteries (included) | |

► PRODUCT INCLUDES

Test leads, alligator clips, batteries, soft carrying case and user manual.



► FEATURES

- Test voltage selections of 250V, 500V and 1000V
- Insulation measurements to 4000M Ω
- Resistance measurements to 4000 Ω
- Continuity test
- Continuity beeper
- 600VAC/DC test voltage range
- Large, easy-to-read digital display
- Data hold switch
- Test button may be “locked-on” for three minutes for hands-free operation
- Automatic discharge when test button is released
- Low battery indicator
- Includes test leads and soft carrying case
- EN 61010-1, 1000V CAT II, 600V CAT III

| CATALOG NO. | DESCRIPTION |
|-------------|--|
| 2117.72 | Megohmmeter Model 1026 (Digital, 250V, 500V, 1000V, 4000 Ω , V) |