

Special product features

MEGOHMMETERS

Digital/Analog & Multi-Function Voice, Data, Video Cable Testing

Models 1030, 1040 & 1045

For motors, cables, switchgear and general applications



Learn how to measure insulation on telephone cables



SPECIFICATIONS

MODELS	1030	1040	1045	
INSULATION TESTS				
Test Voltage	250V 500V 1000V	50kΩ to 2000MΩ (2GΩ) 100kΩ to 2000MΩ (2GΩ) —	— 100kΩ to 2000MΩ (2GΩ) 200kΩ to 2000MΩ (2GΩ)	50kΩ to 2000MΩ (2GΩ) 100kΩ to 2000MΩ (2GΩ) 200kΩ to 2000MΩ (2GΩ)
Short Circuit Current	≤3mA			
Accuracy	<40MΩ ≥40MΩ	3% of Reading ± 5cts 3% of Reading ± 2cts		
Voltage Test/Safety Check	0 to 600Vac/dc			
Voltage Warning Indicator	>25V			
Test Inhibition	Yes >25V			
RESISTANCE TESTS (MODELS 1040 AND 1045)				
Measurement Range	—	0.0 to 400kΩ		
Test Voltage	—	7 to 9V		
Test Current	—	600μA		
Accuracy	>4kΩ	3% of Reading ± 1ct		
CONTINUITY TESTS				
Measurement Range	0.00 to 19.99Ω			
Test Current	≥200mA			
Accuracy	3% of Reading ± 1ct			
ELECTRICAL				
Power Source	Six 1.5V AA Alkaline batteries (included)			

PRODUCT INCLUDES

1040 & 1045 Field Kit

Megohmmeter, soft carrying case, field case, two color-coded leads, two alligator clips, black test probe, remote test probe, batteries and user manual.



1035 Field Kit

Megohmmeter, soft carrying case, field case, color-coded leads, alligator clips, black test probe, two grip probes, remote test probe, batteries, and user manual.



Soft carrying case
Included with all Models



Hands-free carrying case
Catalog #2118.99 (optional)



Models 1035 & 1039

For voice, data and video cable applications

► FEATURES

- True Megohmmeter®
- Test voltage combinations of 250V, 500V and 1000V
- Insulation measurements to 2000MΩ (2GΩ)
- Automatic test inhibition (if live sample >25V)
- Automatic discharge for operator safety
- Multi-line, 4000-count, backlit, digital display with analog bargraph
- Resistance measurements to 400kΩ
- Continuity with 200mA test current
- Timer function for easy DAR and PI (Model 1045)
- Slip-proof, over-molded, protective rubber housing for rugged field use
- Includes test leads and soft carrying case
- Test voltage combinations of 50V, 100V, 250V and 500V (Model 1035)
- Insulation measurement to 20,000MΩ (20GΩ) (Model 1035)
- Insulation measurement to 400MΩ (Model 1039)
- Capacitance measurement to 4000nF (Model 1039)
- Cable length measurement to 80.0km (>264,000 ft) (Model 1039)
- Ideal for telecom testing and high sensitivity measurements
- Backlit display (Models 1035, 1039, 1040 & 1045)



► SPECIFICATIONS

MODELS	1035	1039
INSULATION TESTS		
Test Voltage	50V 100V 250V 500V	10kΩ to 2000MΩ (2GΩ) 20kΩ to 2000MΩ (2GΩ) 50kΩ to 20,000MΩ (20GΩ) 100kΩ to 20,000MΩ (20GΩ)
Open Circuit Voltage	<75V @ 50V, <150V @ 100V, <375V @ 250V, <750V @ 500V	
Short Circuit Current	≤3mA	
Accuracy	±3% of Reading ± 5cts	
Voltage Test/Safety Check	0 to 600Vac/bc	
Voltage Warning Indicator	>25V	
Test Inhibition	Yes >25V	
RESISTANCE TESTS		
Measurement Range	0.0 to 400kΩ	0.0 to 40.0kΩ
Test Voltage	7 to 9V	
Test Current	600μA < 400Ω; 6μA > 40Ω	
Accuracy	>400kΩ ±3% of Reading ± 1ct	
CURRENT TESTS		
AC/DC Current Range	–	0.00 to 400mA (240A) (with probe option)
CAPACITANCE/CABLE LENGTH		
Capacitance Range	–	0.00 to 4000nF
Cable Length Range	–	0.000 to 80.0km
VOLTAGE TESTS		
Measurement Range	–	0 to 400Vac
Accuracy	–	±3% of Reading ± 1ct
ELECTRICAL		
Power Source	Six 1.5V AA Alkaline batteries (included)	

CATALOG NO. DESCRIPTION

2116.89	Megohmmeter Model 1030 (Digital w/Analog Bargraph, 250V, 500V)
2116.92	Megohmmeter Model 1040 (Digital w/Analog Bargraph, Alarm, Backlight, 500V, 1000V, 400kΩ, Continuity)
2116.93	Megohmmeter Model 1045 (Digital w/Analog Bargraph, Alarm, Timer, Backlight, 250V, 500V, 1000V, 400kΩ, Continuity)
2117.30	Megohmmeter Model 1040 Field Kit (Model 1040, Remote Test Probe & Field Case)
2117.31	Megohmmeter Model 1045 Field Kit (Model 1045, Remote Test Probe & Field Case)
2116.90	Megohmmeter Model 1035 (Digital w/Analog Bargraph, Alarm, Backlight, 50V, 100V, 250V, 500V, 400kΩ)
2116.91	Megohmmeter Model 1039 (Digital w/Analog Bargraph, Alarm, Timer, ΔRel, Backlight, 50V, 100V, mA, nF, km)
2115.42	Megohmmeter Model 1035 Field Kit (Model 1035, Remote Test Probe & Field Case)

Accessories (Optional)

2118.97	Remote Test Probe
2118.98	Field Case (Waterproof)
2118.99	Hands-Free Carrying Case

