

AE402 Indicator



The AE402 indicator is a stainless steel indicator that has a range of features for many different weighing applications. Whether these indicators are used outdoors, on a loading dock or in a warehouse or industrial buildings the stainless steel housing is sealed for IP66 wash down environments and the quality construction is built tough to handle even the most demanding tasks. The sleek compact design comes complete with the wall mount bracket and hardware to place it where you want it. A built-in rechargeable battery with low battery indicator, check weighing limit LED, an easy-to-use keypad with highlighted tare key and a large backlit display complete the AE402 indicator.

Adam Equipment has been manufacturing balances and scales for over 35 years, providing professionals worldwide with quality products that are always the perfect balance of speed, performance, and value.



AE ADAM[®]
THE RIGHT BALANCE
Speed, Performance, Value

AE 402 Highlights:

Stainless steel housing is grade 304 for superior durability to withstand heavy industrial applications.

Sealed indicator and keypad allows the AE402 to be used in wash down applications, the unit is IP66 rated for dust and moist environments. An internal rechargeable battery means that you do not need to be attached to a power supply for operation.

Check weighing products is faster than ever with the AE402 indicator. The colour coded LED indicators, Amber, green and red quickly show you if the sample is within acceptable limits, over or under. The bright large backlit display is easy to read in any lighting condition.

Easy to use wash down indicator with large backlit display and checkweighing lights

Features

- Large backlit LCD
- Colour coded keys
- Rechargeable battery
- Bi-directional RS-232 interface
- Bracket for wall mounting
- Hold function
- Wash down meets IP66 standards
- Stainless steel housing
- Checkweighing LED lights
- Capacity tracker

Applications

- Weighing
- Animal / Dynamic Weighing
- Accumulation
- Check weighing
- Percentage weighing



Large backlit display



Stainless steel indicator



Wash down IP66 rated

Technical Specifications

Model	AE 402 Indicator
Maximum Capacity	1.5kg to 750,000kg
Readability	0.0001kg to 50kg
Loadcells	Up to 4 loadcells 350 ohms Minimum 87 ohms Maximum 1120 ohms
Excitation Voltage (each loadcell)	5Vdc
Sensitivity	0.15uv/d
Zero Range	0 -10mv
Units of Measure	Kilogram (kg), Pound (lb), Gram (G), Newtons
Power Supply	12VDC 800mA adapter
Display	6 digit LCD digital display - Green backlit display 40mm digits
Indicator Housing	SS grade 304 - AE 402 IP66 rated
Net Weight	2kg