



AGM  
GLOBAL  
VISION

# ASP

## THERMAL IMAGING MONOCULAR



The AGM ASP represents the line of the most technologically advanced thermal imaging monoculars currently existing on the market. Based on FLIR Tau 2 VOx microbolometer cores and made of high-grade aircraft aluminum alloy the unit guarantees durability and outstanding performance even to the most sophisticated users.

This uncooled, long-wave infrared, magnified thermal imaging camera by AGM is designed for fulfilling of both day and night missions irrespective of the environment and weather factors, while a wide variety of objective lenses (25 mm, 50 mm, and 75 mm) enables the operator to use the device as both a compact, pocket-sized thermal imaging monocular, or as a long-range observation tool.

The ASP thermal imaging monocular can be easily connected to extended battery pack to increase operational time. Optional WiFi module for live video streaming and recording is also available.

- FLIR Tau 2 17 $\mu$ m pitch thermal sensor
- Durable and lightweight design
- Easy and intuitive operation
- Manually adjustable eyepiece and objective lens
- A wide variety of color palettes
- Digital zoom: 1x, 2x, 4x, and 8x
- Waterproof
- Integral MIL-STD-1913 rails on unit for optional accessories
- External Wi-Fi module via micro USB
- Optional video recording
- Powered by two standard CR123A batteries
- External power supply via micro USB
- Limited 3-Year Warranty



Equipment described herein is subject to US export regulations and may require a license prior to export. Diversion contrary to US law is prohibited.

[www.agmglobalvision.com](http://www.agmglobalvision.com)

## SPECIFICATIONS

	Asp TM50-336	Asp TM75-336	Asp TM25-640	Asp TM50-640	Asp TM75-640
Detector Type	FLIR Tau 2 336x256 17µm Uncooled Microbolometer		FLIR Tau 2 640x512 17µm Uncooled Microbolometer		
Refresh Rate	60 Hz				
Start Up	3 seconds				
Lens System	50 mm; F/1.0	75 mm; F/1.0	25 mm; F/1.0	50 mm; F/1.0	75 mm; F/1.0
Optical Magnification	3.45x	5.2x	1x	2.1x	3.1x
Field of View (H x V)	7.8° x 5.9°	4.3° x 3.3°	24° x 20°	14.8° x 11.8°	8.3° x 6.6°
Digital Zoom	1x, 2x, 4x	1x, 2x, 4x	1x, 2x, 4x, 8x	1x, 2x, 4x, 8x	1x, 2x, 4x, 8x
Diopter Adjustment Range	-5 to +5 dpt	-5 to +5 dpt	-5 to +5 dpt	-5 to +5 dpt	-5 to +5 dpt
Focusing Range	5 m to infinity	10 m to infinity	2.5 m to infinity	5 m to infinity	10 m to infinity
Display Resolution	800x600				
Video Output	PAL (768x574 pixels) / NTSC (640x480 pixels)				
Temperature Imaging Palettes	White Hot, Black Hot, Fusion, Rainbow, Globow, Ironbow1, Ironbow2, Sepia, Color1, Color2, Ice-Fire, Rain, and OEM				
Interfacing	S620 Connector (Power In, Analog Video In/Out, Digital Video Recorder); Micro USB (External Battery Pack)				
Battery Type	Two CR123A 3V Lithium Batteries or CR123 Type Rechargeable Batteries with Voltage from 3.0V to 3.7V (2)				
Battery Life (Operating)	Up to 4 hr (optional up to 12 hrs)				
Operating Temperature Range	-40°C to +50°C (-40°F to +122°F)				
Weight	0.69 kg (1.5 lbs)	0.83 kg (1.8 lbs)	0.58 kg (1.2 lbs)	0.69 kg (1.5 lbs)	0.83 kg (1.8 lbs)
Overall Dimensions	220 x 72 x 60 mm (8.6 x 2.8 x 2.3 in)	248 x 89 x 89 mm (9.7 x 3.5 x 3.5 in)	196 x 72 x 56 mm (7.7 x 2.8 x 2.2 in)	220 x 72 x 60 mm (8.6 x 2.8 x 2.3 in)	248 x 89 x 89 mm (9.7 x 3.5 x 3.5 in)
Package Includes	Thermal imaging monocular, Lens Cloth, Soft Carrying Case, User Manual				

Specifications are subject to change without notice.



173 West Main Street | PO Box 962 | Springerville, AZ 85938  
Tel. 928.333.4300 | Fax 480.393.4882 | info@agmglobalvision.com

[www.agmglobalvision.com](http://www.agmglobalvision.com)