

SPECIFICATIONS

Ceiling Mount (Landscape only)

Wall Mount (Landscape only)

Desk Mount (Landscape only)

CMP-01+LMK-01

DTS-01

LMK-01, LMK-03, LMA-02

Pai	ne
-----	----

Panel	
Panel Type	LED-Backlit TFT LCD (IPS Technology)
Panel Size	42.5"
Max. Resolution	UHD 3840 x 2160
Pixel Pitch	0.245 mm
Brightness	700 cd/m ²
Contrast Ratio	1200:1
Viewing Angle (H/V)	178°/178°
Display Colour	1.07G
Response Time	5 ms
Surface Treatment	Anti-glare treatment (Haze 25%), 3H Hard Coating
Frequency	
Frequency (H)	31 kHz-92 kHz
Frequency (V)	48 Hz-85 Hz
Signal Input	
DisplayPort	x1
HDMI	2.0 x 3
DVI	29-Pin DVI-I x 1 (VGA)
Signal Output	
DisplayPort	1
External Control	
IR In	3.5 mm Phone Jack
IR Out	3.5 mm Phone Jack
RS232 In	2.5 mm Phone Jack
RS232 Out LAN	2.5 mm Phone Jack RJ45 x 1
Other Connectivity	KJ45 X I
USB	20 v 1 (Saniga Part / Madia Playback) / 20 v 1 (Madia Playback)
Micro SD Card Slot	2.0 x1 (Service Port / Media Playback) / 2.0 x1 (Media Playback) Yes
SDM Slot	SDM-S
Audio	ODIWI-0
Audio In	Stereo Audio Jack (3.5 mm)
Audio Out	Stereo Audio Jack (3.5 mm)
Internal Speakers	10W x 2
Power	
Power Requirements	AC 100-240V, 50/60 Hz
	AC 100-240V, 50/60 FIZ
On Mode	
	123 (On) < 0.5W
On Mode	123 (On)
On Mode Standby Mode	123 (On) < 0.5W
On Mode Standby Mode Off Mode	123 (On) < 0.5W 0W
On Mode Standby Mode Off Mode Power Supply	123 (On) < 0.5W 0W
On Mode Standby Mode Off Mode Power Supply Operating Conditions	123 (On) < 0.5W 0W Internal
On Mode Standby Mode Off Mode Power Supply Operating Conditions Temperature	123 (On) < 0.5W 0W Internal 0°C-40°C (32°F-104°F)
On Mode Standby Mode Off Mode Power Supply Operating Conditions Temperature Humidity	123 (On) < 0.5W 0W Internal 0°C-40°C (32°F-104°F)
On Mode Standby Mode Off Mode Power Supply Operating Conditions Temperature Humidity Storage Conditions	123 (On) < 0.5W 0W Internal 0°C-40°C (32°F-104°F) 20%-80% (non-condensing)
On Mode Standby Mode Off Mode Power Supply Operating Conditions Temperature Humidity Storage Conditions Temperature	123 (On) < 0.5W 0W Internal 0°C-40°C (32°F-104°F) 20%-80% (non-condensing) -20°C-60°C (-4°F-140°F)
On Mode Standby Mode Off Mode Power Supply Operating Conditions Temperature Humidity Storage Conditions Temperature Humidity	123 (On) < 0.5W 0W Internal 0°C-40°C (32°F-104°F) 20%-80% (non-condensing) -20°C-60°C (-4°F-140°F)
On Mode Standby Mode Off Mode Power Supply Operating Conditions Temperature Humidity Storage Conditions Temperature Humidity Mounting VESA FPMPMI Security	123 (On) < 0.5W 0W Internal 0°C-40°C (32°F-104°F) 20%-80% (non-condensing) -20°C-60°C (-4°F-140°F) 10%-90% (non-condensing)
On Mode Standby Mode Off Mode Power Supply Operating Conditions Temperature Humidity Storage Conditions Temperature Humidity Mounting VESA FPMPMI Security Kensington Security Slot	123 (On) < 0.5W 0W Internal 0°C-40°C (32°F-104°F) 20%-80% (non-condensing) -20°C-60°C (-4°F-140°F) 10%-90% (non-condensing)
On Mode Standby Mode Off Mode Power Supply Operating Conditions Temperature Humidity Storage Conditions Temperature Humidity Mounting VESA FPMPMI Security Kensington Security Slot Dimensions	123 (On) < 0.5W 0W Internal 0°C-40°C (32°F-104°F) 20%-80% (non-condensing) -20°C-60°C (-4°F-140°F) 10%-90% (non-condensing) Yes (200 x 200 mm)
On Mode Standby Mode Off Mode Power Supply Operating Conditions Temperature Humidity Storage Conditions Temperature Humidity Mounting VESA FPMPMI Security Kensington Security Slot Dimensions Product w/o Base (W x H x D)	123 (On) < 0.5W 0W Internal 0°C-40°C (32°F-104°F) 20%-80% (non-condensing) -20°C-60°C (-4°F-140°F) 10%-90% (non-condensing) Yes (200 x 200 mm) Yes 973.0 x 561.2 x 63.5 mm (38.3" x 22.1" x 2.5")
On Mode Standby Mode Off Mode Power Supply Operating Conditions Temperature Humidity Storage Conditions Temperature Humidity Mounting VESA FPMPMI Security Kensington Security Slot Dimensions Product w/o Base (W x H x D) Packaging (W x H x D)	123 (On) < 0.5W 0W Internal 0°C-40°C (32°F-104°F) 20%-80% (non-condensing) -20°C-60°C (-4°F-140°F) 10%-90% (non-condensing) Yes (200 x 200 mm)
On Mode Standby Mode Off Mode Power Supply Operating Conditions Temperature Humidity Storage Conditions Temperature Humidity Mounting VESA FPMPMI Security Kensington Security Slot Dimensions Product w/o Base (W x H x D) Packaging (W x H x D) Weight	123 (On) < 0.5W 0W Internal 0°C-40°C (32°F-104°F) 20%-80% (non-condensing) -20°C-60°C (-4°F-140°F) 10%-90% (non-condensing) Yes (200 x 200 mm) Yes 973.0 x 561.2 x 63.5 mm (38.3" x 22.1" x 2.5") 1070.0 x 680.0 x 141.0 mm (42.1" x 26.8" x 5.6")
On Mode Standby Mode Off Mode Power Supply Operating Conditions Temperature Humidity Storage Conditions Temperature Humidity Mounting VESA FPMPMI Security Kensington Security Slot Dimensions Product w/o Base (W x H x D) Packaging (W x H x D) Weight Product w/o Base	123 (On) < 0.5W 0W Internal 0°C-40°C (32°F-104°F) 20%-80% (non-condensing) -20°C-60°C (-4°F-140°F) 10%-90% (non-condensing) Yes (200 x 200 mm) Yes 973.0 x 561.2 x 63.5 mm (38.3" x 22.1" x 2.5") 1070.0 x 680.0 x 141.0 mm (42.1" x 26.8" x 5.6") 10.7 kg (23.6 lb)
On Mode Standby Mode Off Mode Power Supply Operating Conditions Temperature Humidity Storage Conditions Temperature Humidity Mounting VESA FPMPMI Security Kensington Security Slot Dimensions Product w/o Base (W x H x D) Packaging (W x H x D) Weight Product w/o Base Packaging	123 (On) < 0.5W 0W Internal 0°C-40°C (32°F-104°F) 20%-80% (non-condensing) -20°C-60°C (-4°F-140°F) 10%-90% (non-condensing) Yes (200 x 200 mm) Yes 973.0 x 561.2 x 63.5 mm (38.3" x 22.1" x 2.5") 1070.0 x 680.0 x 141.0 mm (42.1" x 26.8" x 5.6")
On Mode Standby Mode Off Mode Power Supply Operating Conditions Temperature Humidity Storage Conditions Temperature Humidity Mounting VESA FPMPMI Security Kensington Security Slot Dimensions Product w/o Base (W x H x D) Packaging (W x H x D) Weight Product w/o Base Packaging Regulation Approval	123 (On) < 0.5W 0W Internal 0°C-40°C (32°F-104°F) 20%-80% (non-condensing) -20°C-60°C (-4°F-140°F) 10%-90% (non-condensing) Yes (200 x 200 mm) Yes 973.0 x 561.2 x 63.5 mm (38.3" x 22.1" x 2.5") 1070.0 x 680.0 x 141.0 mm (42.1" x 26.8" x 5.6") 10.7 kg (23.6 lb) 13.1 kg (28.9 lb)
On Mode Standby Mode Off Mode Power Supply Operating Conditions Temperature Humidity Storage Conditions Temperature Humidity Mounting VESA FPMPMI Security Kensington Security Slot Dimensions Product w/o Base (W x H x D) Packaging (W x H x D) Weight Product w/o Base Packaging Regulation Approval Certifications & Compliance	123 (On) < 0.5W 0W Internal 0°C-40°C (32°F-104°F) 20%-80% (non-condensing) -20°C-60°C (-4°F-140°F) 10%-90% (non-condensing) Yes (200 x 200 mm) Yes 973.0 x 561.2 x 63.5 mm (38.3" x 22.1" x 2.5") 1070.0 x 680.0 x 141.0 mm (42.1" x 26.8" x 5.6") 10.7 kg (23.6 lb)
On Mode Standby Mode Off Mode Power Supply Operating Conditions Temperature Humidity Storage Conditions Temperature Humidity Mounting VESA FPMPMI Security Kensington Security Slot Dimensions Product w/o Base (W x H x D) Packaging (W x H x D) Weight Product w/o Base Packaging Regulation Approval Certifications & Compliance Accessories	123 (On) < 0.5W 0W Internal 0°C-40°C (32°F-104°F) 20%-80% (non-condensing) -20°C-60°C (-4°F-140°F) 10%-90% (non-condensing) Yes (200 x 200 mm) Yes 973.0 x 561.2 x 63.5 mm (38.3" x 22.1" x 2.5") 1070.0 x 680.0 x 141.0 mm (42.1" x 26.8" x 5.6") 10.7 kg (23.6 lb) 13.1 kg (28.9 lb) FCC, CE, LVD, ICES-003(Issue 7), WEEE, RoHS, REACH
On Mode Standby Mode Off Mode Power Supply Operating Conditions Temperature Humidity Storage Conditions Temperature Humidity Mounting VESA FPMPMI Security Kensington Security Slot Dimensions Product w/o Base (W x H x D) Packaging (W x H x D) Weight Product w/o Base Packaging Regulation Approval Certifications & Compliance Accessories Supplied	123 (On) < 0.5W 0W Internal 0°C-40°C (32°F-104°F) 20%-80% (non-condensing) -20°C-60°C (-4°F-140°F) 10%-90% (non-condensing) Yes (200 x 200 mm) Yes 973.0 x 561.2 x 63.5 mm (38.3" x 22.1" x 2.5") 1070.0 x 680.0 x 141.0 mm (42.1" x 26.8" x 5.6") 10.7 kg (23.6 lb) 13.1 kg (28.9 lb)
On Mode Standby Mode Off Mode Power Supply Operating Conditions Temperature Humidity Storage Conditions Temperature Humidity Mounting VESA FPMPMI Security Kensington Security Slot Dimensions Product w/o Base (W x H x D) Packaging (W x H x D) Weight Product w/o Base Product w/o	123 (On) < 0.5W 0W Internal 0°C-40°C (32°F-104°F) 20%-80% (non-condensing) -20°C-60°C (-4°F-140°F) 10%-90% (non-condensing) Yes (200 x 200 mm) Yes 973.0 x 561.2 x 63.5 mm (38.3" x 22.1" x 2.5") 1070.0 x 680.0 x 141.0 mm (42.1" x 26.8" x 5.6") 10.7 kg (23.6 lb) 13.1 kg (28.9 lb) FCC, CE, LVD, ICES-003(Issue 7), WEEE, RoHS, REACH
On Mode Standby Mode Off Mode Power Supply Operating Conditions Temperature Humidity Storage Conditions Temperature Humidity Mounting VESA FPMPMI Security Kensington Security Slot Dimensions Product w/o Base (W x H x D) Packaging (W x H x D) Weight Product w/o Base Product w/o	123 (On) < 0.5W 0W Internal 0°C-40°C (32°F-104°F) 20%-80% (non-condensing) -20°C-60°C (-4°F-140°F) 10%-90% (non-condensing) Yes (200 x 200 mm) Yes 973.0 x 561.2 x 63.5 mm (38.3" x 22.1" x 2.5") 1070.0 x 680.0 x 141.0 mm (42.1" x 26.8" x 5.6") 10.7 kg (23.6 lb) 13.1 kg (28.9 lb) FCC, CE, LVD, ICES-003(Issue 7), WEEE, RoHS, REACH Power Cord, HDMI Cable, Remote Control, Batteries, Quick Start Guide FMS-01, FMS-02, FMC-02
On Mode Standby Mode Off Mode Power Supply Operating Conditions Temperature Humidity Storage Conditions Temperature Humidity Mounting VESA FPMPMI Security Kensington Security Slot Dimensions Product w/o Base (W x H x D) Packaging (W x H x D) Weight Product w/o Base Packaging Regulation Approval Certifications & Compliance Accessories Supplied Optional Accessories Floor Mount Ceiling Mount	123 (On) < 0.5W 0W Internal 0°C-40°C (32°F-104°F) 20%-80% (non-condensing) -20°C-60°C (-4°F-140°F) 10%-90% (non-condensing) Yes (200 x 200 mm) Yes 973.0 x 561.2 x 63.5 mm (38.3" x 22.1" x 2.5") 1070.0 x 680.0 x 141.0 mm (42.1" x 26.8" x 5.6") 10.7 kg (23.6 lb) 13.1 kg (28.9 lb) FCC, CE, LVD, ICES-003(Issue 7), WEEE, RoHS, REACH Power Cord, HDMI Cable, Remote Control, Batteries, Quick Start Guide FMS-01, FMS-02, FMC-02 CMP-01+LMK-02, CMP-01+WMK-03
On Mode Standby Mode Off Mode Power Supply Operating Conditions Temperature Humidity Storage Conditions Temperature Humidity Mounting VESA FPMPMI Security Kensington Security Slot Dimensions Product w/o Base (W x H x D) Packaging (W x H x D) Weight Product w/o Base Product w/o	123 (On) < 0.5W 0W Internal 0°C-40°C (32°F-104°F) 20%-80% (non-condensing) -20°C-60°C (-4°F-140°F) 10%-90% (non-condensing) Yes (200 x 200 mm) Yes 973.0 x 561.2 x 63.5 mm (38.3" x 22.1" x 2.5") 1070.0 x 680.0 x 141.0 mm (42.1" x 26.8" x 5.6") 10.7 kg (23.6 lb) 13.1 kg (28.9 lb) FCC, CE, LVD, ICES-003(Issue 7), WEEE, RoHS, REACH Power Cord, HDMI Cable, Remote Control, Batteries, Quick Start Guide FMS-01, FMS-02, FMC-02













