

AMPLIFIED SPEAKER: TRUMPET

ARCHITECTS AND ENGINEERS
SPECIFICATIONS / TECHNICAL DATA



TRP470W



AMPBACKPLATEW
with Power Supply

GENERAL SPECIFICATIONS

MODEL NUMBER: AMP04TRPW	
DESCRIPTION:	4", full range, single input amplified trumpet speaker
POWER:	25 Watts
FREQUENCY RESPONSE:	20 Hz - 30 kHz +0-2 dB
NOISE FLOOR:	Better than 90 dB
DISTORTION:	Better than .1% at 10 Watts
INPUT:	Line Input -10 to +4 dB
INPUT CONFIGURATION:	Differential, Balanced DC Isolated
VOLUME CONTROL:	Step for Mechanical Level Memory
PROTECTION:	Short Circuit, Heat and Over Current
MAXIMUM POWER SUPPLY WIRE LENGTH:	400 Ft. with 16 Gauge Wire
MULTIPLE AMPLIFIERS:	Yes, Line Input In Parallel
EACH AMPLIFIER MAY POWER:	Four Speaker Total per Amp
INPUT/OUTPUT:	Each Amplifier has a Line Level Input and Output
CONNECTOR TYPE:	Phoenix Connector
CONDUIT ENTRY:	Two 1/2" Conduit Access Holes with Knock Outs
TYPICAL LINE LEVEL SOURCES:	CD Player, Audio Mixer, Background Music Service, Telephone PBX Dry Audio Pair Hooked to the Balanced +,- Input. There is No Shield on a Telephone Input.
HOOK UP FOR ADDITIONAL HORNS:	Wired through the Conduit Entry, Use the 4 Way Binding Posts for Additional High Level Speakers Hooked up to the Amplifier.
FOR FOUR HORNS:	Wire them Series Parallel to Achieve a 4 Ohm Load Impedance
POWER SUPPLY:	12 Volts
COLOR:	White



205 Westwood Ave, Long Branch, NJ 07740
Phone: 866-94 BOARDS (26273) / (732)-222-1511
Fax: (732)-222-7088 | E-mail: sales@touchboards.com