

AMP3IC6 - Amplified, Three Source, 6.5", Drop Ceiling Speakers

Three Source, 6.5", Amplified Drop Ceiling Speakers deliver up to 25 watts of class AB power directly to the speaker. Each powered speaker (AMP3IC6) can drive three additional speakers (IC6). One line can drive up to 50 self-amplified speakers. Lower noise feature and protection from shorts and overheating. 15 Volt DC power supply included.



Features:

- Built onto the OWI IC6 In-Ceiling Speakers
- 3 Line Level Input/Sources
- Up to 25 Watts of Class AB Power - right at the speaker
- Lower Noise Feature
- Fast and easy - install in the field
- 15 Volt DC power supply (UL rated) included
- Protected from shorts and overheating
- Available in 1, 2 and 4 speaker package
- Stereo/mono volume controls available

Available also in complete install packages:

- [AMP3S61](#) - Single speaker combination with tile bridge, backcan
- [AMP3S61SVC](#) - Single speaker combination with tile bridge, backcan and volume control
- [AMP3S62](#) - Two speaker combination with tile bridges, backcans
- [AMP3S62SVC](#) - Two speaker combination with tile bridges, backcans and volume control
- [AMP3S64](#) - Four speaker combination with tile bridges, backcans
- [AMP3S64SVC](#) - Four speaker combination with tile bridges, backcans and volume control