

**NEW**

# SELF-AMPLIFIED SURFACE MOUNT SPEAKER COMBO

Models AMP602-2W & AMP602-2B



Model AMP602-2B



Amplified Speaker  
AMP602B



Backside



With a Non-Amplified Speaker  
P602B

CE

**Touchboards**

205 Westwood Ave, Long Branch, NJ 07740  
Phone: 866-94 BOARDS (26273) / (732)-222-1511  
Fax: (732)-222-7088 | E-mail: sales@touchboards.com

## FEATURES

**Versatile Self-Amplified Surface Mount Speaker Featuring an Aluminum Grill, Rugged Plastic Housing and Mounting Bracket. Perfect for Schools, Hotels, Conference Rooms and Training Rooms.**

- Professional, Commercial Speakers
- Two Speakers – 6.5" Active and Passive (1 Amplified and 1 Non-Amplified)
- Wall Mount Bracket Included
- 6.5" Woofer
- 0.79" (20 mm) Tweeter
- Weight: 12 Lbs. (Amplified)  
10 Lbs. (Non-Amplified)
- CE Approved
- White or Black
- 1 Year Warranty

## GENERAL SPECS - AMP602

<b>MODEL NUMBER:</b>	<b>AMP602 – AMPLIFIED SPEAKER</b>
Description:	6.5" Active
Outdoor:	No
Impedance:	4 Ω
Dispersion:	92°
Sensitivity (1W / 1M):	83 dB (VR at Max.)
Power:	15 W x 2
Frequency Response:	80 Hz - 20 kHz
Crossover:	3.5 kHz
S / N:	>80 dB
Input Configuration:	RCA L / R
Input Load Impedance:	20 K Ω
Maximum Current Protected:	Yes
One Wire To Ground Protected:	Yes
Short Circuit Protected:	Yes
THD:	<0.2%
Power Supply:	115 V
High Frequency Driver:	1.5 kHz - 20 kHz
Low Frequency Driver:	80 Hz - 6 kHz
Woofer Size:	6.5"
Woofer Material:	Mica
Tweeter Size:	.79" (20 mm)
Tweeter Material:	PEI
Enclosure:	High Impact Polystyrene (HIPS)
Dimensions (LxWxH):	9.5 x 8.46 x 11.3" (242 x 215 x 288 mm)
Weight (Pounds/Kgs):	12 lbs. (5.5 Kgs)
CE Approved:	Yes
Colors:	White or Black
Paintable:	Yes
Warranty:	1 Year

**NEW**

# SELF-AMPLIFIED SURFACE MOUNT SPEAKER COMBO

Models AMP602-2W & AMP602-2B



## GENERAL SPECS

Amplified Speaker and Backside

Non-Amplified Speaker

White or Black

### AMPLIFIED SPEAKER

<b>MODEL NUMBER:</b>	<b>AMP602</b>
Description:	6.5" Active
Outdoor:	No
Impedance:	4 Ω
Dispersion:	92°
Sensitivity (1W / 1M):	83 dB (VR at Max.)
Power:	15 W x 2
Frequency Response:	80 Hz - 20 kHz
Crossover:	3.5 kHz
S / N:	>80 dB
Input Configuration:	RCA L / R
Input Load Impedance:	20 K Ω
Maximum Current Protected:	Yes
One Wire To Ground Protected:	Yes
Short Circuit Protected:	Yes
THD:	<0.2%
Power Supply:	115 V
High Frequency Driver:	1.5 kHz - 20 kHz
Low Frequency Driver:	80 Hz - 6 kHz
Woofer Size:	6.5"
Woofer Material:	Mica
Tweeter Size:	.79" (20 mm)
Tweeter Material:	PEI
Enclosure:	High Impact Polystyrene (HIPS)
Dimensions (LxWxH):	9.5 x 8.46 x 11.3" (242 x 215 x 288 mm)
Weight (Pounds/Kgs):	12 lbs. (5.5 Kgs)
CE Approved:	Yes
Colors:	White or Black
Paintable:	Yes
Warranty:	1 Year

### PASSIVE SPEAKER

<b>MODEL NUMBER:</b>	<b>P602</b>
Description:	6.5" Passive Cabinet Speaker
Outdoor:	No
Impedance:	4 Ω
Dispersion:	92°
Sensitivity (1W / 1M):	86 dB
Maximum Power:	30 W
Nominal Power:	15 W
Frequency Response:	80 Hz - 20 kHz
Crossover:	3.5 kHz
High Frequency Driver:	1.5 kHz - 6 kHz
Low Frequency Driver:	80 Hz - 6 kHz
Woofer Size:	6.5"
Woofer Material:	Mica / Foam Surround
Tweeter Size:	.79" (20 mm)
Tweeter Material:	PEI
Enclosure:	Plastic Enclosure
Dimensions (LxWxH):	9.5 x 8.46 x 11.3" (242 x 215 x 288 mm)
CE Approved:	Yes
Weight (Pounds/Kgs):	10 lbs. (4.5 Kgs)
Colors:	White or Black
Paintable:	Yes
Warranty:	1 Year



## FREQUENCY RESPONSE CHARTS

