

AMPIC6 - Amplified, Single Source, 6.5", Drop Ceiling Speakers (UL Listed)

Single Source, 6.5", UL Listed, Amplified Drop Ceiling Speakers deliver up to 25 watts of class AB power directly to the speaker. Each powered speaker can drive up to three additional speakers. One line can drive up to 20 self-amplified speakers. Lower noise feature and protection from shorts and overheating. 12 Volt AC power supply included. Available also in 5-inch amplified speaker and in complete install packages.



Features:

- Built onto the OWI IC6 In-Ceiling Speakers
- Up to 25 Watts of Class AB Power - Right at the speaker
- Lower Noise Feature
- Fast and easy - install in the field
- 12 Volt AC power supply included
- Protected from shorts and overheating
- Available in 1, 2 and 4 speaker package
- Stereo/mono volume controls available

Available also in complete install packages:

- [AMP1S61](#) - Single speaker combination with tile bridge, backcan
- [AMP1S61SVC](#) - Single speaker combination with tile bridge, backcan and volume control
- [AMP1S62](#) - Two speaker combination with tile bridges, backcans
- [AMP1S62SVC](#) - Two speaker combination with tile bridges, backcans and volume control
- [AMP1S64](#) - Four speaker combination with tile bridges, backcans
- [AMP1S64SVC](#) - Four speaker combination with tile bridges, backcans and volume control



Touchboards

205 Westwood Ave, Long Branch, NJ 07740
Phone: 866-94 BOARDS (26273) / (732)-222-1511
Fax: (732)-222-7088 | E-mail: sales@touchboards.com