

AMPLIFIED SURFACE SPEAKER

Low Voltage Speaker

AMPLV602B / AMPLV602W

ARCHITECTS AND ENGINEERS
SPECIFICATIONS / TECHNICAL DATA



GENERAL SPECIFICATIONS

MODEL NUMBER: AMPLV602B / AMPLV602W	
DESCRIPTION:	6.5", 2-Way, Amplified Surface Mount Speaker
OUTDOOR:	No
IMPEDANCE:	4Ω
DISPERSION:	92°
SENSITIVITY (1W/1M):	83 dB (VR at Max)
POWER:	15 W x 2
FREQUENCY RESPONSE:	80 Hz - 20 kHz
S/N:	>80dB
INPUT CONFIGURATION:	RCA L/R
INPUT LOAD IMPEDANCE:	20 KΩ
MAXIMUM CURRENT PROTECTED:	Yes
ONE WIRE TO GROUND PROTECTED:	Yes
SHORT CIRCUIT PROTECTED:	Yes
THD:	<0.2%
POWER SUPPLY:	15V DC, UL Listed, Level 5 (Energy Star)
HIGH FREQUENCY DRIVER:	1.5 kHz - 20 kHz
LOW FREQUENCY DRIVER:	80 Hz - 6 kHz
WOOFER SIZE:	6.5"
WOOFER MATERIAL:	Mica
TWEETER SIZE:	079"(20 mm)
TWEETER MATERIAL:	PEI
ENCLOSURE:	High Impact Polystyrene (HIPS)
WEIGHT:	12 lbs. (5.5 Kgs)
COLOR/S:	White or Black
PAINTABLE:	Yes
WARRANTY:	1 Year
GIFT BOX DIMENSIONS (LxWxH):	19" x 11" x 13"
GIFT BOX WEIGHT:	24 lbs.
MASTER CARTON DIMENSIONS (LxWxH):	23" x 21" x 15"
MASTER CARTON QUANTITY:	4



OWI Incorporated
17141 Kingsview Avenue, Carson, CA 90746 USA
Tel: 310.515.1900
Toll Free: 800.638.1694
Fax: 310.515.1606
Web: www.owi-inc.com
E-mail: info@owi-inc.com



205 Westwood Ave, Long Branch, NJ 07740
Phone: 866-94 BOARDS (26273) / (732)-222-1511
Fax: (732)-222-7088 | E-mail: sales@touchboards.com