

**NEW**

# SELF-AMPLIFIED, SURFACE MOUNT, LOW VOLTAGE SPEAKER COMBO

Model: AMPLV602

Versatile, Low Voltage, Self-Amplified, Surface Mount Speaker, Featuring an Aluminum Grill, High-Impact Polystyrene Housing and Mounting Bracket.

Perfect for Schools, Hotels, Conference Rooms and Training Rooms.



AMPLV602W



UL Listed,  
Efficiency Level  $\nabla$   
(Energy Star)  
15V DC Power Supply



Amplified Speaker  
AMPLV602B



Backside



UL Listed,  
Efficiency Level  $\nabla$   
(Energy Star)  
15V DC Power Supply



With a Non-Amplified Speaker  
P602B

- Professional, Commercial Speaker
- Two Speakers – 6.5" Active and Passive (1 Amplified and 1 Non-Amplified)
- Combined Power: 26 W
- Impedance: 4  $\Omega$
- Dispersion: 92°
- Outdoor: No
- 6.5" Woofer
- 0.79" (20 mm) Tweeter
- 15V DC, UL Listed, Efficiency Level  $\nabla$  (Energy Star) Power Supply (Dimensions: 4.7"H x 2.0"W x 1.2"D)
- Dimensions: 9.5"H x 8.46"W x 11.3"D (242 x 215 x 288 mm)
- Weight: 12 Lbs. (Amplified)  
10 Lbs. (Non-Amplified)
- CE Approved
- Wall Mount Bracket Included
- Black or White (Paintable)
- Sold as Each or in Pairs
- 1 Year Warranty

**Envirōtainment™**

**OWI®**  
OWI Incorporated  
Established 1978  
[www.owi-inc.com](http://www.owi-inc.com)

**NEW**

# SELF-AMPLIFIED SURFACE MOUNT, LOW VOLTAGE SPEAKER COMBO

Model: AMPLV602



**GENERAL SPECS**

Amplified Speaker and Backside

Non-Amplified Speaker

White or Black

**AMPLIFIED SPEAKER**

<b>MODEL NUMBER:</b>	<b>AMPLV602</b>
Description:	6.5", 2-Way, Active, Full Range
Outdoor:	No
Impedance:	4 Ω
Dispersion:	92°
Sensitivity (1W / 1M):	83 dB (VR at Max)
Power:	15 W x 2
Maximum Power:	30 W
Nominal Power:	15 W
Frequency Response:	80 Hz - 20 kHz
S/N:	>80 dB
Input Configuration:	RCA L/R
Input Load Impedance:	20 KΩ
Maximum Current Protected:	Yes
One Wire to Ground Protected:	Yes
Short Circuit Protected:	Yes
THD:	<0.2%
High Frequency Driver:	1.5 kHz - 20 kHz
Low Frequency Driver:	80 Hz - 6 kHz
Woofer Size:	6.5"
Woofer Material:	Mica
Tweeter Size:	.79" (20 mm)
Tweeter Material:	PEI
Enclosure:	High Impact Polystyrene (HIPS)
Grill Material:	FE
Dimensions (LxWxH):	9.5 x 8.46 x 11.3" (242 x 215 x 288 mm)
Weight (Pounds/Kgs):	12 lbs. (5.5 Kgs)
Colors:	White or Black
Paintable:	Yes
Power Supply:	15V DC, UL Listed, Efficiency Level <b>V</b> (Energy Star) (Dimensions: 4.7"H x 2.0"W x 1.2"D)
Warranty:	1 Year

**PASSIVE SPEAKER**

<b>MODEL NUMBER:</b>	<b>P602</b>
Description:	6.5" Passive Cabinet Speaker
Outdoor:	No
Impedance:	4 Ω
Dispersion:	92°
Sensitivity (1W / 1M):	86 dB
Maximum Power:	30 W
Nominal Power:	15 W
Frequency Response:	80 Hz - 20 kHz
Crossover:	3.5 kHz
High Frequency Driver:	1.5 kHz - 6 kHz
Low Frequency Driver:	80 Hz - 6 kHz
Woofer Size:	6.5"
Woofer Material:	Mica/Foam Surround
Tweeter Size:	.79" (20 mm)
Tweeter Material:	PEI
Enclosure:	Plastic Enclosure
Dimensions (LxWxH):	9.5 x 8.46 x 11.3" (242 x 215 x 288 mm)
CE Approved:	Yes
Weight (Pounds/Kgs):	10 lbs. (4.5 Kgs)
Colors:	White or Black
Paintable:	Yes
Warranty:	1 Year

Engineered in the USA • Made in China



**205 Westwood Ave, Long Branch, NJ 07740**  
**Phone: 866-94 BOARDS (26273) / (732)-222-1511**  
**Fax: (732)-222-7088 | E-mail: sales@touchboards.com**



**OWI, Inc.**  
 17141 Kingsview Ave.  
 Carson, CA 90746 USA

ph. 310.515.1900  
 toll free 800.638.1694  
 fax 310.515.1606

email info@owi-inc.com  
 web www.owi-inc.com