



ASG, Division of Jergens, Inc.

Jergens Way, 15700 South Waterloo Road
Cleveland, Ohio 44110-3898 USA

Phone: 216-486-6163 • **Toll-Free USA:** 888-486-6163

Fax: 216-481-4519

Email: asginfo@asg-jergens.com • **Website:** www.asg-jergens.com

FIAM Non Auto Shutoff Pneumatic Screwdrivers & Nutrunners

Gold standard quality cushion clutch technology






Hex and square drives

Push to start, lever start, trigger start, push/lever start combination and push/trigger start combination models

Torque range across all cushion clutch models: 7.08 to 194.7 lbf.in (0.8 to 22 N.m)

⚠ WARNING Cancer or Reproductive Harm - www.P65Warnings.ca.gov



Items	 <p><u>CSE5PRE</u> FIAM CSE5PRE Pistol Grip Cushion Clutch Pneumatic Screwdriver</p> <p>+ Request Quote</p>	 <p><u>CSE6PRE</u> FIAM CSE6PRE Pistol Grip Cushion Clutch Pneumatic Screwdriver</p> <p>+ Request Quote</p>	 <p><u>CSE8PRE</u> FIAM CSE8PRE Pistol Grip Cushion Clutch Pneumatic Screwdriver</p> <p>+ Request Quote</p>	 <p><u>CSE10PRE</u> FIAM CSE10PRE Pistol Grip Cushion Clutch Pneumatic Screwdriver</p> <p>+ Request Quote</p>
Torque	1 to 5 N·m 8.85 to 44.25 lbf·in	1.5 to 6 N·m 13.28 to 53.1 lbf·in	1.5 to 8 N·m 13.28 to 70.8 lbf·in	

Free Speed	2300 rpm	1400 rpm	900 rpm	450 rpm
Drive Size	1/4 in. HEX			
Length	8.5 in 216 mm	9.06 in 230 mm	9.06 in 230 mm	9.06 in 230 mm
Weight	35.27 oz 2.2 lb 1 kg			
Air Inlet	1/4" NPT			
Min. Hose I.D.	5/16 in 8 mm			
Air Consumption	19 cfm 9 l/sec			
Noise Level \pm2dBA	74			
Reversibility	Reversible			
Starting System	Pistol Grip Cushion Clutch			