



**ASG, Division of Jergens, Inc.**

Jergens Way, 15700 South Waterloo Road  
Cleveland, Ohio 44110-3898 USA

**Phone:** 216-486-6163 • **Toll-Free USA:** 888-486-6163

**Fax:** 216-481-4519

**Email:** [asginfo@asg-jergens.com](mailto:asginfo@asg-jergens.com) • **Website:** [www.asg-jergens.com](http://www.asg-jergens.com)

## FIAM Non Auto Shutoff Pneumatic Screwdrivers & Nutrunners

Gold standard quality cushion clutch technology

Hex and square drives

Push to start, lever start, trigger start, push/lever start combination and push/trigger start combination models

Torque range across all cushion clutch models: 7.08 to 194.7 lbf.in (0.8 to 22 N.m)

**⚠ WARNING** Cancer or Reproductive Harm - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)



Items



### CY7PR1

FIAM CY7PR1 Pistol Grip  
Cushion Clutch  
Pneumatic Screwdriver



[Request Quote](#)



### CY9PR1

FIAM CY9PR1 Pistol Grip  
Cushion Clutch  
Pneumatic Screwdriver



[Request Quote](#)



### CY11PR1

FIAM CY11PR1 Pistol  
Grip Cushion Clutch



[Contact us](#)

<b>Torque</b>	4.5 to 13 N·m 39.83 to 115.05 lbf·in	6 to 16 N·m 53.1 to 141.6 lbf·in	6 to 22 N·m 53.1 to 194.7 lbf·in
<b>Free Speed</b>	1600 rpm	700 rpm	450 rpm
<b>Drive Size</b>	1/4 in. HEX		
<b>Length</b>	8.19 in 208 mm	9.37 in 238 mm	9.37 in 238 mm
<b>Weight</b>	48.33 oz 3.01 lb 1.37 kg	55.38 oz 3.01 lb 1.57 kg	55.38 oz 3.45 lb 1.57 kg
<b>Air Inlet</b>	1/4" NPT		
<b>Min. Hose I.D.</b>	5/16 in 8 mm		
<b>Air Consumption</b>	21 cfm 10 l/sec		
<b>Noise Level ±2dBA</b>	80		
<b>Reversibility</b>	Reversible		
<b>Starting System</b>	Pistol Grip Push/Trigger Start Combination		



**ASG, Division of Jergens, Inc.**

Jergens Way, 15700 South Waterloo Road  
Cleveland, Ohio 44110-3898 USA

**Phone:** 216-486-6163 • **Toll-Free USA:** 888-486-6163

**Fax:** 216-481-4519

**Email:** [asginfo@asg-jergens.com](mailto:asginfo@asg-jergens.com) • **Website:** [www.asg-jergens.com](http://www.asg-jergens.com)

## FIAM Non Auto Shutoff Pneumatic Screwdrivers & Nutrunners

Gold standard quality cushion clutch technology

Hex and square drives

Push to start, lever start, trigger start, push/lever start combination and push/trigger start combination models

Torque range across all cushion clutch models: 7.08 to 194.7 lbf.in (0.8 to 22 N.m)

**⚠ WARNING** Cancer or Reproductive Harm - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)



Items



### CY7PR1-WP

FIAM CY7PR1-WP Pistol  
Grip Cushion Clutch  
Pneumatic Screwdriver



[Request Quote](#)



### CY9PR1-WP

FIAM CY9PR1-WP Pistol  
Grip Cushion Clutch  
Pneumatic Screwdriver



[Request Quote](#)



### CY11PR1-WP

FIAM CY11PR1-WP Pistol  
Grip Cushion Clutch



[Contact us](#)

<b>Torque</b>	4.5 to 13 N·m 39.83 to 115.05 lbf·in	6 to 16 N·m 53.1 to 141.6 lbf·in	6 to 22 N·m 53.1 to 194.7 lbf·in
<b>Free Speed</b>	1600 rpm	700 rpm	450 rpm
<b>Drive Size</b>	1/4 in. HEX		
<b>Length</b>	8.19 in 208 mm	9.37 in 238 mm	9.37 in 238 mm
<b>Weight</b>	48.33 oz 3.01 lb 1.37 kg	55.38 oz 3.45 lb 1.57 kg	55.38 oz 3.45 lb 1.57 kg
<b>Air Inlet</b>	1/4" NPT		
<b>Min. Hose I.D.</b>	5/16 in 8 mm		
<b>Air Consumption</b>	21 cfm 10 l/sec		
<b>Noise Level ±2dBA</b>	80		
<b>Reversibility</b>	Reversible		
<b>Starting System</b>	Pistol Grip Cushion Clutch		