

Section 3: Torque Arm and Tool Support Stands

Articulating Torque Arms



ASG #65058

- Easily mounts or clamps to bench-top (clamp optional)
- Maintains tool location while allowing easy movement
- Durable, lightweight
- Adjustable height
- Specialized tool mount couplings available, please see page 19 for additional information
- Helps reduce potential operator injury to arm, wrist or hand
- Optional heavy duty spring set available

ASG Number	Operation	Max. Torque Reaction		Max. Tool Weight		Forearm Backarm	Max. Reach	
		lbf.in	N.m	lb.	kg		in.	mm
65050*	Spring Assisted	100	11.3	5*	2.3*	12 x 12	27.5	698
65046*	Spring Assisted	100	11.3	5*	2.3*	12 x 6	21.75	552
65054*	Spring Assisted	100	11.3	5*	2.3*	12 x 18	33.75	857
65056	Spring Assisted	100	11.3	5*	2.3*	18 x 18	39.75	1010
65060	Pneumatically Assisted	150	16.9	10	4.5	12 x 6	21.75	552
65058	Pneumatically Assisted	150	16.9	10	4.5	12 x 12	27.75	698
65062	Pneumatically Assisted	150	16.9	10	4.5	12 x 18	33.75	857

* Optional heavy duty springs available for up to 10lb (4.5 kg) tool weight, ASG #65048

Linear Torque Arms



ASG #65010

- Easily mounts or clamps to bench-top (clamp optional)
- Maintains tool location while allowing easy movement
- Durable, lightweight
- Adjustable height
- Specialized tool mount couplings available, please see page 19 for additional information
- Reduces potential operator injury to arm, wrist or hand

Model Number	ASG Number	Max. Torque Reaction			Max. Tool Weight		Max. Reach	
		lbf.in	N.m	kgf.cm	lb.	kg	in.	mm
N/A	65010	150	17	170	5	2.25	26.75	679
N/A	65013	150	17	170	1.5	0.7	19.5	495
LTA20	66203	177	20	204	6.6	3.0	26.22	666
LTA40	66204	354	40	408	6.6	3.0	26.22	666
LTA100	66205	885	100	1020	6.6	3.0	26.22	666