

Section 3: Auto Shut-Off Clutch Pneumatic Nutrunners



HAW35

- Value engineered auto shut-off technology
- Light weight, ergonomic composite housings
- Reversible, delivers full torque in reverse

Right Angle Lever Start

Model Number	ASG Number	Torque Range		Free Speed RPM	Drive Size	Operating Pressure		Inlet Size	Min Hose ID	Air Consumption		±2 DBA
		lbf.in	N.m			PSI	Bar			CFM	L/Sec.	
HAW35	68283	2.7 - 14.2	0.3 - 1.6	2200	1/4" Sq.	90	6.2	1/4" NPT	3/16"	9.9	4.7	74
HAW48	68286	4.4 - 31.0	0.5 - 3.5	1700	3/8" Sq.	90	6.2	1/4" NPT	5/16"	19.4	9.17	78
HAW60	68289	13.3 - 66.4	1.5 - 7.5	550	3/8" Sq.	90	6.2	1/4" NPT	5/16"	19.4	9.17	78
HAW65	68290	25.7 - 124.8	2.9 - 14.1	300	3/8" Sq.	90	6.2	1/4" NPT	5/16"	19.4	9.17	78
HA35	68263	2.7 - 14.2	0.3 - 1.6	2200	1/4" Hex	90	6.2	1/4" NPT	3/16"	9.9	4.7	74
HA48	68266	4.4 - 31.0	0.5 - 3.5	1700	1/4" Hex	90	6.2	1/4" NPT	5/16"	19.4	9.17	78
HA60	68269	13.3 - 66.4	1.5 - 7.5	550	1/4" Hex	90	6.2	1/4" NPT	5/16"	19.4	9.17	78
HA65	68270	25.7 - 124.8	2.9 - 14.1	300	1/4" Hex	90	6.2	1/4" NPT	5/16"	19.4	9.17	78

Right Angle Lever Start: High Torque

Model Number	ASG Number	Torque Range		Free Speed RPM	Drive Size	Operating Pressure		Inlet Size	Min Hose ID	Air Consumption		DBA
		lbf.ft	N.m			PSI	Bar			CFM	L/Sec.	
HAW150	68466	3.6 - 10.5	4.9 - 14.2	770	3/8" Sq.	90	6.2	1/4" NPT	5/16"	19.4	9.17	78
HAW200	68467	2.1 - 14.5	2.9 - 19.6	430	3/8" Sq.	90	6.2	1/4" NPT	5/16"	19.4	9.17	78
HAW300	68468	3.6 - 28.9	4.9 - 39.2	300	3/8" Sq.	90	6.2	1/4" NPT	5/16"	19.4	9.17	78
HAW480	68469	25.3 - 34.8	34.3 - 47.1	180	1/2" Sq.	90	6.2	1/4" NPT	5/16"	19.4	9.17	78