

Section 1: Auto Shut-Off Clutch Pneumatic Screwdrivers



HP65

- Value engineered auto shut-off technology
- Light weight, ergonomic composite housings
- Reversible, delivers full torque in reverse
- Unique top and bottom inlet ports on pistol grip push-to-start (trigger permit) models
- Anti-tamper proof torque adjustment covers

In-Line Push-to-Start

Model Number	ASG Number	Torque Range		Free Speed RPM	Drive Size	Operating Pressure		Inlet Size	Min Hose ID	Air Consumption		±2 DBA
		lbf.in	N.m			PSI	Bar			CFM	L/Sec.	
HP20	68201	0.9 - 5.6	0.1 - 0.63	1000	1/4" Hex	90	6.2	1/4" NPT	3/16"	7	3.3	70
HP35	68203	2.7 - 14.2	0.3 - 1.6	2200	1/4" Hex	90	6.2	1/4" NPT	3/16"	9.9	4.7	74
HP40	68204	4.4 - 21.2	0.5 - 2.4	1000	1/4" Hex	90	6.2	1/4" NPT	3/16"	9.9	4.7	74
HP55	68208	6.2 - 45.1	0.7 - 5.1	1000	1/4" Hex	90	6.2	1/4" NPT	5/16"	19.4	9.17	78
HP65	68210	25.7 - 124.8	2.9 - 14.1	300	1/4" Hex	90	6.2	1/4" NPT	5/16"	19.4	9.17	78

In-Line Lever Start

Model Number	ASG Number	Torque Range		Free Speed RPM	Drive Size	Operating Pressure		Inlet Size	Min Hose ID	Air Consumption		±2 DBA
		lbf.in	N.m			PSI	Bar			CFM	L/Sec.	
HL20	68241	0.9 - 5.6	0.1 - 0.63	1000	1/4" Hex	90	6.2	1/4" NPT	3/16"	7	3.3	70
HL35	68243	2.7 - 14.2	0.3 - 1.6	2200	1/4" Hex	90	6.2	1/4" NPT	3/16"	9.9	4.7	74
HL40	68244	4.4 - 21.2	0.5 - 2.4	1000	1/4" Hex	90	6.2	1/4" NPT	3/16"	9.9	4.7	74
HL55	68248	6.2 - 45.1	0.7 - 5.1	1000	1/4" Hex	90	6.2	1/4" NPT	5/16"	19.4	9.17	78
HL65	68250	25.7 - 124.8	2.9 - 14.1	300	1/4" Hex	90	6.2	1/4" NPT	5/16"	19.4	9.17	78

Auto Shut-Off Clutch Pneumatic Screwdrivers

Pistol Grip Trigger Start

Model Number	ASG Number	Torque Range		Free Speed	Drive Size	Operating Pressure		Inlet Size	Min Hose ID	Air Consumption		±2 DBA
		lbf.in	N.m	RPM		PSI	Bar			CFM	L/Sec.	
HBP38	68301	2.7 - 17.4	0.3 - 1.96	1800	1/4" Hex	90	6.2	1/4" NPT	3/16"	9.9	4.7	74
HBP47	68303	8.9 - 34.5	1.0 - 3.9	550	1/4" Hex	90	6.2	1/4" NPT	3/16"	9.9	4.7	74
HBP55	68306	10.6 - 52.2	1.2 - 5.9	1000	1/4" Hex	90	6.2	1/4" NPT	5/16"	19.4	9.17	78
HBP65	68308	25.7 - 124.8	2.9 - 14.1	300	1/4" Hex	90	6.2	1/4" NPT	5/16"	19.4	9.17	78

Pistol Grip Push-to-Start (Trigger Permit) With Top and Bottom Inlet Ports

Model Number	ASG Number	Torque Range		Free Speed	Drive Size	Operating Pressure		Inlet Size	Min Hose ID	Air Consumption		±2 DBA
		lbf.in	N.m	RPM		PSI	Bar			CFM	L/Sec.	
HPP38	68321	2.7 - 17.4	0.3 - 1.96	1800	1/4" Hex	90	6.2	1/4" NPT	3/16"	9.9	4.7	74
HPP41	68322	4.4 - 24.3	0.5 - 2.74	1000	1/4" Hex	90	6.2	1/4" NPT	3/16"	9.9	4.7	74



HP20



HL35



HBP47



HPP38