

Assembly · Industrial · Precision Fastening · Automation

ASG, Division of Jergens, Inc.

Jergens Way, 15700 South Waterloo Road

Cleveland, Ohio 44110-3898 USA

Phone: 216-486-6163 • Toll-Free USA: 888-486-6163

Fax: 216-481-4519

Email: asginfo@asg-jergens.com • Website: www.asg-jergens.com

Item # 64135, Model CLF-6500XH Brushed Electric Screwdriver for Automation

Most suitable for automation assembly machines because it can be installed into the XY robot

Stable torque accuracy helps uniform screw tightening for automation

Easy to install to the existing system

Safe and risk free low voltage DC30V

All models have stepless torque adjustment

RoHS compliant

▲ **WARNING**Cancer or Reproductive Harm - www.P65Warnings.ca.gov



Specifications | Classification

SPECIFICATIONS -				
	Model No.	CLF-6500XH		
	Drive Size	1/4 in. HEX		
	Driver Type	Inline		
	Operation	Remote		





Torque	3.5 to 9 lbf·in 4 to 10 kgf·cm .4 to 1 N·m
Approximate RPM	850 @ 30VDC 440 @ 20VDC
Length	9.21 in
Dia.	1.46 in
Weight	23.63 oz
Screw Size (mm)	2.0 to 3.0 Machine Screw 2.0 to 3.0 Tapping Screw

CLASSIFICATION -				
	Product Group	Automation & Engineered Products		
	Brand	HIOS		
	Manual or Powered	Powered		
	Electric or Pneumatic	Electric		
	Low Voltage DC w /Power Source or Direct Plug-in	DC		
	Standard or Brushless	Standard		
	ESD Safe	No		