









**ASG, Division of Jergens, Inc.**  
 Jergens Way, 15700 South Waterloo Road  
 Cleveland, Ohio 44110-3898 USA  
**Phone:** 216-486-6163 • **Toll-Free USA:** 888-486-6163  
**Fax:** 216-481-4519  
**Email:** [• Website:](#) \_\_\_\_\_

## FIAM Non Auto Shutoff Pneumatic Screwdrivers & Nutrunners

Gold standard quality cushion clutch technology  
 Hex and square drives  
 Push to start, lever start, trigger start, push/lever start combination and push/trigger start combination models  
 Torque range across all cushion clutch models: 7.08 to 194.7 lbf.in (0.8 to 22 N.m)

**⚠ WARNING** Cancer or Reproductive Harm - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)



Items	 <b><u>CSE5LRE</u></b> FIAM CSE5LRE Lever Start Cushion Clutch Pneumatic Screwdriver with External Clutch Adjust  <a href="#">Request Quote</a>	 <b><u>CSE6LRE</u></b> FIAM CSE6LRE Lever Start Cushion Clutch Pneumatic Screwdriver with External Clutch Adjust  <a href="#">Request Quote</a>	 <b><u>CSE8LRE</u></b> FIAM CSE8LRE Lever Start Cushion Clutch Pneumatic Screwdriver with External Clutch Adjust  <a href="#">Request Quote</a>	 <b><u>CSE10LRE</u></b> FIAM CSE10LRE Lever Start Cushion Clutch Pneumatic Screwdriver with External Clutch Adjust  <a href="#">Request Quote</a>
-------	---	---	--	---

 **Contact us**

<b>Torque</b>	1 to 5 N·m 8.85 to 44.25 lbf·in	1.5 to 6 N·m 13.28 to 53.1 lbf·in	1.5 to 8 N·m 13.28 to 70.8 lbf·in	1.5 to 10 N·m 13.28 to 88.5 lbf·in
<b>Free Speed</b>	2500 rpm	1500 rpm	1000 rpm	500 rpm
<b>Drive Size</b>	1/4 in. HEX			
<b>Length</b>	9.06 in 230 mm			
<b>Weight</b>	33.16 oz 2.07 lb 0.94 kg			
<b>Air Inlet</b>	1/4" NPT			
<b>Min. Hose I.D.</b>	5/16 in 8 mm			
<b>Air Consumption</b>	19 cfm 9 l/sec			
<b>Noise Level ±2dBA</b>	76			
<b>Reversibility</b>	Reversible			
<b>Starting System</b>	Inline Lever Start			