



ASG, Division of Jergens, Inc.

Jergens Way, 15700 South Waterloo Road
Cleveland, Ohio 44110-3898 USA

Phone: 216-486-6163 • **Toll-Free USA:** 888-486-6163

Fax: 216-481-4519

Email: [Website:](#) _____

FIAM Non Auto Shutoff Pneumatic Screwdrivers & Nutrunners

Gold standard quality cushion clutch technology

Hex and square drives

Push to start, lever start, trigger start, push/lever start combination and push/trigger start combination models

Torque range across all cushion clutch models: 7.08 to 194.7 lbf.in (0.8 to 22 N.m)

⚠ WARNING Cancer or Reproductive Harm - www.P65Warnings.ca.gov



1 2

Item #	Torque	Free Speed	Drive Size	Length	Weight	Air Inlet	Min. Hose I.D.	Air Consumption	Noise Level ±2dBA	F
CSE5LRE	1 to 5 N·m 8.85 to 44.25 lbf·in	2500 rpm	1/4 in. HEX	9.06 in 230 mm	33.16 oz 2.07 lb 0.94 kg	1/4" NPT	5/16 in 8 mm	19 cfm 9 l/sec	76	F

Item #	Torque	Free Speed	Drive Size	Length	Weight	Air Inlet	Min. Hose I.D.	Air Consumption	Noise Level ±2dBA	
CZ2PR1	2.5 N·m 7.08 to 22.13 lbf·in	2700 rpm	1/4 in. HEX	7.48 in 190 mm	23.28 oz 1.45 lb 0.66 kg	1/4" NPT	3/16 in 5 mm	11 cfm 5 l/sec	73	F
CZ3PR1	0.8 to 3.5 N·m 7.08 to 30.98 lbf·in	1350 rpm	1/4 in. HEX	7.95 in 202 mm	24.69 oz 1.54 lb 0.7 kg	1/4" NPT	3/16 in 5 mm	11 cfm 5 l/sec	73	F
CZ4PR1	0.8 to 3.8 N·m 7.08 to 33.63 lbf·in	900 rpm	1/4 in. HEX	7.95 in 202 mm	24.69 oz 1.54 lb 0.7 kg	1/4" NPT	3/16 in 5 mm	11 cfm 5 l/sec	73	F
CZ5PR1	.6 to 4.2 N·m 5.31 to 27.17 lbf·in	600 rpm	1/4 in. HEX	7.95 in 202 mm	24.69 oz 1.54 lb 0.7 kg	1/4" NPT	3/16 in 5 mm	11 cfm 5 l/sec	73	F
CZ2PR1-WP	.8 to 2.5 N·m 7.08 to 22.13 lbf·in	2700 rpm	1/4 in. HEX	7.48 in 190 mm	23.28 oz 1.45 lb 0.66 kg	1/4" NPT	3/16 in 5 mm	11 cfm 5 l/sec	73	F
CZ3PR1-WP	0.8 to 3.5 N·m 7.08 to 30.98 lbf·in	1350 rpm	1/4 in. HEX	7.95 in 202 mm	24.69 oz 1.54 lb 0.7 kg	1/4" NPT	3/16 in 5 mm	11 cfm 5 l/sec	73	F
CZ4PR1-WP	0.8 to 3.8 N·m 7.08 to 33.63 lbf·in	900 rpm	1/4 in. HEX	7.95 in 202 mm	24.69 oz 1.54 lb 0.7 kg	1/4" NPT	3/16 in 5 mm	11 cfm 5 l/sec	73	F

Item #	Torque	Free Speed	Drive Size	Length	Weight	Air Inlet	Min. Hose I.D.	Air Consumption	Noise Level ±2dBA	F
CZ5PR1-WP	.6 to 4.2 N·m 5.31 to 27.17 lbf·in	600 rpm	1/4 in. HEX	7.95 in 202 mm	24.69 oz 1.54 lb 0.7 kg	1/4" NPT	3/16 in 5 mm	11 cfm 5 l/sec	73	F
CSE5PR	1 to 5 N·m 8.85 to 44.25 lbf·in	2300 rpm	1/4 in. HEX	8.35 in 212 mm	32.45 oz 2.02 lb 0.920 kg	1/4" NPT	5/16 in 8 mm	19 cfm 9 l/sec	74	F
CSE6PR	1.5 to 6 N·m 13.28 to 53.1 lbf·in	1400 rpm	1/4 in. HEX	8.82 in 224 mm	34.57 oz 2.16 lb 0.98 kg	1/4" NPT	5/16 in 8 mm	19 cfm 9 l/sec	74	F
CSE8PR	1.5 to 8 N·m 13.28 to 70.8 lbf·in	900 rpm	1/4 in. HEX	8.82 in 224 mm	34.57 oz 2.16 lb 0.98 kg	1/4" NPT	5/16 in 8 mm	19 cfm 9 l/sec	74	F
CSE10PR	1.5 to 10 N·m 13.28 to 88.5 lbf·in	450 rpm	1/4 in. HEX	8.82 in 224 mm	34.57 oz 2.16 lb 0.98 kg	1/4" NPT	5/16 in 8 mm	19 cfm 9 l/sec	74	F
CY7PR1	4.5 to 13 N·m 39.83 to 115.05 lbf·in	1600 rpm	1/4 in. HEX	8.19 in 208 mm	48.33 oz 3.01 lb 1.37 kg	1/4" NPT	5/16 in 8 mm	21 cfm 10 l/sec	80	F
CY9PR1	6 to 16 N·m 53.1 to 141.6 lbf·in	700 rpm	1/4 in. HEX	9.37 in 238 mm	55.38 oz 3.01 lb 1.57 kg	1/4" NPT	5/16 in 8 mm	21 cfm 10 l/sec	80	F