



ASG, Division of Jergens, Inc.

Jergens Way, 15700 South Waterloo Road
Cleveland, Ohio 44110-3898 USA

Phone: 216-486-6163 • **Toll-Free USA:** 888-486-6163

Fax: 216-481-4519

Email: asginfo@asg-jergens.com • **Website:** www.asg-jergens.com

FIAM Non Auto Shutoff Pneumatic Screwdrivers & Nutrunners

Gold standard quality cushion clutch technology

Hex and square drives

Push to start, lever start, trigger start, push/lever start combination and push/trigger start combination models

Torque range across all cushion clutch models: 7.08 to 194.7 lbf.in (0.8 to 22 N.m)

⚠ WARNING Cancer or Reproductive Harm - www.P65Warnings.ca.gov



1 2

Item #	Torque	Free Speed	Drive Size	Length	Weight	Air Inlet	Min. Hose I.D.	Air Consumption	Noise Level ±2dBA	F
CSE5LRE	1 to 5 N·m 8.85 to 44.25 lbf·in	2500 rpm	1/4 in. HEX	9.06 in 230 mm	33.16 oz 2.07 lb 0.94 kg	1/4" NPT	5/16 in 8 mm	19 cfm 9 l/sec	76	F

Item #	Torque	Free Speed	Drive Size	Length	Weight	Air Inlet	Min. Hose I.D.	Air Consumption	Noise Level ±2dBA	F
SCZ5R	4.2 N·m 5.31 to 37.17 lbf·in	600 rpm	1/4 in. HEX	8.03 in 204 mm	17.28 oz 1.07 lb 0.49 kg	1/8" NPT	3/16 in 5 mm	11 cfm 5 l/sec	74	F
CSE5LR	1 to 5 N·m 8.85 to 44.25 lbf·in	2500 rpm	1/4 in. HEX	8.74 in 222 mm	28.92 oz 1.8 lb 0.82 kg	1/4" NPT	5/16 in 8 mm	19 cfm 9 l/sec	76	F
CSE6LR	1.5 to 6 N·m 13.28 to 53.1 lbf·in	1500 rpm	1/4 in. HEX	8.74 in 222 mm	28.92 oz 1.8 lb 0.82 kg	1/4" NPT	5/16 in 8 mm	19 cfm 9 l/sec	76	F
CSE8LR	1.5 to 8 N·m 13.28 to 70.8 lbf·in	1000 rpm	1/4 in. HEX	8.74 in 222 mm	28.92 oz 1.8 lb 0.82 kg	1/4" NPT	5/16 in 8 mm	19 cfm 9 l/sec	76	F
CSE10LR	1.5 to 10 N·m 13.28 to 88.5 lbf·in	500 rpm	1/4 in. HEX	8.74 in 222 mm	28.92 oz 1.8 lb 0.82 kg	1/4" NPT	5/16 in 8 mm	19 cfm 9 l/sec	76	F
SCSE5R	1 to 5 N·m 8.85 to 44.25 lbf·in	2500 rpm	1/4 in. HEX	8.90 in 226 mm	28.92 oz 1.8 lb 0.82 kg	1/4" NPT	5/16 in 8 mm	19 cfm 9 l/sec	76	F
SCSE6R	1.5 to 6 N·m 13.28 to 53.1 lbf·in	1500 rpm	1/4 in. HEX	8.90 in 226 mm	28.92 oz 1.8 lb 0.82 kg	1/4" NPT	5/16 in 8 mm	19 cfm 9 l/sec	76	F
SCSE8R	1.5 to 8 N·m 13.28 to 70.8 lbf·in	1000 rpm	1/4 in. HEX	8.90 in 226 mm	28.92 oz 1.8 lb 0.82 kg	1/4" NPT	5/16 in 8 mm	19 cfm 9 l/sec	76	F