



ASG, Division of Jergens, Inc.

Jergens Way, 15700 South Waterloo Road
Cleveland, Ohio 44110-3898 USA

Phone: 216-486-6163 • **Toll-Free USA:** 888-486-6163

Fax: 216-481-4519

Email: [• Website:](#) _____

Pneumatic Slip-Clutch

Manufactured with high quality materials

High performance

Reduced noise level

Maximum reliability

Reduced weight & dimensions

Reversible & non-reversible models available

Available in two starting systems: push-to-start and remote start

Optional axial compensator: an accessory to eliminate any difference of screw height on the component.

Facilitates entry of screw and reduces axial thrust on the motor's mechanical components, protecting the internal components and guaranteeing their

[+ more](#)



1

Item #	Torque	Drive Size	Weight	Air Consumption	Operation	Reversible	Free Speed
MCZE2	.8 to 2.5 N·m 7.08 to 22.125 lbf·in	1/4" Hex	1.45 lb	14.83 cfm	Remote Start		2800

[Contact us](#)

Item #	Torque	Drive Size	Weight	Air Consumption	Operation	Reversible	Free Speed
MCZE3	.8 to 3 N·m 7.08 to 26.55 lbf·in	1/4" Hex	1.65 lb	14.83 cfm	Remote Start	No	1300 rpm
MCZE4	.8 to 3.3 N·m 7.08 to 29.205 lbf·in	1/4" Hex	1.65 lb	14.83 cfm	Remote Start	No	850 rpm
MCZE5	.6 to 4.2 N·m 5.31 to 37.17 lbf·in	1/4" Hex	1.65 lb	14.83 cfm	Remote Start	No	600 rpm
MCSE4	1 to 5.8 N·m 8.85 to 51.33 lbf·in	1/4" Hex	1.85 lb	19.07 cfm	Remote Start	No	2500 rpm
MCSE5	1.5 to 7.5 N·m 13.275 to 66.375 lbf·in	1/4" Hex	1.87 lb	19.07 cfm	Remote Start	No	1500 rpm
MCSE8	1.5 to 9.5 N·m 13.275 to 84.075 lbf·in	1/4" Hex	1.87 lb	19.07 cfm	Remote Start	No	1000 rpm
MCSE10	1.5 to 12 N·m 13.275 to 106.2 lbf·in	1/4" Hex	1.87 lb	19.07 cfm	Remote Start	No	500 rpm
MCY7-1	4.6 to 13 N·m 40.71 to 115.05 lbf·in	1/4" Hex	2.42 lb	21.19 cfm	Remote Start	No	1700 rpm
MCY9-1	6 to 16 N·m 53.1 to 141.6 lbf·in	1/4" Hex	2.86 lb	21.19 cfm	Remote Start	No	750 rpm

Item #	Torque	Drive Size	Weight	Air Consumption	Operation	Reversible	Free Speed
MCY11-1	6 to 22 N·m 53.1 to 194.7 lbf·in	1/4" Hex	2.86 lb	21.19 cfm	Remote Start	No	500 rpm
MSCZE2	.8 to 2.5 N·m 7.08 to 22.125 lbf·in	1/4" Hex	1.58 lb	14.83 cfm	Push-to-Start	No	2800 rpm
MSCZE3	.8 to 3 N·m 7.08 to 26.55 lbf·in	1/4" Hex	1.61 lb	14.83 cfm	Push-to-Start	No	1300 rpm
MSCZE4	.8 to 3.3 N·m 7.08 to 29.205 lbf·in	1/4" Hex	1.61 lb	14.83 cfm	Push-to-Start	No	850 rpm
MSCZE5	.6 to 4.2 N·m 5.31 to 37.17 lbf·in	1/4" Hex	1.61 lb	14.83 cfm	Push-to-Start	No	600 rpm
MSCSE4	1 to 5.8 N·m 8.85 to 51.33 lbf·in	1/4" Hex	2 lb	19.07 cfm	Push-to-Start	No	2500 rpm
MSCSE5	1.5 to 7.5 N·m 13.275 to 66.375 lbf·in	1/4" Hex	2.02 lb	19.07 cfm	Push-to-Start	No	1500 rpm
MSCSE8	1.5 to 9.5 N·m 13.275 to 84.075 lbf·in	1/4" Hex	2.02 lb	19.07 cfm	Push-to-Start	No	1000 rpm
MSCSE10	1.5 to 12 N·m 13.275 to 106.2 lbf·in	1/4" Hex	2.02 lb	19.07 cfm	Push-to-Start	No	500 rpm

.8 to 2.5

Item #	Torque	Drive Size	Weight	Air Consumption	Operation	Reversible	Free Speed
MCZE2R	N·m 7.08 to 22.125 lbf·in	1/4" Hex	1.74 lb	14.83 cfm	Remote Start	Yes	2800 rpm
MCZE3R	.8 to 3 N·m 7.08 to 26.55 lbf·in	1/4" Hex	1.76 lb	14.83 cfm	Remote Start	Yes	1300 rpm
MCZE4R	.8 to 3.3 N·m 7.08 to 29.205 lbf·in	1/4" Hex	1.76 lb	14.83 cfm	Remote Start	Yes	850 rpm
MCZE5R	.6 to 4.2 N·m 5.31 to 37.17 lbf·in	1/4" Hex	1.76 lb	14.83 cfm	Remote Start	Yes	600 rpm
MCSE4R	1 to 5.8 N·m 8.85 to 51.33 lbf·in	1/4" Hex	1.72 lb	19.07 cfm	Remote Start	Yes	2500 rpm
MCSE5R	1.5 to 7.5 N·m 13.275 to 66.375 lbf·in	1/4" Hex	1.91 lb	19.07 cfm	Remote Start	Yes	1500 rpm
MCSE8R	1.5 to 9.5 N·m 13.275 to 84.075 lbf·in	1/4" Hex	1.91 lb	19.07 cfm	Remote Start	Yes	1000 rpm
MCSE10R	1.5 to 12 N·m 13.275 to 106.2 lbf·in	1/4" Hex	1.91 lb	19.07 cfm	Remote Start	Yes	500 rpm
MCY7R-1	4.5 to 13 N·m 38.825 to 115.05 lbf·in	1/4" Hex	2.42 lb	21.19 cfm	Remote Start	Yes	1600 rpm

Item #	Torque	Drive Size	Weight	Air Consumption	Operation	Reversible	Free Speed
MCY9R-1	6 to 16 N·m 53.1 to 141.6 lbf·in	1/4" Hex	2.86 lb	21.19 cfm	Remote Start	Yes	700 rpm
MCY11R-1	6 to 22 N·m 53.1 to 194.7 lbf·in	1/4" Hex	2.86 lb	21.19 cfm	Remote Start	Yes	450 rpm