



ASG, Division of Jergens, Inc.

Jergens Way, 15700 South Waterloo Road
Cleveland, Ohio 44110-3898 USA

Phone: 216-486-6163 • **Toll-Free USA:** 888-486-6163

Fax: 216-481-4519

Email: [• Website:](#) _____

Pneumatic Shut-Off Clutch

Manufactured with high quality materials

High performance

Reduced noise level

Maximum reliability

Reduced weight & dimensions

Reversible & non-reversible models available

Available in two starting systems: push-to-start and remote start

Optional axial compensator: an accessory to eliminate any difference of screw height on the component.

Facilitates entry of screw and reduces axial thrust on the motor's mechanical components, protecting the internal components and guaranteeing their

[+ more](#)



1

Item #	Torque	Drive Size	Weight	Air Consumption	Noise Level ±2dBA	Operation	Reversible	Free Speed
20MC2A	.4 to 2.5 N·m 3.54 to	1/4" Hex	1.65 lb	11.65 cfm	75	Remote Start	Contact us	

Item #	Torque	Drive Size	Weight	Air Consumption	Noise Level ±2dBA	Operation	Reversible	Free Speed
	22.125 lbf·in							
20MC3A	0.4 to 3.0 N·m 3.54 to 26.55 lbf·in	1/4" Hex	1.69 lb	11.65 cfm	75	Remote Start	No	1400 rpm
20MC4A	.4 to 4 N·m 3.54 to 35.4 lbf·in	1/4" Hex	1.69 lb	11.65 cfm	75	Remote Start	No	1000 rpm
20MC5A	.4 to 5 N·m 3.54 to 44.25 lbf·in	1/4" Hex	1.69 lb	11.65 cfm	75	Remote Start	No	650 rpm
MCSEZ4A	.9 to 4 N·m 7.965 to 35.4 lbf·in	1/4" Hex	2.05 lb	19.07 cfm	76	Remote Start	No	2500 rpm
MCSE5A	2.5 to 5 N·m 22.125 to 44.25 lbf·in	1/4" Hex	2.16 lb	19.07 cfm	76	Remote Start	No	1500 rpm
MCSE8A	2.5 to 8 N·m 22.125 to 70.8 lbf·in	1/4" Hex	2.16 lb	19.07 cfm	76	Remote Start	No	1000 rpm
MCSE10A	2.5 to 10 N·m 22.125 to 88.5 lbf·in	1/4" Hex	2.16 lb	19.07 cfm	76	Remote Start	No	500 rpm

Item #	Torque	Drive Size	Weight	Air Consumption	Noise Level ±2dBA	Operation	Reversible	Free Speed
MCY9A	7 to 18 N·m 61.95 to 159.3 lbf·in	1/4" Hex	3.3 lb	21.19 cfm	79	Remote Start	No	800 rpm
MCY11A	7.0 to 24 N·m 61.95 to 212.4 lbf·in	1/4" Hex	3.3 lb	21.19 cfm	79	Remote Start	No	550 rpm
MCG25A1	12 to 25 N·m 106.2 to 221.25 lbf·in	3/8" Square	4.84 lb	27.55 cfm	79	Remote Start	No	600 rpm
MCG40A1	18 to 40 N·m 159.3 to 354 lbf·in	3/8" Square	4.84 lb	27.55 cfm	79	Remote Start	No	450 rpm
20MCS2A	.4 to 2.5 N·m 3.54 to 22.125 lbf·in	1/4" Hex	1.65 lb	11.65 cfm	75	Push-to-Start	No	2700 rpm
20MCS3A	0.4 to 3.0 N·m 3.54 to 26.55 lbf·in	1/4" Hex	1.69 lb	11.65 cfm	75	Push-to-Start	No	1400 rpm
20MCS4A	.4 to 4 N·m 3.54 to 35.4 lbf·in	1/4" Hex	1.69 lb	11.65 cfm	75	Push-to-Start	No	1000 rpm

Item #	Torque	Drive Size	Weight	Air Consumption	Noise Level ±2dBA	Operation	Reversible	Free Speed
20MCS5A	.4 to 5 N·m 3.54 to 44.25 lbf·in	1/4" Hex	1.69 lb	11.65 cfm	75	Push-to- Start	No	650 rpm
MSCEZ4A	.9 to 4 N·m 7.965 to 35.4 lbf·in	1/4" Hex	2 lb	19.07 cfm	76	Push-to- Start	No	2500 rpm
MSCSE5A	2.5 to 5 N·m 22.125 to 44.25 lbf·in	1/4" Hex	2.18 lb	19.07 cfm	76	Push-to- Start	No	1500 rpm
MSCSE8A	2.5 to 8 N·m 22.125 to 70.8 lbf·in	1/4" Hex	2.18 lb	19.07 cfm	76	Push-to- Start	No	1000 rpm
MSCSE10A	2.5 to 10 N·m 22.125 to 88.5 lbf·in	1/4" Hex	2.18 lb	19.07 cfm	76	Push-to- Start	No	500 rpm
MSCY9A	7 to 18 N·m 61.95 to 159.3 lbf·in	1/4" Hex	3.3 lb	21.19 cfm	79	Push-to- Start	No	800 rpm
MSCY11A	7.0 to 24 N·m 61.95 to 212.4 lbf·in	1/4" Hex	3.3 lb	21.19 cfm	79	Push-to- Start	No	550 rpm
	.4 to 2.5							

Item #	Torque	Drive Size	Weight	Air Consumption	Noise Level ±2dBA	Operation	Reversible	Free Speed
20MC2RA	N·m 3.54 to 22.125 lbf·in	1/4" Hex	1.67 lb	11.65 cfm	77	Remote Start	Yes	2700 rpm
20MC3RA	0.4 to 3.0 N·m 3.54 to 26.55 lbf·in	1/4" Hex	1.72 lb	11.65 cfm	77	Remote Start	Yes	1400 rpm
20MC4RA	.4 to 4 N·m 3.54 to 35.4 lbf·in	1/4" Hex	1.72 lb	11.65 cfm	77	Remote Start	Yes	1000 rpm
20MC5RA	.4 to 5 N·m 3.54 to 44.25 lbf·in	1/4" Hex	1.72 lb	11.65 cfm	77	Remote Start	Yes	650 rpm
MCSEZ4RA	.9 to 4 N·m 7.965 to 35.4 lbf·in	1/4" Hex	2.07 lb	19.07 cfm	78	Remote Start	Yes	2500 rpm
MCSE4RA	2.5 to 5 N·m 22.125 to 44.25 lbf·in	1/4" Hex	2.18 lb	19.07 cfm	78	Remote Start	Yes	1500 rpm
MCSE8RA	2.5 to 8 N·m 22.125 to 70.8 lbf·in	1/4" Hex	2.18 lb	19.07 cfm	78	Remote Start	Yes	1000 rpm
MCSE10RA	2.5 to 10 N·m 22.125 to 88.5	1/4" Hex	2.18 lb	19.07 cfm	78	Remote Start	Yes	500 rpm

Item #	Torque	Drive Size	Weight	Air Consumption	Noise Level ±2dBA	Operation	Reversible	Free Speed
	lbf·in							
MCY9RA	7 to 16 N·m 61.95 to 141.6 lbf·in	1/4" Hex	3.3 lb	21.19 cfm	81	Remote Start	Yes	700 rpm
MCY11RA	7.0 to 24 N·m 61.95 to 212.4 lbf·in	1/4" Hex	3.3 lb	21.19 cfm	81	Remote Start	Yes	450 rpm
MCG25RA1	12 to 25 N·m 106.2 to 221.25 lbf·in	3/8" Square	4.84 lb	27.55 cfm	81	Remote Start	Yes	600 rpm
MCG40RA1	18 to 40 N·m 159.3 to 354 lbf·in	3/8" Square	5.06 lb	27.55 cfm	81	Remote Start	Yes	450 rpm