



ASG, Division of Jergens, Inc.

Jergens Way, 15700 South Waterloo Road

Cleveland, Ohio 44110-3898 USA

Phone: 216-486-6163 • **Toll-Free USA:** 888-486-6163

Fax: 216-481-4519

Email: [Website:](#)

NSB and NSR Series

The NSB (Manual Pick-Up) and NSR (Robotic Pick-Up) Series accommodates a wide variety of screw sizes by plugging in interchangeable rails, featuring an 80cc hopper and handles screw sizes #000 to #4.

⚠ WARNING Cancer or Reproductive Harm - www.P65Warnings.ca.gov

BUY NOW!



1

Item #	Model No.	Screw Diameter	Max. Screw Length	 Contact us
67240	NSB-10	Up to 0.039 in Up to 1.0 mm	0.7874 in 20 mm	
67241	NSB-12	0.039 to 0.047 in 1.0 to 1.2 mm	0.7874 in 20 mm	
67242	NSB-14	0.047 to 0.055 in 1.2 to 1.4 mm	0.7874 in 20 mm	
67243	NSB-17	0.055 to 0.067 in 1.4 to 1.7 mm	0.7874 in 20 mm	

Item #	Model No.	Screw Diameter	Max. Screw Length
67244	NSB-20	0.067 to 0.079 in 1.7 to 2.0 mm	0.7874 in 20 mm
67245	NSB-23	0.079 to 0.090 in 2.0 to 2.3 mm	0.7874 in 20 mm
67246	NSB-26	0.090 to 0.102 in 2.3 to 2.6 mm	0.7874 in 20 mm
67247	NSB-30	0.102 to 0.118 in 2.6 to 3.0 mm	0.7874 in 20 mm
67290	NSR-10	Up to 0.039 in Up to 1.0 mm	0.7874 in 20 mm
67291	NSR-12	0.039 to 0.047 in 1.0 to 1.2 mm	0.7874 in 20 mm
67292	NSR-14	0.047 to 0.055 in 1.2 to 1.4 mm	0.7874 in 20 mm
67293	NSR-17	0.055 to 0.067 in 1.4 to 1.7 mm	0.7874 in 20 mm
67294	NSR-20	0.067 to 0.079 in 1.7 to 2.0 mm	0.7874 in 20 mm
67295	NSR-23	0.079 to 0.090 in 2.0 to 2.3 mm	0.7874 in 20 mm
67296	NSR-26	0.090 to 0.102 in 2.3 to 2.6 mm	0.7874 in 20 mm
67297	NSR-30	0.102 to 0.118 in 2.6 to 3.0 mm	0.7874 in 20 mm