

## Section 2: Non Auto Shut-Off Pneumatic Screwdrivers



HPS39



HDP48

- Value engineered technology
- Light weight, ergonomic composite housings
- Reversible

### Pistol Grip Trigger Start: Cushion Clutch

Model Number	ASG Number	Torque Range		Free Speed	Drive Size	Operating Pressure		Inlet Size	Min Hose ID	Air Consumption		±2 DBA
		lbf.in	N.m	RPM		PSI	Bar			CFM	L/Sec.	
HCP39	68340	4.4 - 35.4	0.5 - 4.0	1600	1/4" Hex	90	6.2	1/4" NPT	3/16"	9.9	4.7	72
HCP48	68342	8.9 - 49.6	1.0 - 5.6	1700	1/4" Hex	90	6.2	1/4" NPT	5/16"	19.4	9.17	76
HCP58	68343	8.9 - 92.04	1.0 - 10.4	750	1/4" Hex	90	6.2	1/4" NPT	5/16"	19.4	9.17	76

### Pistol Grip Trigger Start: Positive Clutch

Model Number	ASG Number	Torque Range		Free Speed	Drive Size	Operating Pressure		Inlet Size	Min Hose ID	Air Consumption		±2 DBA
		lbf.in	N.m	RPM		PSI	Bar			CFM	L/Sec.	
HPS39	68360	7.5 - 35.4	0.85 - 4.0	1600	1/4" Hex	90	6.2	1/4" NPT	3/16"	9.9	4.7	70
HPS48	68362	10.6 - 49.6	1.2 - 5.6	1700	1/4" Hex	90	6.2	1/4" NPT	5/16"	19.4	9.17	75
HPS58	68363	19.5 - 92.04	2.2 - 10.4	750	1/4" Hex	90	6.2	1/4" NPT	5/16"	19.4	9.17	75

### Pistol Grip Trigger Start: Direct Drive

Model Number	ASG Number	Torque Range		Free Speed	Drive Size	Operating Pressure		Inlet Size	Min Hose ID	Air Consumption		±2 DBA
		lbf.in	N.m	RPM		PSI	Bar			CFM	L/Sec.	
HDP39	68370	7.5 - 35.4	0.85 - 4.0	1600	1/4" Hex	90	6.2	1/4" NPT	3/16"	9.9	4.7	72
HDP48	68372	10.6 - 49.6	1.2 - 5.6	1700	1/4" Hex	90	6.2	1/4" NPT	5/16"	19.4	9.17	76
HDP58	68373	19.5 - 92.04	2.2 - 10.4	750	1/4" Hex	90	6.2	1/4" NPT	5/16"	19.4	9.17	76