

Section 2: Brush Type Electric Screwdrivers

Premium Screwdrivers



HIOS® CL Series

- Brush type motor offers proven performance
- Inline body style
- External torque adjustment
- 4 mm drive type is a HIOS® drive (wing style)
- Tamper proof torque locking nuts available
- Low RPM models for low speed applications
- CE certified



CL-2000



CL-4000



CL-6500



CL-9000-PS

Model Number	ASG Number	Operation	Torque Range		Speed (RPM)		Length		Weight lb.	Drive Type	Power Supply	
			lbf.in	N.m	HI	LOW	mm	in.			HIOS®	OR ASG
CL-2000	64107	Lever	0.18 - 1.8	0.02 - 0.2	680	490	166	6.5	0.4	4 mm	CLT-60	OR PS-55C
CL-3000	64109	Lever	0.27 - 1.8	0.03 - 0.2	1000	670	183	7.2	0.8	4 mm	CLT-60	OR PS-55C
CL-4000	64110	Lever	0.9 - 4.9	0.1 - 0.55	1000	690	197	7.75	0.84	1/4" Hex	CLT-60	OR PS-55C
CL-4000	64111	Lever	0.9 - 4.9	0.1 - 0.55	1000	690	197	7.75	0.84	4 mm	CLT-60	OR PS-55C
CL-6000	64116	Lever	1.8 - 8.85	0.2 - 1.0	800	500	220	8.7	1.3	1/4" Hex	CLT-60	OR PS-55
CL-6000	64106	Lever	1.8 - 8.85	0.2 - 1.0	800	500	220	8.7	1.3	5 mm	CLT-60	OR PS-55
CL-6000-PS	64200	Push-to-Start	1.8 - 8.85	0.2 - 1.0	800	500	220	8.7	1.3	1/4" Hex	CLT-60	OR PS-55
CL-6000*	64257	Lever	1.8 - 8.85	0.2 - 1.0	104	70	220	8.7	1.3	1/4" Hex	CLT-60	OR PS-55
CL-6500	64121	Lever	2.7 - 14.2	0.3 - 1.6	900	600	235	9.25	1.5	1/4" Hex	CLT-60	OR PS-55
CL-6500	64118	Lever	2.7 - 14.2	0.3 - 1.6	900	600	235	9.25	1.5	5 mm	CLT-60	OR PS-55
CL-6500-PS	64120	Push-to-Start	2.7 - 14.2	0.3 - 1.6	900	600	235	9.25	1.5	1/4" Hex	CLT-60	OR PS-55
CL-6500*	64268	Lever	2.7 - 14.2	0.3 - 1.6	116	75	235	9.25	1.5	1/4" Hex	CLT-60	OR PS-55
CL-7000	64126	Lever	2.7 - 22.1	0.3 - 2.5	750	—	255	10.0	1.7	1/4" Hex	CLT-60	—
CL-7000	64117	Lever	2.7 - 22.1	0.3 - 2.5	750	—	255	10.0	1.7	5 mm	CLT-60	—
CL-7000-PS	64125	Push-to-Start	2.7 - 22.1	0.3 - 2.5	750	—	255	10.0	1.7	1/4" Hex	CLT-60	—
CL-7000HT	64129	Lever	2.7 - 22.1	0.3 - 2.5	480	—	255	10.0	1.7	1/4" Hex	CLT-60	—
CL-7000*	64269	Lever	2.7 - 22.1	0.3 - 2.5	96	60	255	10.0	1.7	1/4" Hex	CLT-60	—
CL-9000-PS	64138	Push-to-Start	10.6 - 44.3	1.2 - 5.0	530	—	250	9.8	6.6	1/4" Hex	CLT-80	—
CL-9000-PS-HT	64139	Push-to-Start	10.6 - 70.8	1.2 - 8.0	330	—	250	9.8	6.6	1/4" Hex	CLT-80	—

* Slow Speed Models