




Speed, Performance, Value - Perfect Balance

- Up to 12 Weighing units (including one custom unit)
- Date and time
- Full range tare
- Zero Tracking
- Multilingual display
- Large backlit display with dual text prompts
- Capacity tracker
- Large stainless steel pan
- Solid metal housing
- Overload protection
- Lock down mounting slot for Kensington® type lock and cable
- Non-slip adjustable levelling feet
- Colour coded, sealed keypad
- Dual tare keys
- Removable draft shield supplied on 0.001g readabilities
- Modern low profile design
- RS-232 bi-directional interface
- GLP print outs
- External calibration
- Rechargeable battery
- DC Adapter
- Auto sleep / power down function to save battery life
- Dust Cover not available on PGL10001, PGL20001 and PGL30001
- Weighing
- Parts counting
- Percentage weighing
- Check weighing
- Density determination
- Below balance weighing



Technical Specifications

Model	PGL 4001	PGL 6001	PGL 8001	PGL 10001	PGL 12001	PGL 15001	PGL 20001	PGL 30001
Maximum capacity	4000g	6000g	8000g	10kg	12kg	15kg	20kg	30kg
Readability	0.1g	0.1g	0.1g	0.1g	0.1g	0.1g	0.1g	0.1g
Repeatability (S.D.)	0.2g	0.2g	0.2g	0.2g	0.2g	0.2g	0.2g	0.2
Linearity (±)	0.2g	0.2g	0.2g	0.4g	0.4g	0.4g	0.4g	0.4g
Units of measurement	Gram (g), Kilogram (kg), Milligram (mg), Carat (ct), Pound (lb), Ounce (Oz), Pound-Ounce (lb-oz), Grain (GN), Troy Ounce (Ozt), Pennyweight (dWt), Newton (N), Custom unit							
Pan size	7.6 x 7.6" / 192 x 192mm			15.7 x 11.8" / 400 x 300mm	7.6 x 7.6" / 192 x 192mm		15.7 x 11.8" / 400 x 300mm	15.7 x 11.8" / 400 x 300mm

General Specifications

Typical stabilisation time	2-3 Sec
Power supply	12VDC 800mA AC adaptor and rechargeable battery pack
Calibration	Automatic External
Display	Backlit LCD display with dual digits and capacity tracker
Overall dimensions (wxdxh)	9.9 x 14.1 x 4.1" / 251 x 358 x 104mm
Dimensions notes	400 x 460 x 100mm (PGL10001 & PGL20001)

Key Accessories

- RS-232 to USB Interface Cable (must be ordered in conjunction)
- Security Lock and Cable
- Anti-Vibration Table
- Below Balance Hanger
- In-use Cover
- Dust Cover
- Adam DU - Data Collection Program
- RS-232 to PC Cable
- ASTM 3 - 10000g (2 x 5000g) calibration weights
- ASTM 2 - 1000g calibration weight
- ASTM 4, 2000g calibration weight
- ASTM 3 - 5000g calibration weight
- ATP Thermal Printer
- Thermal Paper For Adam ATP (10 pack)
- ASTM 1, 200g calibration weight



Adam Equipment - offices worldwide

www.adamequipment.com