



# **Product Info**

Brand: AM Series
UPC: 85339974888
UNSPSC: 39121324
Carton Quantity: 1
Carton Weight: 8 lbs

Country of Origin: United States of America

Color: Gray (RAL 7035)

Material: ULTRAGUARD® Fiberglass reinforced polyester -

compression molded SMC box and Cover

**Additional Materials:** 316 stainless steel external hardware (hinges/latches/fasteners), 316 stainless steel mounting brackets, Plated carbon steel internal hardware, Brass inserts, Polyurethane (FIP) Formed-In-Place gasket system

## **AM1224T**

12"x12"x4" AM Series fiberglass wall mount enclosure assembly with hinged cover and stainless-steel twist latch **Availability:** 

**In-Stock** (Will ship within 2-4 business days after receipt of order)

Enclosure Type: JIC Size Cover Type: Opaque

Closure Type: metal twist latch

Mounting Description: Stainless steel feet fastened to

back side brass inserts

Box Features:
Installation Type:
Height: 12.14 in
Width: 12.14 in
Depth: 4.13 in
Usable Depth: 3.73 in
Volume: 609 cu in

#### Features:

Non-corrosive, non-conductive, light weight with lower installation cost, easy to modify and longer life cycle compared to steel. Rigid design with back panel inserts plus stainless steel mounting brackets and a gasket system encased in a continuous channel on the cover.

### **Application:**

Enclose and protect electrial and electronic controls, instruments or components for indoor and outdoor applications. Especially well suited for extreme temperature and corrosive environments.

### Standards:

UL 508A, UL 50 and UL 50E Types 1, 2, 3, 3R, 4, 4X, 12 and 13;  $\underline{\text{File No. }}$   $\underline{\text{E120175}}$ 

CSA-C22.2 No. 14 and CSA C22.2 No. 94 Types 1, 2, 3, 3R, 4, 4X, 12 and 13; File No. 89590

### Complies with:

1. EN / IEC 60204-1 and 60529 Type IP66

2. RoHS directive



