

222 N Union Street • Bryan, OH 43506 Ph: (800) 722-2679 • Fx: (800) 237-7269

Email: sales@alliedmoulded.com www.alliedmoulded.com

# AM1084HP9



# **Product Description**

Wall mount enclosure assembly with 9 pushbutton holes in cover

Cover Type: Hinged 2-Screw Solid/Opaque Cover (30.5 mm PB Hole Size)

Brand: Pushbutton Series Catalog #: AM1084HP9

Height: 10.14 in. Width: 8.26 in. Depth: 4 in. Usable Depth: 3.68 in. Volume: 346 cu. in. Carton Quantity: 1 Carton Weight: 5 lb.

UPC: 085339840329 UNSPSC: 39121326 Country of Origin: United States of America

# FEATURES

Non-corrosive, non-conductive, light weight with lower installation cost, easy to modify and longer life cycle compared to steel. Rigid design with back panel inserts plus stainless steel mounting brackets and a gasket system encased in a continuous channel on the cover.

# **APPLICATION**

Enclose and protect electrial and electronic controls, instruments or components for indoor and outdoor applications. Especially well suited for extreme temperature and corrosive environments.

# **STANDARDS**

UL 508A, UL 50 and UL 50E Types 1, 2, 3, 3R, 4, 4X, 12 and 13; File No. E120175

CSA-C22.2 No. 14 and CSA C22.2 No. 94 Types 1, 2, 3, 3R, 4, 4X, 12 and 13; File No. 89590

Complies with:

- 1. EN / IEC 60204-1 and 60529 Type IP66
- 2. RoHS directive



# COLOR

RAL 7035 - Gray

# MATERIAL

ULTRAGUARD® Fiberglass reinforced polyester - compression molded SMC box and Cover

# MOUNTING

Stainless steel feet fastened to back side brass inserts

#### **ADDITIONAL MATERIALS**

316 stainless steel external hardware (hinges, latches and fasteners)

316 stainless steel mounting brackets

Plated carbon steel internal hardware

Brass inserts

Polyurethane (FIP) Formed-In-Place gasket system

© 2016 Allied Moulded Products, Inc.

**Product Specification Sheet**