### 22mm Non-Illuminated Metal Operators









Certified for **NEMA Type 4X** 12 environment.

# Flush Momentary with mounting bracket





	Color	Cat No.
	White	2AF1
	Black	2AF2
	Green	2AF3
	Red	2AF4
	Blue	2AF6
	Yellow	2AF8

### **Booted** Momentary with mounting bracket





Color	Cat No.
White	2AB1
Black	2AB2
Green	2AB3
Red	2AB4
Blue	2AB6
Yellow	2AB8

# **Projecting** Momentary with mounting bracket





		Color	Cat No.
		White	2AP1
		Black	2AP2
		Green	2AP3
		Red	2AP4
ı		Blue	2AP6
	_	Yellow	2AP8

# Recessed Momentary with mounting bracket





Color	Cat No.
White	2AF1RH
Black	2AF2RH
Green	2AF3RH
Red	2AF4RH
Blue	2AF6RH
Yellow	2AF8RH







All above operators available with remote attachment. Standard length is 50mm (2 in.), other lengths available upon request. Contact Altech for Part Number.





### Markings on Request











Altech Push Buttons are available in a variety of markings, including molded arrows. Please contact Altech for further information and part numbers.

#### **Switch Contacts** (sold separately)





- · Heavy-duty contact blocks with mounting screws. Blocks can be stacked 2 blocks across by 3 blocks deep for a total of 6 circuits.
- · Contact blocks are available with silver contacts or gold plated contacts
- · Self-wiping contacts

#### **Panel Mount**

Normally Open Silver S1 Normally Closed Silver S2 Normally Open Gold Plated **S3** Normally Closed Gold Plated **S4** 

#### **Base Mount\***

Normally Open Silver **S5** Normally Closed Silver **S6 S7** Normally Open Gold Plated Normally Closed Gold Plated S8

\* For use with non-illuminated operators in thermoplastic or aluminum enclosures listed on pages 30 and 36-37.