

Assistive Listening

Tour Guide & Assistive Listening Systems



- Pre-set 100 (10 x10) Selectable Channels
- True Diversity for Maximum Range and Dropout Protection
- PLL Synthesized Circuit
- EIA Standard 1/2U Rack-mountable Metal Chassis
- Up to 500' Line-of-Sight Operating Range

Touchboards

205 Westwood Ave, Long Branch, NJ 07740
Phone: 866-94 BOARDS (26273) / (732)-222-1511
Fax: (732)-222-7088 | E-mail: sales@touchboards.com



TWO YEAR WARRANTY



AnchorAudio.com • 800.262.4671



TWO YEAR WARRANTY

UHF Tour Guide System

This multi-purpose portable system provides one-way communication that helps cut through the background noise. Your tour guide or interpreter wears a compact body-pack transmitter with headset microphone. Listeners use portable belt pack receivers and lightweight headphones to hear every word clearly and easily.



TOUR-9000 PACKAGE

- Six ALB-9000 belt pack receivers
- Six AL-HP in-ear headphones
- HBM-TA4F headband mic
- WB-9000 wireless transmitter

Guided Tours/Factories
Language Translation
Museums/Tourist Attractions
Classrooms/Workshops

16 Channel UHF In-Ear Monitor

Anchor Audio assistive listening systems are designed to help hard of hearing people better understand speech, music, and other sounds during a movie, performance, lecture, meeting, or worship service.

Houses of Worship/Theaters/Cinemas
Auditoriums/Classrooms

AL-9000 PACKAGE

- Four ALB-9000 belt pack receivers
- Four AL-HP in-ear headphones
- ALT-9000 wireless transmitter base station



ACCESSORIES

- ALB-9000 Belt pack receiver
- ALT-9000 Transmitter base station
- AL-HP Lightweight headphone

Technical Specifications

WB-9000 - Belt Pack Transmitter

System Range	Up to 500' line of sight
Frequency Range	UHF 902 - 928 MHz
RF Power Output	100 mW
T.H.D.	< 0.5% @ 1KHz
Dimensions (WHD)	2.48" x 4.33" x 1.06" (63 x 110 x 27 mm)

ALT-9000 - Base Station Transmitter

System Range	Up to 500' line of sight
Frequency Range	UHF 902 - 928 MHz
RF Power Output	100 mW max
T.H.D.	< 0.5% @ 1KHz
Power Supply	DC 12 ~ 18 V / 500mA
Inputs:	2 x 1/4" / XLR combo Line In
Dimensions (WHD)	8.27" x 1.97" x 8.27" (210 x 50 x 210 mm)

ALB-9000 - Belt Pack Receiver

System Range	Up to 500' line of sight
Frequency Range	UHF 902 - 928 MHz
Oscillator	PLL synthesized
T.H.D.	< 0.5% @ 1KHz
Power Supply	DC 3V (2 x 1.5 V AA batteries)
Audio Output:	
Headphone Output	3.5mm / 16 ohms 105mW
Dimensions (WHD)	2.48" x 4.33" x 1.06" (63 x 110 x 27 mm)



(Features & Specifications Subject To Change Without Notice)