

DRAKOS

Multi-Spectral Laser Aiming/ Illumination Devices

The Armasight Drakos is the new series of an innovative, rugged, multi-spectral Class I near-infrared and visible/near-infrared laser aiming devices, designed to mount via a locking quick-release MIL-STD-1913 rail grabber on to a variety of kinetic weapons for day, low-light, and nighttime targeting. The Drakos is equipped with a wireless remote control; the laser operates on either a single CR123A 3V lithium or AA 1.5V battery, and the battery compartment adapter comes standard, which provides more than two thousand two-second activations of the lasers. The Drakos series is designed to withstand kinetic recoil of 0.50 caliber and .338 caliber Lapua ammunition, and is MIL-STD-810G compliant. The Armasight Drakos' performance level, along with its adaptability to virtually any night vision device, inherently makes it a "critical need" item for all law enforcement professionals, military personnel, hunters, and professional shooters.

Drakos – IR Laser Pointer Class I with Quick Release Mount and Wireless Remote Control

Drakos-I – Dual Channel: IR 850 Laser Pointer Class I & IR LED 850 Illuminator with Quick Release Mount and Wireless Remote Control

Drakos-II – Dual Channel: IR 850 Laser Pointer Class I & Visible Red Laser Pointer Class II with Quick Release Mount and Wireless Remote Control

- Ⓐ **Tactile click stops for windage & elevation adjustments**
- Ⓐ **Rapid active target acquisition**
- Ⓐ **True night vision compatible mode**
- Ⓐ **Utilizes single CR123A lithium battery or AA Alkaline, adapter included**
- Ⓐ **Aiming lasers are co-boresighted**
- Ⓐ **Will not cause damage to eyes**
- Ⓐ **MIL-STD-810G compliant**
- Ⓐ **Limited two-year warranty**

	Drakos	Drakos-I	Drakos-II
Wavelength (nm)	850	850	850 / 650
Laser Output Power (mW)	0.7	0.7	0.7 / 0.9
IR Illuminator Output Power (mW)	-	25	-
Operating Distance (m)	800	800	800 / 200
Aiming Dot Size (mm at 100m)	50	50	50
Elevation/Windage Adjustment Range (MOA, min)	±90		
Elevation/Windage Adjustment Increment (mils)	0.5±0.05 (5 cm at a distance of 100 m)		
Battery	Single CR123A Lithium (3V) or AA Alkaline (1.5V)	Single CR123A Lithium (3V)	Single CR123A Lithium (3V) or AA Alkaline (1.5V)
Battery Life, (hr, min)	42	13	27
Operating Temperature	-20 to +40 °C (-4 to +104 °F)		
Storage Temperature	-40 to +55 °C (-40 to +131 °F)		
Immersion	10 m for 2 hr		
Overall Dimensions (mm/in)	110 x 67 x 43 / 4.3 x 2.6 x 1.7	110 x 67 x 43 / 4.3 x 2.6 x 1.7	110 x 67 x 43 / 4.3 x 2.6 x 1.7
Weight (g/oz)	198 / 7	210 / 7.4	220 / 7.8

