

VULCAN 8X

Night Vision Riflescope

The Armasight Vulcan scopes represent the apex for the night vision weapon sight technology.

Host of the Vulcan features including wireless remote control, ability to use either CR123A or AA battery and quick release Picatinny mount with locks. Small on dimensions, but big on value – the Armasight Vulcan will not unbalance your rifle; it mounts on an adjustable mount that will fit weaver or Picatinny rails, and can be mounted in seconds without tools.

The Vulcan has multicoated all-glass lenses and an internally adjustable fine reticle that makes precise shot placement incredibly easy. This night vision riflescope is also water, dust and sand proof for increased reliability. Complete with tactical rails for lasers or illuminators (high power IR illuminator included as standard), the Armasight Vulcan is ideal for the predator hunter, tactical marksmen, or anyone that needs a compact and light night vision riflescope.

- ⓐ **Wide array of IIT configurations**
- ⓐ **Shock protected, all-glass IR transmission multicoated optics**
- ⓐ **Bright light cut-off**
- ⓐ **Illuminated reticle with brightness adjustment**
- ⓐ **Wireless remote control included**
- ⓐ **XLR-IR850 Detachable X Long-Range Infrared Illuminator**
- ⓐ **Waterproof design**
- ⓐ **Powered by a single CR123A Lithium or AA battery**
- ⓐ **Low battery indicator**
- ⓐ **Quick release mount**
- ⓐ **Mounts to standard weaver rails**
- ⓐ **Limited Two-Year Warranty**



Image Intensifier Tube	Gen 2+ SD - "Standard Definition" 45-51 lp/mm
	Gen 2+ ID - "Improved Definition" 47-54 lp/mm
	Gen 2+ HD - "High Definition" 55-72 lp/mm
	Gen 2+ QS-HD - "Quick Silver-High Definition" White Phosphor 55-72 lp/mm
	Gen 3 Bravo - 57 lp/mm (min) - 64 lp/mm (typical)
	Gen 3 Alpha - High Performance 64-72 lp/mm
	Gen 3 Ghost - "Ghost" White Phosphor 47-57 lp/mm
Magnification	Gen 3 P - High Performance IIT 64-72 lp/mm PINNACLE® IIT
	FLAG - Filmless Auto-Gated IIT (comparable to Gen 4)
Lens System	62-72 lp/mm
FOV	8x
Exit Pupil	192mm; F/2.13
Eye Relief	5.4°
Focus Range	7 mm
Diopter Adjustment	45 mm
Controls	50 m to infinity
Remote Control	-4 to +4
Brightness Control	Direct
Infrared Illuminator	Yes (wireless)
Low Battery Indicator	Manual
Power Supply	Long range (detachable)
Battery Life	Yes (in FOV)
Operating Temperature	CR123 Lithium 3V (1) or AA Alkaline 1.5V (1) or any AA or CR123 type rechargeable batteries with voltage from 1.2V to 3.2V (1)
Storage Temperature	Up to 60 hours
Dimensions	-40°C to +50°C
Weight	-50°C to +70°C
	310x108x103 mm / 12.2"x4.2"x4.1"
	1.43 kg / 3.1 lbs