

CO-MINI 3 Alpha MG

Clip-On Night Vision Device

Designed for short-to-medium range observation, the Armasight CO-MINI is the most compact commercially available clip-on night vision device. The CO-MINI uses image intensification technology and is designed to convert most low-to-mid power daytime sights, scopes, or binoculars into night vision devices. The CO-MINI can be mounted in seconds without tools. It can be attached in front of a day riflescope (using its quick-release Picatinny mount) or directly onto the day scope (or binocular/ telescope) objective lens with the included adaptor.

The CO-MINI is suitable for use with most commercial and military specification daytime sights, telescopes or binoculars (up to 6X magnification). Because the CO-MINI can be easily mounted in front of the user's existing day scope, comfort is never sacrificed, while shot release and follow through remain accurate.

The clip-on device is factory bore-sighted to greater than 1MOA accuracy, so no rezeroing is necessary. It really is as simple as mount and shoot!

The Armasight CO-MINI is intended primarily for use by demanding hunters and in short-range warfare, where field of view and ease of use is more important than high magnification. Packed with innovative and important features like variable gain control, automatic bright light shut-off, and wireless remote control, the Armasight CO-MINI is designed to make quick, intuitive shooting just as easy at night as it is during the day. The Armasight CO-MINI is equally as effective whether mounted to a brand name or lesser-known day scope at magnifications ranging from 2-6X.

- Simple and quick conversion of daytime scope, sight or binoculars to Night Vision
- Manual Gain control
- Mounts in front of riflescope with no re-zeroing required
- **A** Equipped with Wireless Remote Control
- Powered by a single alkaline 1.5V AA or 3V CR123A lithium battery
- **Quick Release Mount**
- Mil Standard Compliant
- A Limited Two-Year Warranty

Image Tube	Gen 3 Alpha - High Performance 64-72 lp/mm
Magnification	1x (recommended to use with up to 6x day time optics)
Lens System	F1:1.26, 38mm
FOV	22°
Exit Pupil	27.5 mm
Range of Focus	20 m to infinity
Diopter Adjustment	No
Controls	Direct 7
Remote Control	Yes (Wireless)
Brightness Control	Manual
Bright Light Cut-off	Yes
Infrared Illuminator	Detachable Long Range IR Illuminator
Low Battery Indicator	Yes
Power Supply	CR123 Lithium 3V (1) or AA Alkaline 1.5V (1) or any AA or CR123 type rechargeable batteries with voltage from 1.2V to 3.2V (1)
Battery Life	up to 60 (3 V) hours / up to 30 (1.5 V) hours
Environmental Rating	Waterproof
MIL-STD-810	Yes
Operating Temperature	-40°C to +50°C
Storage Temperature	-50°C to +50°C
Dimensions	125 x 68 x 55 mm / 4.9" x 2.7" x 2.2"
Weight	0.43 kg / 0.95 kg









