

# POWERMODULE

2016 Product Brochure



5A OF TOTAL OUTPUT

FAST USB CHARGE

- FULLY INTEGRATED
- ERGONOMIC ABOVE DESK ACCESS

by Atdec

**Touchboards**  
205 Westwood Ave, Long Branch, NJ 07740  
Phone: 866-94 BOARDS (26273) / (732)-222-1511  
Fax: (732)-222-7088 | E-mail: sales@touchboards.com

# ATDEC POWER MODULE

above desk accessory with Intelligent Device Recognition technology (IDR)

## SPACE SAVING

All-in-one solution

### POWERFUL

Twin USB port with a combined output of 5A

### INTEGRATED

Works seamlessly with Visidec™ and Systema™ monitor mounts

### INTELLIGENT

Uses Intelligent Device Recognition (IDR) to provide optimal power to your mobile device up to 5A

### FAST

Charges devices **4 x FASTER** than a standard PC USB port

### DURABLE

Commercial-grade gold-plated USB connectors with 5,000 insertion lifetime

### DUAL

Two 10A general power outlets for your convenience


### GREEN

Standby power: less than 0.5W (best in its class)



### COMPATIBLE

- Apple
- Samsung
- Blackberry
- Android
- Windows



### COMPETITIVE


- Provides double the power output of competitors
- Enables full 2.4A Apple charge rate
- Charges iPhone 6S 50% faster than its own charger
- Charges Samsung devices 4x faster than competitors
- Supports any mobile device irrespective of brand/model

### CUSTOMISE

sockets for projects




Category Cable



Twin USB Data



RJ45



HDMI

### SAFE

- Surge, short circuit and overload protection
- Approved for AU, EU, CA and US safety standards

### THE ATDEC EDGE

Satisfying the demands of power-hungry devices in world-class work spaces.

<http://www.atdec.com/atdec-power-module>

# POWERMODULE

by Atdec

## TECHNICAL DATA

### FORMAT

2 x general power sockets  
1 x Twin USB charger (5A max total load)  
6.5ft (1.0mm2) long cable

### SPECIFICATIONS

USB Charging Outlets	2 x TYPE A Females
Charging Current	Maximum 5A in total
Rated Total Output Power	25W
AC Voltage Range	100-240VAC at 50/60Hz
AC Input Current (FULL LOAD)	Maximum 0.25A (240VAC)
AC Input Current (NO LOAD)	Less than 0.5mA
Environment	0 - 35°C / 85% relative humidity
Standby Power	Less than 0.05W

### COMPATIBILITY

	Ensuring optimal charging with all known USB charging compliant mobile devices
Apple iPhone/iPad	Yes - Including NEW Apple 2.4A (12W)
Android (USB BC1.2)	Yes
Samsung Tablet Charging Specification	Yes
Blackberry	Yes
Windows	Yes

### FEATURES

Protection from External Surges	Yes - (3.5kA for 8/20us Pulse)
Internal Over Temperature Protection	Self-resetting
Internal Over Voltage Protection	Self-resetting
Output Over Current Protection	Self-limiting
Short Circuit Protection	Self-resetting
USB Sockets	Gold plated for improved contact
	Specially manufactured for minimum 5000 insertions
Cable Compensation	Dynamic voltage adjustment to compensate for cable voltage loss
Internal Blue LED	

### DESIGN AND MATERIALS

- Made from ABS/PC UL94 V-0 flame retardant plastic
- Robust PU based paint, fully ROHS compliant
- Silicone pad on base to prevent slippage and protect mounting surface
- Integrated cable management wings at rear each can hold up to 2 CAT6A cables
- Can be customised to support a large range of data or power ports
- Available in multiple colours
- Compatible with SYSTEMA™ and VISIDEC™ desk mounts

### INDICATIVE CHARGING TIMES

	From 10% TO 90%
Sony Xperia Z1	2:50 hrs
iPhone 6S	1:50 hrs
Samsung Galaxy Note 10.1" Tablet	2:50 hrs
iPAD 3/4	3:75 hrs

Atdec North America  
Phone: +1 888 303 4252  
Email: [customercare@atdec.com](mailto:customercare@atdec.com)  
Web: [www.atdec.com](http://www.atdec.com)