

## 2M / 3M / 5M / 10M / 15M / 20M / 30M VGA Cable

2L-2502 / 2L-2503 / 2L-2505 / 2L-2510 / 2L-2515 / 2L-2520 / 2L-2530

The VGA Cable is designed to provide a high quality VGA connection, ideally suited for high resolution applications up to 1920 x 1200. This durably constructed VGA video cable eliminates the picture ghosting and fuzzy images, guaranteeing users the ultimate A/V experiences.



### Features

- Optimized for analog signal transmission
- VGA cable with 15-pin male input and output
- Bend Radius: 60°\*
- Outer shielded material: Al Mylar tape
- A range of cable lengths, available from 2 to 30 m
- Compatible with ATEN VGA products

Note:\* Swings 3000 times between angles of +/- 60 degrees, at a frequency of 40 times per minute

### Specifications

	2L-2502	2L-2503	2L-2505	2L-2510	2L-2515	2L-2520	2L-2530
Conductor							
Material	Tinned Copper						
Conductor Diameter	30 AWG						
Jacketed							
Material	Jacket: PVC Shielding: AL-Mylar						
Connectors							
Video	HDB-15 Male HDB-15 Male						
Cable Length	2 m	3 m	5 m	10 m	15 m	20 m	30 m

