

CS1754/CS1758

4/8-Port PS/2-USB KVM Switch

The CS1754 and CS1758 USB KVM (Keyboard, Video, Mouse) Switches are control units that allow access and control of up to 4 (CS1754) or 8 (CS1758) computers from a single USB keyboard, USB mouse, and monitor console. They can be cascaded to three levels – allowing up to 21 CS1754s to control up to 64 computers, and up to 73 CS1758s to control up to 512 computers - all from the original single console.

Although the switches use a USB keyboard and mouse for the console, they support both PS/2 and USB computers. Users have the choice of connecting the switch to a computer with PS/2 connectors or USB connectors depending on the cable used to link the switch to the computers.



















Features


- One USB console controls 4/8 computers
- Cascadable up to 3 levels control up to 64 or 512 computers
- Dual Interface supports computers with PS/2 or USB keyboards and mice
- Multiplatform support Windows 2000/XP/Vista, Linux, Mac, and Sun
- Auto PS/2 and USB interface detection
- Computer selection via front panel pushbuttons, hotkeys, and OSD
- With speaker and microphone support
- Superior video quality up to 2048 x 1536; DDC2B
- Buzzer on/off via hotkey and OSD
- Firmware upgradable
- ATEN USB ASIC inside
- Special design for easy stacking

ATEN International Co., Ltd.

• Rack-mountable in 19" system rack

Touch

205 Westwood Ave, Long Branch, NJ 07740 Phone: 866-94 BOARDS (26273) / (732)-222-1511 Fax: (732)-222-7088 | E-mail: sales@touchboards.com



Specification

	Function		CS1754	CS1758
Computer	Direct		4	8
Connections	Max		64 (via Cascade)	512 (via Cascade)
Port Selection			OSD; Hotkey; Pushbutton	
Connectors	Console Ports	Keyboard	1 x USB Type A (Female)	
		Video	1 x HDB-15 (Female)	
		Mouse	1 x USB Type A (Female)	
		Speaker	1 x Mini Stereo Jack Female (Green)	
		Microphone	1 x Mini Stereo Jack Female (Pink)	
	KVM Ports	Keyboard	4 x SPHD-15 Female	8 x SPHD-15 Female
		Video	(Yellow)	(Yellow)
		Mouse	(Tellow)	(Tellow)
		Speaker	4 x Mini Stereo Jack	8 x Mini Stereo Jack
			Female	Female
			(Green)	(Green)
		Microphone	4 x Mini Stereo Jack	8 x Mini Stereo Jack
			Female	Female
			(Pink)	(Pink)
	F/W Upgrade		1 x RJ-11 socket(Female)	
	Power		1 x DC Jack	
Switches	Port		4 x Pushbutton	8 x Pushbutton
	Reset		1 x Semi-recessed Pushbutton	
	F/W Upgrade		1 x Slide	
LEDs	On Line		4 (Orange)	8 (Orange)
	Selected		4 (Green)	8 (Green)
	Power		1 (Blue)	
Video			Up to 2048 x 1536	
Scan Interval			User Specified	l: 1 - 255 secs.
Power Consumption		DC5V, 2.75W	DC5V, 3.4W	
Environment	Operating Temp.		0 – 50°C	
	Storage Temp.		-20 – 60°C	
	Humidity		0–80% RH, Non-condensing	
	Housing		Metal	
Physical	Weight		2.64 Kg	2.72 Kg
Properties	Dimensions		43.72 x 16.10 x 4.40 cm	43.72 x 16.10 x 4.40 cm
	(L x W x H)		75.72 A 10.10 A 4.40 CIII	



Printed 05/2014 V3.0