

CS1942 / CS1944

2/4-Port USB2.0 Mini DisplayPort Dual View KVMP™ Switch

The CS1942 / CS1944 2/4-port USB 2.0 Dual View Mini DisplayPort KVMP™ Switch allows access to 2/4 computers from a single USB keyboard and USB mouse with dual displays. The KVM switches amazing functionality combines a Dual view 2/4-port Mini DisplayPort switch, with a 2-port USB 2.0 hub, and front panel USB quick charge port for mobile devices.


The CS1942 / CS1944 further improves on previous KVM designs with the latest Mini-DisplayPort and Mini-TOSLINK connectors. It also provides the capability of digital video & audio with reliable Ultra high resolution, vivid picture quality, surround sound with SPDIF connections.

The CS1942 / CS1944 is ideal for multimedia applications, and offers the ultimate in space-saving, streamlined KVM technology for the desktop.



Features

- One dual-view USB console independently and simultaneously controls two/four Mini DisplayPort computers and two USB devices
 - [USB quick charge mode \(front panel USB port\)](#)
 - Mini DisplayPort 1.1a & HDCP compatible
 - Full bass response provides a rich experience for digital surround sound systems via Mini-TOSLINK
 - [Superior video quality - enables up to 2560 x 1600 resolution and 3D displays up to 1920x1080 resolution at 120Hz](#)
 - [Nvidia 3D Vision Ready](#)
 - 2-port USB 2.0 hub built in, fully compliant with USB 2.0 specifications
 - Computer selection via front touch panel /hotkeys/ mouse*
 - Independent switching for USB peripherals, audio, and KVM focus
 - Keyboard and Mouse support emulation and bypass
 - Power on Detection
 - Mac keyboard support and emulation**
 - Multilingual keyboard mapping - Supports English, Japanese, and French keyboards
 - Multiplatform support- Windows, Linux and Mac
- * Mouse port switching is only workable under mouse emulation mode. For 3-key USB wheel mouse only.
- **PC keyboard combinations emulate Mac keyboards.
- **Mac keyboards only work with their own computers.



Specification

Function		CS1942	CS1944
Computer Connections		2	4
Connectors	Port Selection	Touch Panel Switches, Hotkey, Mouse*	
	Console Ports	Keyboard	1 x USB Type A Female (Black, rear panel)
		Video	2 x Mini DisplayPort Female (Black)
		Mouse	1 x USB Type A Female (Black, rear panel)
		Speaker	1 x Mini TOSLINK Jack Female (Black)
			1 x 3.5mm Audio Jack Female (Green)
		Microphone	1 x Mini TOSLINK Jack Female (Black)
			1 x 3.5mm Audio Jack Female (Pink)
	KVM Ports	Keyboard / Mouse	2 x USB Type B Female (White)
		Video	4 x Mini DisplayPort Female (Black)
Switches	Speaker	2 x Mini TOSLINK Jack Female (Black)	4 x Mini TOSLINK Jack Female (Black)
	Microphone	2 x Mini TOSLINK Jack Female (Black)	4 x Mini TOSLINK Jack Female (Black)
	USB 2.0 Hub	2 x USB Type A Female (White; 1 x Front panel, 1 x Rear panel)	
	Power	1 x DC Jack	
LEDs	Selected	3 x Point Touch Panel	5 x Point Touch Panel
	KVM	2 (Orange)	4 (Orange)
	Audio	2 (Green)	4 (Green)
	USB	2 (Green)	4 (Green)
Emulation	Keyboard	USB	
	Mouse	USB	
Environment	Video	DP: 2560 x 1600 resolution @ 60Hz, or 3D Display 1920 x 1080 resolution @ 120Hz	
	Scan Interval	1 - 99 seconds (Default: 5 seconds)	
	Power Consumption	DC 5.3V, 6.68 W	DC5.3V, 8.63W
Physical Properties	Operation Temp.	0-50°C	
	Storage Temp.	-20-60°C	
	Humidity	0-80% RH, Non-condensing	
	Housing	Plastic	
Weight	Weight	0.56 kg	0.61 kg
	Dimension (L x W x H)	19.70 x 19.70 x 4.47 cm	19.70 x 19.70 x 4.47 cm

* Product specifications and appearance are subject to change without notice.

