

# KA7230



- PS/2-USB Console Module
- The KA7230 Console Module offers secure access to the servers in a Matrix KVM Switch (KM0932/KM0532) from a PS/2 or USB console (monitor, keyboard, and mouse) up to 300 meters away. It provides an extra computer port for integration with a computer workstation, enabling users to seamlessly switch between the local computer and the servers in the Matrix KVM Switch. The KA7230 also features an intuitive graphical user interface, the Graphical OSD, with easy-to-use menus and icons that enable easy access and efficient management. KA7230 has a built-in RS-232 port. Administrators can establish a serial terminal login to the Console Module in order to control the KVM port access for all consoles connected to switch - any console can be assigned to access any KVM port from a single interface point. This function is extremely useful in large data centers where the display of all the consoles can be projected onto a wall for easy viewing of all operations, and the entire installation can be monitored on a port-by-port basis.



## Features

- One Combo Graphic Console Module can control a local computer and a matrix KVM switch (KM0932/KM0532)
- Supports PS/2 and USB keyboards and mice(Console)
- Switch between your workstation computer and the matrix KVM switch
- Graphical OSD-intuitive, easy-to-use graphical On Screen Display to manage servers
- RS-232 port login support permits an administrator to control the KVM port access for all consoles connected to switch - any console can be assigned to access any KVM port from a single interface point
- Connects to matrix KVM switch via Cat 5e/6apple cable
- Superior video quality - 1280 x 1024 @ 60 Hz for up to 300 m

- Manual video gain control for fine tuning
- Convenient computer selection via intuitive hotkey combinations or graphical OSD menus
- Firmware upgradeable

## Specification

Computer Connections		1	
Console Connections		1	
Port Selection		GUI, Hotkey	
Connectors	Console Port	Keyboard	1 x USB Type A Female (White) 1 x 6-pin Mini-DIN Female (Purple)
		Video	1 x HDB-15 Female (Blue)
		Mouse	1 x USB Type A Female (White) 1 x 6-pin Mini-DIN Female (Green)
	Local Computer KVM Port		1 x SPHD-17 Female (Yellow)
	KVM Switch Ports		2 x RJ-45 Female
	RS-232		1 x DB-9 Male (Black)
	Power		1 x DC Jack
	Switches	Local/Remote	
F/W Upgrade		1 x Slide	
Video Gain Adjustment		2 x Pushbutton	
LEDs	Power		1 (Blue)
	Online		1 (Green)
	Local		1 (Orange)
	Remote		1 (Orange)
Emulation	Keyboard / Mouse		PS/2; USB (PC, Sun, Mac)
Video		1280 x 1024 @ 60Hz (300m max.)	
Scan Interval		1-240 Seconds	
Power Consumption		DC5.3V,6.5W	
Environment	Operating Temperature		0 - 50°C
	Storage Temperature		-20 - 60°C
	Humidity		0-80% RH, Non-condensing
Physical Properties	Housing		Metal
	Weight		1.22 kg
	Dimensions ( L x W x H )		22.71x17.15x5.48cm

## Diagram



### **ATEN International Co., Ltd.**

3F, No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan  
Phone: 886-2-8692-6789 Fax: 886-2-8692-6767  
www.aten.com E-mail: marketing@aten.com



© Copyright 2014 ATEN® International Co., Ltd.  
ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.  
All rights reserved. All other trademarks are the property of their  
respective owners.