

AVOCOR E SERIES 86" DISPLAY AVE-8630



The cutting-edge lightweight LED technology of the Avocor E series 86" interactive display combines first-to-market 2mm optically bonded glass with a 4K IR interactive display. The E series delivers ultra-fast 20-points of touch using Avocor Intelligent Touch, the functionality to insert an OPS unit as well as the Connect and Control bar at the bottom of the screen.



2mm optically bonded glass on a 4K IR display The E series integrates 2mm optically bonded glass into a 4K IR display producing a visually stunning interactive experience with increased brightness and contrast. With no gap between the glass and the display, parallax is eliminated giving users a pixelperfect touch experience and a superior accuracy pen performance.



Pen Aware functionality with a fine-tip passive pen Experience superb pen

performance while inking and writing with the 3mm tipped passive pen. Avocor Intelligent Touch can precisely recognize the size of the object touching it differentiating between a pen, finger or palm. Utilize the popular Microsoft 'in-app' inking features within your day-to-day applications including Whiteboard and PowerPoint.



Connect and Control bar The Connect and Control bar brings simplicity to the front of the display by providing the ability to easily switch input sources without having to use the remote control. You can even access content from USB drivers using the front facing USB connections as well as connecting guest devices easily through the HDMI & USB Touch connection. The E series also includes 30W of front facing speakers built with custom housing to deliver an increased crisp audio experience.



Ultra-fast 20-points of touch Encourage collaboration with ultra-fast 20-points of touch using Avocor Intelligent Touch. Immediately experience the superior writing capabilities and benefits of simultaneous annotation. The display has also been optimized for Windows 10 by including the edge swipe functionality, while the anti-glare and anti-fingerprint glass provides an exceptionally smooth and natural writing experience.



Lightweight and slimline design The Avocor E series represents the very latest in lightweight LED technology with an exceptionally thin bezel, creating an aesthetically pleasing finish on a beautifully slim display.

Connectivity Options The E series boasts a range of digital connectivity options to connect 3rd party devices. These include 3 x HDMI, 1 x DisplayPort, 1 x HDMI Out, 1 x USB Hub and room control. The HDMI Out connection is ideal for dual display set up and a room automation system can be used via the RS-232 port.

OPS slot functionality

Additional functionalities can be added onto this display with the OPS slot that complies with Intel's international standard for Slot-in PCs and works seamlessly with Avocor's range of OPS units. The OPS slot also enables users to add a PC which conforms to their own settings for firewall and security.





DISPLAY

Puilt in speakers	z x 15w - lolwala lacing
	2 x 15W - forward facing
AUDIO	
Supporting operating system	Windows 7/8/10, Mac OS, Linux
Glass	2mm optically bonded, anti-glare, anti-fingerprint
Touch	Up to 20 point Avocor Intelligent Touch
Interface	5 x USB-A
Interface	
TOUCH SYSTEM	
TOUCH SYSTEM	
	TA DIGHT, STURIOUU, JULT & UJUL
Light settings	4 x Bright, Standard, Soft & User
Light settings	4 x Bright, Standard, Soft & User
	Yes
Freeze	Yes
Light settings	
ight settings	
ight settings	
ight settings	4 x Bright, Standard, Soft & User
Light settings	4 x Bright, Standard, Soft & User
Light settings	4 x Bright, Standard, Soft & User
Light settings	4 x Bright, Standard, Soft & User
Light settings	4 x bigni, standard, son & User
OUCH SYSTEM	
OUCH SYSTEM	
OUCH SYSTEM	
nterface	5 x 1/SR_A
nterface	5 x USB-A
nenuce	
Iouch	Up to 20 point Avocor Intelligent Touch
Iouch	Up to 20 point Avocor Intelligent Touch
Glass	2mm optically bonded, anti-glare, anti-fingerprint
Supporting operating system	
supporting operating system	Windows 7/8/10, Mac OS, Linux
AUDIO	
	2 x 15W forward facing
	2 x 15W - forward facing
Built-in speakers	
Built-in speakers	
PHYSICAL SPECIFICATIONS	
PHYSICAL SPECIFICATIONS	2018 x 100 x 1211 mm 1 79.45 x 3.94 x 47.68 in
PHYSICAL SPECIFICATIONS	2018 x 100 x 1211 mm 79.45 x 3.94 x 47.68 in
PHYSICAL SPECIFICATIONS Product dimensions (W x D x H)	
PHYSICAL SPECIFICATIONS Product dimensions (W x D x H)	2018 x 100 x 1211 mm 79.45 x 3.94 x 47.68 in 2150 x 310 x 1320 mm 84.65 x 12.20 x 51.97 in
PHYSICAL SPECIFICATIONS Product dimensions (W x D x H) Shipping dimensions (W x D x H)	2150 x 310 x 1320 mm 84.65 x 12.20 x 51.97 in
PHYSICAL SPECIFICATIONS Product dimensions (W x D x H) Shipping dimensions (W x D x H)	
PHYSICAL SPECIFICATIONS Product dimensions (W x D x H) Shipping dimensions (W x D x H)	2150 x 310 x 1320 mm 84.65 x 12.20 x 51.97 in Net: 62 kg 136.69 lbs / Gross: 82.5 kg 181.88 lbs
PHYSICAL SPECIFICATIONS Product dimensions (W x D x H) Shipping dimensions (W x D x H) Weight	2150 x 310 x 1320 mm 84.65 x 12.20 x 51.97 in Net: 62 kg 136.69 lbs / Gross: 82.5 kg 181.88 lbs
PHYSICAL SPECIFICATIONS Product dimensions (W x D x H) Shipping dimensions (W x D x H) Weight	2150 x 310 x 1320 mm 84.65 x 12.20 x 51.97 in
PHYSICAL SPECIFICATIONS Product dimensions (W x D x H) Shipping dimensions (W x D x H) Weight Wall mount VESA	2150 x 310 x 1320 mm 84.65 x 12.20 x 51.97 in Net: 62 kg 136.69 lbs / Gross: 82.5 kg 181.88 lbs 800 x 400 mm 31.50 x 15.75 in
PHYSICAL SPECIFICATIONS Product dimensions (W x D x H) Shipping dimensions (W x D x H) Weight Wall mount VESA	2150 x 310 x 1320 mm 84.65 x 12.20 x 51.97 in Net: 62 kg 136.69 lbs / Gross: 82.5 kg 181.88 lbs
PHYSICAL SPECIFICATIONS Product dimensions (W x D x H) Shipping dimensions (W x D x H) Weight Wall mount VESA	2150 x 310 x 1320 mm 84.65 x 12.20 x 51.97 in Net: 62 kg 136.69 lbs / Gross: 82.5 kg 181.88 lbs 800 x 400 mm 31.50 x 15.75 in 3840 x 2160 @ 60Hz
PHYSICAL SPECIFICATIONS Product dimensions (W x D x H) Shipping dimensions (W x D x H) Weight Wall mount VESA OPS slot	2150 x 310 x 1320 mm 84.65 x 12.20 x 51.97 in Net: 62 kg 136.69 lbs / Gross: 82.5 kg 181.88 lbs 800 x 400 mm 31.50 x 15.75 in
PHYSICAL SPECIFICATIONS Product dimensions (W x D x H) Shipping dimensions (W x D x H) Weight Wall mount VESA OPS slot	2150 x 310 x 1320 mm 84.65 x 12.20 x 51.97 in Net: 62 kg 136.69 lbs / Gross: 82.5 kg 181.88 lbs 800 x 400 mm 31.50 x 15.75 in 3840 x 2160 @ 60Hz
PHYSICAL SPECIFICATIONS Product dimensions (W x D x H) Shipping dimensions (W x D x H) Weight Wall mount VESA OPS slot Handles	2150 x 310 x 1320 mm 84.65 x 12.20 x 51.97 in Net: 62 kg 136.69 lbs / Gross: 82.5 kg 181.88 lbs 800 x 400 mm 31.50 x 15.75 in 3840 x 2160 @ 60Hz
PHYSICAL SPECIFICATIONS Product dimensions (W x D x H) Shipping dimensions (W x D x H) Weight Wall mount VESA OPS slot Handles	2150 x 310 x 1320 mm 84.65 x 12.20 x 51.97 in Net: 62 kg 136.69 lbs / Gross: 82.5 kg 181.88 lbs 800 x 400 mm 31.50 x 15.75 in 3840 x 2160 @ 60Hz
Built-in speakers PHYSICAL SPECIFICATIONS Product dimensions (W x D x H) Shipping dimensions (W x D x H) Weight Wall mount VESA OPS slot Handles POWER	2150 x 310 x 1320 mm 84.65 x 12.20 x 51.97 in Net: 62 kg 136.69 lbs / Gross: 82.5 kg 181.88 lbs 800 x 400 mm 31.50 x 15.75 in 3840 x 2160 @ 60Hz
PHYSICAL SPECIFICATIONS Product dimensions (W x D x H) Shipping dimensions (W x D x H) Weight Wall mount VESA OPS slot Handles POWER	2150 x 310 x 1320 mm 84.65 x 12.20 x 51.97 in Net: 62 kg 136.69 lbs / Gross: 82.5 kg 181.88 lbs 800 x 400 mm 31.50 x 15.75 in 3840 x 2160 @ 60Hz 4
PHYSICAL SPECIFICATIONS Product dimensions (W x D x H) Shipping dimensions (W x D x H) Weight Wall mount VESA OPS slot Handles POWER	2150 x 310 x 1320 mm 84.65 x 12.20 x 51.97 in Net: 62 kg 136.69 lbs / Gross: 82.5 kg 181.88 lbs 800 x 400 mm 31.50 x 15.75 in 3840 x 2160 @ 60Hz
PHYSICAL SPECIFICATIONS Product dimensions (W x D x H) Shipping dimensions (W x D x H) Weight Wall mount VESA OPS slot Handles POWER Power supply	2150 x 310 x 1320 mm 84.65 x 12.20 x 51.97 in Net: 62 kg 136.69 lbs / Gross: 82.5 kg 181.88 lbs 800 x 400 mm 31.50 x 15.75 in 3840 x 2160 @ 60Hz 4 AC100-240V (Worldwide)50/60Hz
PHYSICAL SPECIFICATIONS Product dimensions (W x D x H) Shipping dimensions (W x D x H) Weight Wall mount VESA OPS slot Handles POWER Power supply	2150 x 310 x 1320 mm 84.65 x 12.20 x 51.97 in Net: 62 kg 136.69 lbs / Gross: 82.5 kg 181.88 lbs 800 x 400 mm 31.50 x 15.75 in 3840 x 2160 @ 60Hz 4
PHYSICAL SPECIFICATIONS Product dimensions (W x D x H) Shipping dimensions (W x D x H) Weight Wall mount VESA OPS slot Handles POWER Power supply Maximum power consumption	2150 x 310 x 1320 mm 84.65 x 12.20 x 51.97 in Net: 62 kg 136.69 lbs / Gross: 82.5 kg 181.88 lbs 800 x 400 mm 31.50 x 15.75 in 3840 x 2160 @ 60Hz 4 AC100-240V (Worldwide)50/60Hz <450W
PHYSICAL SPECIFICATIONS Product dimensions (W x D x H) Shipping dimensions (W x D x H) Weight Wall mount VESA OPS slot Handles POWER Power supply	2150 x 310 x 1320 mm 84.65 x 12.20 x 51.97 in Net: 62 kg 136.69 lbs / Gross: 82.5 kg 181.88 lbs 800 x 400 mm 31.50 x 15.75 in 3840 x 2160 @ 60Hz 4 AC100-240V (Worldwide)50/60Hz <450W
PHYSICAL SPECIFICATIONS Product dimensions (W x D x H) Shipping dimensions (W x D x H) Weight Wall mount VESA OPS slot Handles POWER Power supply Maximum power consumption	2150 x 310 x 1320 mm 84.65 x 12.20 x 51.97 in Net: 62 kg 136.69 lbs / Gross: 82.5 kg 181.88 lbs 800 x 400 mm 31.50 x 15.75 in 3840 x 2160 @ 60Hz 4 AC100-240V (Worldwide)50/60Hz
PHYSICAL SPECIFICATIONS Product dimensions (W x D x H) Shipping dimensions (W x D x H) Weight Wall mount VESA OPS slot Handles POWER Power supply Maximum power consumption Standby	2150 x 310 x 1320 mm 84.65 x 12.20 x 51.97 in Net: 62 kg 136.69 lbs / Gross: 82.5 kg 181.88 lbs 800 x 400 mm 31.50 x 15.75 in 3840 x 2160 @ 60Hz 4 AC100-240V (Worldwide)50/60Hz <450W
PHYSICAL SPECIFICATIONS Product dimensions (W x D x H) Shipping dimensions (W x D x H) Weight Wall mount VESA OPS slot Handles POWER Power supply Maximum power consumption Standby	2150 x 310 x 1320 mm 84.65 x 12.20 x 51.97 in Net: 62 kg 136.69 lbs / Gross: 82.5 kg 181.88 lbs 800 x 400 mm 31.50 x 15.75 in 3840 x 2160 @ 60Hz 4 AC100-240V (Worldwide)50/60Hz <450W
PHYSICAL SPECIFICATIONS Product dimensions (W x D x H) Shipping dimensions (W x D x H) Weight Wall mount VESA OPS slot Handles POWER Power supply Maximum power consumption Standby ENVIRONMENTAL	2150 x 310 x 1320 mm 84.65 x 12.20 x 51.97 in Net: 62 kg 136.69 lbs / Gross: 82.5 kg 181.88 lbs 800 x 400 mm 31.50 x 15.75 in 3840 x 2160 @ 60Hz 4 AC100-240V (Worldwide)50/60Hz <450W
PHYSICAL SPECIFICATIONS Product dimensions (W x D x H) Shipping dimensions (W x D x H) Weight Wall mount VESA OPS slot Handles POWER Power supply Maximum power consumption Standby ENVIRONMENTAL	2150 x 310 x 1320 mm 84.65 x 12.20 x 51.97 in Net: 62 kg 136.69 lbs / Gross: 82.5 kg 181.88 lbs 800 x 400 mm 31.50 x 15.75 in 3840 x 2160 @ 60Hz 4 AC100-240V (Worldwide)50/60Hz <450W ≦0.5 W
PHYSICAL SPECIFICATIONS Product dimensions (W x D x H) Shipping dimensions (W x D x H) Weight Wall mount VESA OPS slot Handles POWER Power supply Maximum power consumption Standby ENVIRONMENTAL	2150 x 310 x 1320 mm 84.65 x 12.20 x 51.97 in Net: 62 kg 136.69 lbs / Gross: 82.5 kg 181.88 lbs 800 x 400 mm 31.50 x 15.75 in 3840 x 2160 @ 60Hz 4 AC100-240V (Worldwide)50/60Hz <450W
PHYSICAL SPECIFICATIONS Product dimensions (W x D x H) Shipping dimensions (W x D x H) Weight Wall mount VESA OPS slot Handles POWER Power supply Maximum power consumption Standby ENVIRONMENTAL Operating temperature	2150 x 310 x 1320 mm 84.65 x 12.20 x 51.97 in Net: 62 kg 136.69 lbs / Gross: 82.5 kg 181.88 lbs 800 x 400 mm 31.50 x 15.75 in 3840 x 2160 @ 60Hz 4 AC100-240V (Worldwide)50/60Hz <450W ≦0.5 W 0 °C ~ 40 °C
PHYSICAL SPECIFICATIONS Product dimensions (W x D x H) Shipping dimensions (W x D x H) Weight Wall mount VESA OPS slot Handles POWER Power supply Maximum power consumption Standby ENVIRONMENTAL	2150 x 310 x 1320 mm 84.65 x 12.20 x 51.97 in Net: 62 kg 136.69 lbs / Gross: 82.5 kg 181.88 lbs 800 x 400 mm 31.50 x 15.75 in 3840 x 2160 @ 60Hz 4 AC100-240V (Worldwide)50/60Hz <450W ≦0.5 W
PHYSICAL SPECIFICATIONS Product dimensions (W x D x H) Shipping dimensions (W x D x H) Weight Wall mount VESA OPS slot Handles POWER Power supply Maximum power consumption Standby ENVIRONMENTAL Operating temperature Storage temperature	2150 x 310 x 1320 mm 84.65 x 12.20 x 51.97 in Net: $62 \text{ kg} 136.69 \text{ lbs / Gross: } 82.5 \text{ kg} 181.88 \text{ lbs}$ 800 x 400 mm 31.50 x 15.75 in 3840 x 2160 @ 60Hz 4 AC100-240V (Worldwide)50/60Hz <450W $\leq 0.5 \text{ W}$ 0 °C ~ 40 °C -20 °C ~ 60 °C
PHYSICAL SPECIFICATIONS Product dimensions (W x D x H) Shipping dimensions (W x D x H) Weight Wall mount VESA OPS slot Handles POWER Power supply Maximum power consumption Standby ENVIRONMENTAL Operating temperature Storage temperature	2150 x 310 x 1320 mm 84.65 x 12.20 x 51.97 in Net: 62 kg 136.69 lbs / Gross: 82.5 kg 181.88 lbs 800 x 400 mm 31.50 x 15.75 in 3840 x 2160 @ 60Hz 4 AC100-240V (Worldwide)50/60Hz <450W ≦0.5 W 0 °C ~ 40 °C
PHYSICAL SPECIFICATIONS Product dimensions (W x D x H) Shipping dimensions (W x D x H) Weight Wall mount VESA OPS slot Handles POWER POWER Power supply Maximum power consumption Standby ENVIRONMENTAL Operating temperature Storage temperature Humidity	2150 x 310 x 1320 mm 84.65 x 12.20 x 51.97 in Net: $62 \text{ kg} 136.69 \text{ lbs / Gross: } 82.5 \text{ kg} 181.88 \text{ lbs}$ 800 x 400 mm 31.50 x 15.75 in 3840 x 2160 @ 60Hz 4 AC100-240V (Worldwide)50/60Hz <450W $\leq 0.5 \text{ W}$ 0 °C ~ 40 °C -20 °C ~ 60 °C
PHYSICAL SPECIFICATIONS Product dimensions (W x D x H) Shipping dimensions (W x D x H) Weight Wall mount VESA OPS slot Handles POWER POWER Power supply Maximum power consumption Standby ENVIRONMENTAL Operating temperature Storage temperature Humidity	2150 x 310 x 1320 mm 84.65 x 12.20 x 51.97 in Net: $62 \text{ kg} 136.69 \text{ lbs / Gross: } 82.5 \text{ kg} 181.88 \text{ lbs}$ 800 x 400 mm 31.50 x 15.75 in 3840 x 2160 @ 60Hz 4 AC100-240V (Worldwide)50/60Hz <450W $\leq 0.5 \text{ W}$ 0 °C ~ 40 °C -20 °C ~ 60 °C
PHYSICAL SPECIFICATIONS Product dimensions (W x D x H) Shipping dimensions (W x D x H) Weight Wall mount VESA OPS slot Handles POWER Power supply Maximum power consumption Standby ENVIRONMENTAL Operating temperature Storage temperature	2150 x 310 x 1320 mm 84.65 x 12.20 x 51.97 in Net: $62 \text{ kg} 136.69 \text{ lbs / Gross: } 82.5 \text{ kg} 181.88 \text{ lbs}$ 800 x 400 mm 31.50 x 15.75 in 3840 x 2160 @ 60Hz 4 AC100-240V (Worldwide)50/60Hz <450W $\leq 0.5 \text{ W}$ 0 °C ~ 40 °C -20 °C ~ 60 °C
PHYSICAL SPECIFICATIONS Product dimensions (W x D x H) Shipping dimensions (W x D x H) Weight Wall mount VESA OPS slot Handles POWER POWER Power supply Maximum power consumption Standby ENVIRONMENTAL Operating temperature Storage temperature Humidity	2150 x 310 x 1320 mm 84.65 x 12.20 x 51.97 in Net: $62 \text{ kg} 136.69 \text{ lbs / Gross: } 82.5 \text{ kg} 181.88 \text{ lbs}$ 800 x 400 mm 31.50 x 15.75 in 3840 x 2160 @ 60Hz 4 AC100-240V (Worldwide)50/60Hz <450W $\leq 0.5 \text{ W}$ 0 °C ~ 40 °C -20 °C ~ 60 °C
PHYSICAL SPECIFICATIONS Product dimensions (W x D x H) Shipping dimensions (W x D x H) Weight Wall mount VESA OPS slot Handles POWER POWER Power supply Maximum power consumption Standby ENVIRONMENTAL Operating temperature Storage temperature Humidity	2150 x 310 x 1320 mm 84.65 x 12.20 x 51.97 in Net: 62 kg 136.69 lbs / Gross: 82.5 kg 181.88 lbs 800 x 400 mm 31.50 x 15.75 in 3840 x 2160 @ 60Hz 4 AC100-240V (Worldwide)50/60Hz <450W ≤ 0.5 W 0 °C ~ 40 °C -20 °C ~ 60 °C 20 % ~ 80%
PHYSICAL SPECIFICATIONS Product dimensions (W x D x H) Shipping dimensions (W x D x H) Weight Wall mount VESA OPS slot Handles POWER POWER Power supply Maximum power consumption Standby ENVIRONMENTAL Operating temperature Storage temperature Humidity	2150 x 310 x 1320 mm 84.65 x 12.20 x 51.97 in Net: 62 kg 136.69 lbs / Gross: 82.5 kg 181.88 lbs 800 x 400 mm 31.50 x 15.75 in 3840 x 2160 @ 60Hz 4 AC100-240V (Worldwide)50/60Hz <450W ≤ 0.5 W 0° C ~ 40 °C -20 °C ~ 60 °C 20% ~ 80% 1 x Remote control & batteries, 2 x 3mm passive touch pen, AC power cords, 2 x USB cable (3m 118.1 inches).
PHYSICAL SPECIFICATIONS Product dimensions (W x D x H) Shipping dimensions (W x D x H) Weight Wall mount VESA OPS slot Handles POWER Power supply Maximum power consumption Standby ENVIRONMENTAL Operating temperature Storage temperature Humidity	2150 x 310 x 1320 mm 84.65 x 12.20 x 51.97 in Net: 62 kg 136.69 lbs / Gross: 82.5 kg 181.88 lbs 800 x 400 mm 31.50 x 15.75 in 3840 x 2160 @ 60Hz 4 AC100-240V (Worldwide)50/60Hz <450W ≤ 0.5 W 0 °C ~ 40 °C -20 °C ~ 60 °C 20 % ~ 80%
PHYSICAL SPECIFICATIONS Product dimensions (W x D x H) Shipping dimensions (W x D x H) Weight Wall mount VESA OPS slot Handles POWER Power supply Maximum power consumption Standby ENVIRONMENTAL Operating temperature Storage temperature Humidity	2150 x 310 x 1320 mm 84.65 x 12.20 x 51.97 in Net: 62 kg 136.69 lbs / Gross: 82.5 kg 181.88 lbs 800 x 400 mm 31.50 x 15.75 in 3840 x 2160 @ 60Hz 4 AC100-240V (Worldwide)50/60Hz <450W ≤ 0.5 W 0° C ~ 40 °C -20 °C ~ 60 °C 20% ~ 80% 1 x Remote control & batteries, 2 x 3mm passive touch pen, AC power cords, 2 x USB cable (3m 118.1 inches).
PHYSICAL SPECIFICATIONS Product dimensions (W x D x H) Shipping dimensions (W x D x H) Weight Wall mount VESA OPS slot Handles POWER Power supply Maximum power consumption Standby ENVIRONMENTAL Operating temperature Storage temperature Humidity	2150 x 310 x 1320 mm 84.65 x 12.20 x 51.97 in Net: 62 kg 136.69 lbs / Gross: 82.5 kg 181.88 lbs 800 x 400 mm 31.50 x 15.75 in 3840 x 2160 @ 60Hz 4 AC100-240V (Worldwide)50/60Hz <450W ≤ 0.5 W 0° C ~ 40 °C -20 °C ~ 60 °C 20% ~ 80% 1 x Remote control & batteries, 2 x 3mm passive touch pen, AC power cords, 2 x USB cable (3m 118.1 inches).
PHYSICAL SPECIFICATIONS Product dimensions (W x D x H) Shipping dimensions (W x D x H) Weight Wall mount VESA OPS slot Handles POWER Power supply Maximum power consumption Standby ENVIRONMENTAL Operating temperature Storage temperature Humidity WHAT'S IN THE BOX	2150 x 310 x 1320 mm 84.65 x 12.20 x 51.97 in Net: 62 kg 136.69 lbs / Gross: 82.5 kg 181.88 lbs 800 x 400 mm 31.50 x 15.75 in 3840 x 2160 @ 60Hz 4 AC100-240V (Worldwide)50/60Hz <450W ≤ 0.5 W 0° C ~ 40 °C -20 °C ~ 60 °C 20% ~ 80% 1 x Remote control & batteries, 2 x 3mm passive touch pen, AC power cords, 2 x USB cable (3m 118.1 inches).
PHYSICAL SPECIFICATIONS Product dimensions (W x D x H) Shipping dimensions (W x D x H) Weight Wall mount VESA DPS slot Handles POWER Power supply Maximum power consumption Standby ENVIRONMENTAL Operating temperature Storage temperature Humidity	2150 x 310 x 1320 mm 84.65 x 12.20 x 51.97 in Net: 62 kg 136.69 lbs / Gross: 82.5 kg 181.88 lbs 800 x 400 mm 31.50 x 15.75 in 3840 x 2160 @ 60Hz 4 AC100-240V (Worldwide)50/60Hz <450W ≤ 0.5 W 0° C ~ 40 °C -20 °C ~ 60 °C 20% ~ 80% 1 x Remote control & batteries, 2 x 3mm passive touch pen, AC power cords, 2 x USB cable (3m 118.1 inches).

Details are subject to change without notice. All other logos and trademarks acknowledged. E&OE. Please note up to 20-point touch in PC mode with Windows 7/8/10, Mac OSX and Linux only supports single touch. Version date: 03/11/2020

