


# Data sheet

## 40 MHz Dual Channel Analog Oscilloscope Model 1541D



B&K Precision's model 1541D is a high performance oscilloscope with many features at a low cost. This oscilloscope is built by and backed by B&K Precision, a company that has been selling reliable, durable, value priced test instruments for over 50 years.

- 5mV/div sensitivity
- 10 calibrated V/Div ranges
- Video sync separators
- X10 sweep magnification
- cUL certified



Specifications	1541D
<b>VERTICAL AMPLIFIERS (CH 1 and CH 2)</b>	
Sensitivity	5 mV/div to 5 V/div, 1 mV/div, with X5 gain
Accuracy	5 mV/div to 5 V/div, $\pm 3\%$ (X5 gain), $\pm 5\%$
Input Impedance	1M $\Omega$ $\pm 2\%$ , 25pF $\pm 10\%$
Frequency Response	DC to 40 MHz (-3dB), DC to 7 MHz (-3dB) at X5 gain
Rise Time	8.8 ns (Overshoot $\leq 5\%$ )
Operating Modes	CH 1; CH 2; DUAL; Alternate/Chop; ADD
Chop Frequency	Approximately 250kHz
Max Input	400 V (DC + AC peak)
<b>SWEEP SYSTEM</b>	
Sweep Speed	0.2 $\mu$ s/div to 0.2 s/div in 1-2-5 sequence; 20 steps, vernier control provided
Accuracy	$\pm 3\%$
Sweep Magnification	10x
Hold Off Time	5:1 Continuously variable
<b>TRIGGERING</b>	
Trigger Modes	Auto, Norm
Trigger Source	Ch 1, CH 2, LINE, EXT, ALT
Trigger Coupling	AC, TV-V, TV-H, NORM
<b>HORIZONTAL AMPLIFIER (Input through EXT TRIG)</b>	
X-Y Mode	CH1: Y axis, CH2: X axis
Sensitivity	Same as vertical CH1
Accuracy	Y axis $\pm 3\%$ , X axis $\pm 6\%$
Input Impedance	same as vertical CH1
Frequency Response	DC to 1MHz (-3dB)
<b>CRT</b>	
Display Area	6 inches diagonal, rectangular screen with internal graticule 8 x 10 div (1 div = 1 cm)
Accelerating Voltage	12 kV
Trace Rotation	Front panel adjustable
Phosphor	B31
<b>OTHER SPECIFICATIONS</b>	
Calibrating Voltage	1kHz positive square wave. 2Vp-p, $\pm 3\%$
<b>ENVIRONMENT</b>	
Within Specified Accuracy	50° to 95°F (10° to 35°C), $\leq 85\%$ RH
Full Operation	32° to 104°F (0° to 40°C), $\leq 85\%$ RH
Storage	-4° to 158°F (-20° to +70°C)
Power Requirements	100/120/220/240 V $\pm 10\%$ , 50/60 Hz, approximately 38W
Dimensions (HxWxD)	12.8 x 15.7 x 5.2" (324 x 398 x 132 mm)
Weight	16.8 lbs. (7.6 kg)
<b>THREE YEAR WARRANTY</b>	
Supplied Accessories	Instruction Manual, Two PR-33A x1/x10 Probes or equivalent, AC Power Cord, Spare Fuse
Optional Accessories	PR-32A Demodulator Probe, PR-37A x1/x10/REF Probe, PR-100A x100 Probe, PR-55 High Voltage x1000 Probe, LC-210A Carrying Case